1-Phase AC Filters / DC Filters https://www.schurter.com /PG84

### AC Filter 3-Stage, Very High Broad Band Attenuation

## FMW-150 (200)



The same image is used for FMW-200

#### Description

- Line-filter in standard version
- 3 stages
- very high attenuation, broadband

#### See below: Approvals and Compliances

## Characteristics

- Designed for highest demands
- High attenuation at maximum resp. asymmetric load independent from the line impedance
- For standard and industrial applications
- Suitable for use in equipment according to IEC/UL 62368-1

#### References

Alternative: Standard version Last order date: 15.12.2023

#### Weblinks

pdf data sheet, html datasheet, General Product Information, Approvals, Distributor-Stock-Check, Detailed request for product, Microsite

Technical Data			
Ratings IEC	4 - 30 A @ Ta 40 °C / 250 VAC; 50 Hz	Line Filter	Industrial version, IEC 60939, UL 1283,
Ratings UL/CSA	4 - 30 A @ Ta 40 °C / 125 VAC; 60 Hz		CSA C22.2 no. 8
Leakage Current	industrial < 1.5 mA (250 V / 60 Hz)		Technical Details
Dielectric Strength	> 1.7 kVDC between L-N > 2.7 kVDC between L/N-PE Test voltage (2 sec)	MTBF	> 200'000h acc. to MIL-HB-217 F
Allowable Operation Tempe- rature	-25 °C to 100 °C		
Climatic Category	25/100/21 acc. to IEC 60068-1		
Protection Class	Suitable for appliances with protection class I acc. to IEC 61140		
Terminal	Screw		
Material	Metal		

#### **Approvals and Compliances**

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

## Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type: FMW-150 (200)

Approval Logo	Certificates	Certification Body	Description
<b>EX</b> 10	VDE Approvals	VDE	Certificate Number: 40004673
c <b>Ru</b> ®us	UL Approvals	UL	UR File Number: E72928

## FMW-150 (200)

Design	Standard	Description
Designed according to	IEC 60939	Passive filters for suppressing electromagnetic interference
Designed according to	UL 1283	Electromagnetic interference filters
Designed according to	CSA C22.2 no. 8	Electromagnetic interference (EMI) filters
ards		
where the product can be used		
Design	Standard	Description
Suitable for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements
s with following Guide Lines		
Details	Initiator	Description
CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
UKCA declaration of conformity	SCHURTER AG	The UKCA marking declares that the product complies with the applicable requirements laid down in the British Amendment of Regulation (EC) 765/2008.
RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.
	Designed according to Designed according to Designed according to Designed according to ards swhere the product can be used Design Suitable for applications acc. Swith following Guide Lines Details CE declaration of conformity UKCA declaration of conformity RoHS China RoHS	Designed according toIEC 60939Designed according toUL 1283Designed according toCSA C22.2 no. 8ardsStandardswhere the product can be usedDesignDesignStandardSuitable for applications acc.IEC/UL 62368-1Swith following Guide LinesInitiatorCE declaration of conformitySCHURTER AGUKCA declaration of conformitySCHURTER AGRoHSSCHURTER AGChina RoHSSCHURTER AG



# FMW-150 (200)

 $50\Omega$  common mode

- - - 50 $\Omega$  differential mode

## Diagrams





1) Line 2) Load

#### **Attenuation Loss**



## All Variants

Rated Cur- rent [A]	Filter-Type	Leakage Cur- rent [mA]	L1 [mH]	<b>L2 [µH]</b>	L3 [µH]	Cx [nF]	Cy1 [nF]	Cy2 [nF]	<b>R [Μ</b> Ω]	Clamps [mm2]	Weight [kg]	Housing	Order Number
4	Industrial version	3.5	2 x 20	2 x 30	3	220	33	2.2	0.5	4	1600 g	43	5500.2048
10	Industrial version	1.5	2 x 5	2 x 30	3	220	15	-	0.5	4	-	43	5500.2049
30	Industrial version	1.5	2 x 4	2 x17	3	220	15	-	0.5	6	3220 g	22	5500.2050

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Packaging unit

product selected for their own applications.

1 Pcs

The specifications, descriptions and illustrations indicated in this document are based on current information. All content is subject to modifications and amendments. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability and test each