VM1VD3000

Hyde Park, Ultrasonic sensor, analog, voltage (V), 18 mm snout dual mount, 15 24 V DC



Main

Range of Product	Hyde Park
Sensor Type	Ultrasonic sensor
Series name	Virtu VM1
Device short name	VM1
Sensor design	Flat form + cylindrical M18
Type of sensing window	Adjustable
Material	Plastic
Enclosure Material	Valox
Front material	Glass epoxy
Type of output signal	Analog
ISO thread	M18 x 1
Wiring Technique	4-wire
[Us] rated supply voltage	1524 V DC overload and short-circuit protection
Supply voltage limits	1328 V DC
Analogue output range	010 V direct
Electrical connection	Cable, 9.84 ft (3 m)

Complementary

1	
[Sn] nominal sensing distance	20.00 in (508 mm)
[Sd] sensing range	2.0020.00 in (50.8508 mm)
Blind zone	2.01 in (51 mm)
Transmission frequency	300 kHz
Repeat accuracy	1.27 %
Beam angle	5 °
Minimum size of detected object	Cylinder diameter 2.5 mm - up to 200 mm sensing distance
Current Consumption	40 mA
Maximum switching current	40 mA reverse polarity protection
Height	1.72 in (43.7 mm)
Width	0.71 in (18 mm)
Depth	1.72 in (43.7 mm)
Length	2.58 in (65.61 mm)
Net Weight	0.07 lb(US) (0.033 kg)

Environment

UL CE NEMA 4X indoor use only) IP67
NEMA 4X indoor use only)
.,
IP67
-22158 °F (-3070 °C)
-40185 °F (-4085 °C)
100 % without condensation
+/-1 mm 1055 Hz)IEC 60068-2-6
30 gn in all 3 axes 11 ms IEC 60068-2-27
9.14 V/m (10 V/m) level 3 IEC 61000-4-3
1 kV level 3 IEC 61000-4-4

Ordering and shipping details

Category	22490-SENSORS-ULTRASONIC (XX5,6)
Discount Schedule	DS2
GTIN	3389119127400
Nbr. of units in pkg.	1
Package weight(Lbs)	0.48 oz (13.608 g)
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	5.63 in (14.288 cm)	
Package 1 width	2.50 in (6.35 cm)	
Package 1 Length	5.63 in (14.288 cm)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope

Contractual warranty

Warranty	18 months
•	