

# **ILLUMINATION**



# LUXEON XR-3535L

Turnkey solution on a rigid substrate enabling high-efficacy designs



LUXEON XR-3535L is a fully integrated solution optimized for lighting applications requiring linear LED arrays mounted on a rigid and thermally conductive substrate. The turnkey solution minimizes time to market and simplifies supply chain by reducing optical and mechanical design efforts. Combined with LUXEON 3535L, the integrated unit provides the same powerful optical performance guaranteed by LUXEON LEDs.

### FEATURES AND BENEFITS

- 1400–1500 lumen offerings enabling efficacies of up to 152 lm/W
- A full range of CCT offerings: 3000–5000K with 80CRI minimum
- Complete integrated solution guarantees simplified supply chain and faster time to market Super CEM3 PCB rigid substrate for mechanical robustness and efficient
- heat dissipation
- Two electrical connector options with snap-together or pushbutton terminal blocks
- Zhaga certified mechanical design for easy mounting and assembly
- UL-recognized component [E335118]

## **PRIMARY APPLICATIONS**

Indoor Area Lighting

- Troffers



#### LUXEON XR-3535L product performance at 300mA, T<sub>i</sub>=25°C<sup>[1]</sup>.

| NOMINAL CCT | MINIMUM<br>CRI <sup>[2]</sup> | LUMINOUS FLUX <sup>[3]</sup> (lm) |         | TYPICAL LUMINOUS | PART NUMBER <sup>[4]</sup> |
|-------------|-------------------------------|-----------------------------------|---------|------------------|----------------------------|
|             |                               | MINIMUM                           | TYPICAL | EFFICACY (lm/W)  |                            |
| 3000K       | 80                            | 1320                              | 1403    | 142              | L202 - 3080033C3000x       |
| 3500K       | 80                            | 1386                              | 1469    | 148              | L202 - 3580033C3000x       |
| 4000K       | 80                            | 1419                              | 1502    | 152              | L202 - 4080033C3000x       |
| 5000K       | 80                            | 1419                              | 1502    | 152              | L202 - 5080033C3000x       |

Notes:

Nominal current is 100mA x 3 parallel strings = 300 mA. Lumileds maintains a tolerance of  $\pm 2$  on CRI measurements. Lumileds maintains a tolerance of  $\pm 7.5\%$  on flux measurements.

3

4. "x" is an attribute used to designate connector brand/type. See Part Number Nomenclature on product datasheet.

#### Mechanical Dimensions for L202 - xxxx033C30000 (snap-together connectors).



Mechanical Dimensions for L202 - xxxx033C30001 (pushbutton connectors).



#### Notes:

Drawings are not scale.
All dimensions are in millimeters.

©2015 Lumileds Holding B.V. All rights reserved. LUXEON is a registered trademark of the Lumileds Holding B.V. in the United States and other countries.

#### lumileds.com

Neither Lumileds Holding B.V. nor its affiliates shall be liable for any kind of loss of data or any other damages, direct, indirect or consequential, resulting from the use of the provided information and data. Although Lumileds Holding BV. and/or its affiliates have attempted to provide the most accurate information and data, the materials and services information and data are provided "as is," and neither Lumileds Holding B.V. nor its affiliates warrants or guarantees the contents and correctness of the provided information and data. Lumileds Holding B.V. and its affiliates reserve the right to make changes without notice. You as user agree to this disclaimer and user agreement with the download or use of the provided materials, information and data.