

XC74UL4066

TOREX

ETR1308_002

CMOS Logic

■ DESCRIPTION

XC74UL4066 is CMOS analog switch manufactured using silicon gate CMOS processes. The small supply current, which is one of the features of the CMOS logic, gives way to high speed analog or digital signal switching.
As the series is integrated into a mini molded, SSOT-25 and SON-6 package, high density mounting is possible.


■ APPLICATIONS

- Palmtops
- Digital equipment


■ FEATURES

- High Speed Operation** : $t_{pd} = 2\text{ns}$ (TYP.)
 - Operating Voltage Range** : $2V \sim 5.5V$
 - Low Power Consumption**: $1\mu\text{A}$ (MAX.)
 - Low ON Resistance** : 22Ω (TYP.)
 - CMOS Logic Analog Switch**
 - Ultra Small Packages** : SSOT-25, SON-6*
- * Under Development

■ PIN CONFIGURATION



■ LOGIC DIAGRAM



■ FUNCTIONS

| CONTROL | STATE |
|---------|-------|
| L | OFF |
| H | ON |

H=High level

L=Low level

■ ABSOLUTE MAXIMUM RATINGS

T_a=-40°C~85°C

| PARAMETER | | SYMBOL | RATINGS | UNITS |
|------------------------------|-----------------------------------|----------------|---------------------------|-------|
| Supply Voltage | V _{CC} | | -0.5~+6.0 | V |
| Control Input Voltage | V _{CONT} | | -0.5~+6.0 | V |
| Switch Output Voltage | V _{OUT} | | -0.5~V _{CC} +0.5 | V |
| Control Input Diode Current | I _{IK} | | -20 | mA |
| Switch Output Diode Current | I _{OK} | | ±20 | mA |
| Switch Output Current | I _{OUT} | | ±25 | mA |
| V _{CC} ,GND Current | I _{CC} ,I _{GND} | | ±50 | mA |
| Power Dissipation* | SSOT-25 | P _d | 150 | mW |
| | SON-6 | | 200 | |
| Storage Temperature Range | T _{STG} | | -65~+150 | °C |

Voltage is all ground standardized.

* Ta=25°C

■ RECOMMENDED OPERATING CONDITIONS

| PARAMETER | | SYMBOL | V _{CC} (V) | CONDITIONS | UNITS |
|-----------------------------|--|-------------------|---------------------|-------------------|-------|
| Supply Voltage | | V _{CC} | — | 2~5.5 | V |
| Input Voltage | | V _{IN} | — | 0~5.5 | V |
| Output Voltage | | V _{OUT} | — | 0~V _{CC} | V |
| Operating Temperature Range | | T _{OPR} | — | -40~+85 | °C |
| Input Rise and Fall Time | | t _{r,tf} | 3.3 | 0~100 | ns/V |
| | | | 5.0 | 0~20 | |

■ DC ELECTRICAL CHARACTERISTICS

| PARAMETER | SYMBOL | CONDITIONS | | | Ta=25°C | | Ta=-40°C~85°C | | UNITS | |
|-------------------------------------|---------------------|------------|---|--|---------|------|---------------|------|-------|--|
| | | | | | MIN. | TYP. | MAX. | MIN. | | |
| "High" Level Control Input Voltage" | V _{IH} | 2.0 | | | 1.5 | — | — | 1.5 | V | |
| | | 3.0 | | | 2.1 | — | — | 2.1 | | |
| | | 5.5 | | | 3.85 | — | — | 3.85 | | |
| "Low" Level Control Input Voltage" | V _{IL} | 2.0 | | | — | — | 0.5 | — | V | |
| | | 3.0 | | | — | — | 0.9 | — | | |
| | | 5.5 | | | — | — | 1.65 | — | | |
| Peak ON Resistance | R _{ONmax} | 2.0 | V _{CONT} =V _{IH} V _{IN} =0~V _{CC} I _{IN/OUT} =1mA | | — | 130 | 350 | — | 550 | |
| | | 3.0 | | | — | 22 | 50 | — | 65 | |
| | | 4.5 | | | — | 12 | 25 | — | 35 | |
| ON Resistance | R _{ON(1)} | 2.0 | V _{CONT} =V _{IH} V _{IN} =GND or V _{CC} I _{IN/OUT} =1mA | | — | 23 | 50 | — | 65 | |
| | | 3.0 | | | — | 14 | 30 | — | 40 | |
| | | 4.5 | | | — | 10 | 20 | — | 25 | |
| Power Off Leak Current | I _{S(OFF)} | 5.5 | V _{CONT} =V _{IL} , V _{IN} =V _{CC} , V _{OUT} =GND | | — | — | ±0.1 | — | ±1.0 | |
| Power On Leak Current | I _{S(ON)} | 5.5 | V _{CONT} =V _{IH} , V _{IN} =V _{CC} , OR GND | | — | — | ±0.1 | — | ±1.0 | |
| Control Input Current | I _{CONT} | 5.5 | V _{IN} =V _{CC} or GND | | — | — | ±0.1 | — | ±1.0 | |
| Static Supply Current | I _{CC} | 5.5 | V _{IN} =V _{CC} or GND | | — | — | 1.0 | — | 5.0 | |
| | | | | | | | | — | μA | |

■SWITCHING ELECTRICAL CHARACTERISTICS

(tr=tf=3ns)

| PARAMETER | SYMBOL | Vcc(V) | CONDITIONS | Ta=25°C | | | Ta=-40°C~85°C | | UNITS |
|------------------------------------|--------------|--------|--|---------|------|------|---------------|------|-------|
| | | | | MIN. | TYP. | MAX. | MIN. | MAX. | |
| Delay Time | tPLH tPHL | 2.0 | RL=10kΩ CL=50pF | — | 4 | 20 | — | 23 | ns |
| | | 3.3 | | — | 3 | 6 | — | 8 | |
| | | 5.0 | | — | 2 | 5 | — | 6 | |
| Output Enable Time | tZL tZH | 2.0 | RL=1kΩ CL=50pF | — | 9 | 50 | — | 65 | ns |
| | | 3.3 | | — | 5 | 10 | — | 12 | |
| | | 5.0 | | — | 3 | 8 | — | 10 | |
| Output Disable Time | tLZ tHZ | 2.0 | RL=1kΩ CL=50pF | — | 12 | 60 | — | 75 | ns |
| | | 3.3 | | — | 10 | 23 | — | 27 | |
| | | 5.0 | | — | 8 | 20 | — | 25 | |
| Sine Wave Distortion Rate | | 3.0 | RL=10kΩ CL=50pF fIN=1kHz | — | 0.05 | — | — | — | % |
| -3dB Band Width | | 3.0 | RL=600kΩ, CL=50pF $20\log_{10} \frac{VOUT}{VIN} = -3dB$ | — | 200 | — | — | — | MHz |
| Feed Through (Switch-off) | | 3.0 | RL=600kΩ CL=50pF fIN=1kHz | — | -60 | — | — | — | dB |
| Cross Talk (Control Switch) | | 2.0 | RL=600kΩ CL=50pF fIN=1kHz | — | 60 | — | — | — | mV |
| | | 3.0 | | — | 100 | — | — | — | |
| | | 4.5 | | — | 150 | — | — | — | |
| Maximum Control Input Frequency | | 2.0 | RL=1kΩ CL=15pF VOUT=Vcc/2 | — | 30 | — | — | — | MHz |
| | | 3.0 | | — | 30 | — | — | — | |
| | | 4.5 | | — | 30 | — | — | — | |
| Control Input Capacitance | CIN | — | | — | 5 | 10 | — | 10 | pF |
| Switch Input/Output Capacitance | CIN/OUT | — | | — | 6 | — | — | — | pF |
| Feed Through Capacitance | CIN-OUT | — | | — | 0.5 | — | — | — | pF |
| Power Dissipation Capacitance | CPD | — | | — | 13 | — | — | — | pF |


Note: CPD is defined as the value of the internal equivalent capacitance which is derived from the operating supply current at times of "No Load".

Ensure that the average operating supply current at times of "No Load" meets the following conditions:


$$I_{CC (\text{opr})} = CPD \cdot V_{CC} \cdot f_{IN} + I_{CC}$$

■ DELAY TIME

● WAVEFORM




● TEST CIRCUIT




Note: Open output when measuring supply current

■ OUTPUT ENABLE TIME, OUTPUT DISABLE TIME


● WAVEFORM



● TEST CIRCUIT




■ SINE WAVE DISTORTION RATE




* Input by sine wave

■ -3dB BAND WIDTH



* Input by sine wave


■ FEED THROUGH TEST CIRCUIT




* Input by sine wave

■ CROSS TALK

● WAVEFORM




● TEST CIRCUIT




■ MAXIMUM CONTROL INPUT FREQUENCY


● WAVEFORM




● TEST CIRCUIT




■ON RESISTANCE




■VOLTAGE DEPENDANCIES OF ON RESISTANCE



■POWER OFF LEAK CURRENT



■POWER ON LEAK CURRENT



1. The products and product specifications contained herein are subject to change without notice to improve performance characteristics. Consult us, or our representatives before use, to confirm that the information in this catalog is up to date.
2. We assume no responsibility for any infringement of patents, patent rights, or other rights arising from the use of any information and circuitry in this catalog.
3. Please ensure suitable shipping controls (including fail-safe designs and aging protection) are in force for equipment employing products listed in this catalog.
4. The products in this catalog are not developed, designed, or approved for use with such equipment whose failure of malfunction can be reasonably expected to directly endanger the life of, or cause significant injury to, the user.
(e.g. Atomic energy; aerospace; transport; combustion and associated safety equipment thereof.)
5. Please use the products listed in this catalog within the specified ranges.
Should you wish to use the products under conditions exceeding the specifications, please consult us or our representatives.
6. We assume no responsibility for damage or loss due to abnormal use.
7. All rights reserved. No part of this catalog may be copied or reproduced without the prior permission of Torex Semiconductor Ltd.

TOREX SEMICONDUCTOR LTD.