

### FD5-120

**Description:**

The FD5-120 Quick Pack small power transformer offers a significant reduction in size and weight over a standard transformer. This transformer can be used for a wide variety of applications. It is bobbin wound for reduced size and small operating space.

**Electrical Specifications (@25C);**

**Maximum Power:** 12.0VA

**Input Voltage:**

**Series:** 230VAC@50/60Hz

**Parallel:** 115VAC@50/60Hz

**Output Voltage:** 120VCT@.1A

**Hipot:** 2500VAC primary to secondary; 1500VAC windings to core.

**Construction:**

Split bobbin non concentric winding eliminates costly electrostatic shielding. Termination is suitable for quick connects or soldering. Built with UL Class B Insulation System.

**Safety:**

UL: File E53148, UL 5085-1 and 2 (formerly UL 506), General Purpose.




**Dimensions:**

A	B	C	D	E	F	G
1.625	2.375	2.812	1.375	1.937	.187 Dia	.812

- Notes:**
1. Units: inches.
  2. Terminal size: .187" X 0.021".
  3. Weight: .70 lbs

**Schematic:**



**Input (115V):** Input 1 & 2  
Connect 1&3, 2&4

**Output: 5 & 8**

**Input (230V):** Input 1 & 4  
Connect 2&3

**RoHS Compliance:** As of manufacturing date February 2016, all standard products meet the requirements of 2015/863/EU, known as the RoHS 3 initiative.

\* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.

