



PJP60R290E / PJF60R290E

600V N-Channel Super Junction MOSFET


Voltage	600 V	Current	15 A
---------	-------	---------	------

Features

- $R_{DS(ON)}$, $V_{GS}@10V$, $I_D@6.5A < 0.29\Omega$
- Fast switching speed
- Low on-resistance
- Low Noise
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case : TO-220AB, ITO-220AB-F Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- TO-220AB Approx. Weight : 0.067 ounces, 1.89 grams
- ITO-220AB-F Approx. Weight : 0.068 ounces, 2 grams



Maximum Ratings and Thermal Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER		SYMBOL	TO-220AB	ITO-220AB-F	UNITS
Drain-Source Voltage		V_{DS}	600		V
Gate-Source Voltage		V_{GS}	± 20		
Continuous Drain Current (Note 4)	$T_C=25^\circ\text{C}$	I_D	15		A
	$T_C=100^\circ\text{C}$		10		
Pulsed Drain Current (Note 1)		I_{DM}	30		
Power Dissipation	$T_C=25^\circ\text{C}$	P_D	184	60	W
	$T_C=100^\circ\text{C}$		74	24	
Continuous Drain Current (Note 4)	$T_A=25^\circ\text{C}$	I_D	1.7		A
	$T_A=70^\circ\text{C}$		1.4		
Power Dissipation	$T_A=25^\circ\text{C}$	P_D	2	1.04	W
	$T_A=70^\circ\text{C}$		1.3	0.9	
Single Pulse Avalanche Energy (Note 5)		E_{AS}	288		mJ
Operating Junction and Storage Temperature Range		T_J, T_{STG}	-55~150		$^\circ\text{C}$
Typical Thermal Resistance (Note 4,5)		$R_{\theta JC}$	0.68	2.08	$^\circ\text{C/W}$
		$R_{\theta JA}$	62.5	120	

- Limited only By Maximum Junction Temperature



PJP60R290E / PJF60R290E

Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Static						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V, I_D=250\mu A$	600	-	-	V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	2	3	4	
Drain-Source On-State Resistance	$R_{DS(on)}$	$V_{GS}=10V, I_D=6.5A$	-	0.25	0.29	Ω
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=600V, V_{GS}=0V$	-	-	1	μA
Gate-Source Leakage Current	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$	-	-	± 100	nA
Diode Forward Voltage	V_{SD}	$I_S=15A, V_{GS}=0V$	-	0.95	1.5	V
Transconductance	G_{FS}	$V_{DS}=10V, I_D=7.5A$	-	8	-	S
Dynamic (Note 7)						
Total Gate Charge	Q_g	$V_{DS}=300V, I_D=15A,$ $V_{GS}=10V$ (Note 2,3)	-	40	-	nC
Gate-Source Charge	Q_{gs}		-	6.5	-	
Gate-Drain Charge	Q_{gd}		-	21	-	
Gate Input Resistance	R_g	$F = 1\text{MHz}$	-	7.3	-	Ω
Input Capacitance	C_{iss}	$V_{DS}=25V, V_{GS}=0V,$ $f=1\text{MHz}$	-	1013	-	pF
Output Capacitance	C_{oss}		-	674	-	
Reverse Transfer Capacitance	C_{rss}		-	91	-	
Turn-On Delay Time	$t_{d(on)}$	$V_{DD}=300V, I_D=7.5A,$ $R_G=10\Omega$ (Note 2,3)	-	15	-	ns
Turn-On Rise Time	t_r		-	28	-	
Turn-Off Delay Time	$t_{d(off)}$		-	109	-	
Turn-Off Fall Time	t_f		-	29	-	
Drain-Source Diode						
Maximum Continuous Drain-Source Diode Forward Current	I_S	---	-	-	15	A
Maximum Pulsed Drain-Source Diode Forward Current	I_{SM}	---	-	-	30	
Reverse Recovery Time	t_{rr}	$V_{GS}=0V, I_S=15A$	-	441	-	ns
Reverse Recovery Charge	Q_{rr}	$di_f/dt=100A/\mu s$ (Note 2)	-	7.2	-	μC

NOTES :

1. Pulse width $\leq 300\mu s$, Duty cycle $\leq 2\%$.
2. Essentially independent of operating temperature typical characteristics.
3. Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}=150^\circ\text{C}$. Ratings are based on low frequency and duty cycles to keep initial $T_J=25^\circ\text{C}$.
4. The maximum current rating is package limited.
5. TO-252AA and TO-251AA mounted on a 1 inch² with 2oz. square pad of copper.
6. $L=100\text{mH}$, $I_{AS}=2.4A$, $V_{DD}=50V$, $R_G=25\text{ohm}$, Starting $T_J=25^\circ\text{C}$.
7. Guaranteed by design, not subject to production testing.



PJP60R290E / PJF60R290E

TYPICAL CHARACTERISTIC CURVES




Fig.1 Output Characteristics




Fig.2 Transfer Characteristics




Fig.3 On-Resistance vs. Drain Current




Fig.4 On-Resistance vs. Junction Temperature




Fig.5 On-Resistance Variation with V_{GS}




Fig.6 Source-Drain Diode Forward Voltage



PJP60R290E / PJF60R290E

TYPICAL CHARACTERISTIC CURVES




Fig.7 Gate-Charge Characteristics




Fig.8 Breakdown Voltage Variation vs. Temperature




Fig.9 Threshold Voltage Variation with Temperature




Fig.10 Capacitance vs. Drain-Source Voltage




Fig.11 PJP Maximum Safe Operating Area




Fig.12 PJF Maximum Safe Operating Area



PJP60R290E / PJF60R290E

TYPICAL CHARACTERISTIC CURVES




Fig.13 PJP Normalized Transient Thermal Impedance




Fig.14 PJF Normalized Transient Thermal Impedance






Fig.15 Total Power Dissipation



PJP60R290E / PJF60R290E

Packaging Information





PJP60R290E / PJF60R290E

Part No Packing Code Version

Part No Packing Code	Package Type	Packing Type	Marking	Version
PJP60R290E_T0_00001	TO-220AB	50pcs / Tube	60R290E	Halogen free
PJF60R290E_T0_00001	ITO-220AB-F	50pcs / Tube	60R290E	Halogen free



PJP60R290E / PJF60R290E

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.