



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

2N5486

Silicon N-Channel JFET Transistor

VHF/UHF Amplifier

TO92 Type Package

Absolute Maximum Ratings:

| | |
|---|-------------------------|
| Drain-Gate Voltage, V_{DG} | 25V |
| Reverse Gate-Source Voltage, V_{GSR} | 25V |
| Drain Current, I_D | 30mA |
| Forward Gate Current, $I_{G(f)}$ | 10mA |
| Total Device Dissipation ($T_C = +25^\circ\text{C}$), P_D | 350mW |
| Derate Above 25°C | 2.8mW/ $^\circ\text{C}$ |
| Operating Junction Temperature Range, T_J | -65° to +150°C |
| Storage Temperature Range, T_{stg} | -65° to +150°C |

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|---|---------------------|--|------|-----|------|-----------------|
| OFF Characteristics | | | | | | |
| Gate-Source Breakdown Voltage | $V_{(BR)GSS}$ | $I_G = -1\mu\text{A}$, $V_{DS} = 0$ | -25 | - | - | V |
| Gate Reverse Current | I_{GSS} | $V_{GS} = -20\text{V}$, $V_{DS} = 0$ | - | - | -1.0 | nA |
| | | $V_{GS} = -20\text{V}$, $V_{DS} = 0$, $T_A = +100^\circ\text{C}$ | - | - | -0.2 | nA |
| Gate-Source Cutoff Voltage | $V_{GS(off)}$ | $I_D = 10\text{nA}$, $V_{DS} = 15\text{V}$ | -2 | - | -6 | V |
| ON Characteristics | | | | | | |
| Zero-Gate-Voltage Drain Current | I_{DSS} | $V_{DS} = 15\text{V}$, $V_{GS} = 0$ | 8 | - | 20 | mA |
| Small Signal Characteristics Characteristics | | | | | | |
| Forward Transfer Admittance | $ y_{fs} $ | $V_{DS} = 15\text{V}$, $V_{GS} = 0$, $f = 1\text{kHz}$ | 4000 | - | 8000 | μmho |
| Input Admittance | $\text{Re}(y_{is})$ | $V_{DS} = 15\text{V}$, $V_{GS} = 0$, $f = 400\text{MHz}$ | - | - | 1000 | μmho |
| Output Admittance | $ y_{os} $ | $V_{DS} = 15\text{V}$, $V_{GS} = 0$, $f = 1\text{kHz}$ | - | - | 75 | μmho |
| Output Conductance | $\text{Re}(y_{os})$ | $V_{DS} = 15\text{V}$, $V_{GS} = 0$, $f = 400\text{MHz}$ | - | - | 100 | μmho |
| Forward Transconductance | g_{fs} | $V_{DS} = 15\text{V}$, $V_{GS} = 0$, $f = 400\text{MHz}$ | 2500 | - | - | μmho |
| Input Capacitance | C_{iss} | $V_{DS} = 15\text{V}$, $V_{GS} = 0$, $f = 1\text{MHz}$ | - | - | 5 | pF |
| Reverse Transfer Capacitance | C_{rss} | $V_{DS} = 15\text{V}$, $V_{GS} = 0$, $f = 1\text{MHz}$ | - | - | 1 | pF |
| Output Capacitance | C_{oss} | $V_{DS} = 15\text{V}$, $V_{GS} = 0$, $f = 1\text{MHz}$ | - | - | 2 | pF |

Electrical Characteristics Cont'd): ($T_A = +25^\circ\text{C}$ unless otherwise specified)

| Parameter | Symbol | Test Conditions | | Min | Typ | Max | Unit |
|-----------------------------------|----------|---|---------------------|-----|-----|-----|------|
| Functional Characteristics | | | | | | | |
| Noise Figure | NF | $V_{DS} = 15\text{V}$, $I_D = 4\text{mA}$, $R_G \approx 1\text{k}\Omega$ | $f = 100\text{MHz}$ | - | - | 2 | dB |
| | | | $f = 400\text{MHz}$ | - | - | 4 | dB |
| Common Source Power Gain | G_{ps} | $V_{DS} = 15\text{V}$, $I_D = 4\text{mA}$ | $f = 100\text{MHz}$ | 18 | - | 30 | dB |
| | | | $f = 400\text{MHz}$ | 10 | - | 20 | dB |

