## XCKT1587922

Limit switch, Limit switches XC Standard, XCK T, roller plunger, 1NC+1 NO





#### Main

Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch
Device short name	XCKT
Body type	Fixed
Material	Plastic
Body Material	Plastic
Head material	Zamak
Fixing Mode	By the body
Number of poles	2
Contacts type and composition	1 NC + 1 NO
Contact operation	Snap action

#### Complementary

Electrical connection	Screw-clamp terminals 1 x 0.342 x 1.5 mm <sup>2</sup>
Cable entry	2 entries tapped for 1/2" NPT cable gland
Contacts insulation form	Zb
Contact code designation	A300, AC-15 (Ue = 240 V), le = 3 A 10 A EN/IEC 60947-5-1 appendix A Q300, DC-13 (Ue = 250 V), le = 0.27 A EN/IEC 60947-5-1 appendix A
[Ui] rated insulation voltage	300 VUL 508 500 V 3)IEC 60947-1 300 VCSA C22.2 No 14
Maximum resistance across terminals	25 MOhm IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	6 KV IEC 60664 6 kV IEC 60947-1
Short-circuit protection	10 A cartridge fuse gG
Electrical durability	5000000 Cycles, DC-13, 120 V, 4 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13, 24 V, 10 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13, 48 V, 7 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C
Mechanical durability	10000000 cycles

#### Environment

Shock resistance	50 gn 11 ms IEC 60068-2-27	
Vibration resistance	25 gn 10500 Hz)IEC 60068-2-6	
IP degree of protection	IP66 conforming to IEC 60529 IP67 conforming to IEC 60529	
IK degree of protection	IK04 EN 50102	
Electrical shock protection class	Class II IEC 61140 Class II NF C 20-030	
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
Protective treatment	TC	

Product Certifications	UL CSA CCC	
Standards	UL 508 IEC 60947-5-1 EN 60947-5-1 EN 60204-1 CSA C22.2 No 14 IEC 60204-1	

# Ordering and shipping details

Category	22418-LIMIT SWITCH,IEC,XCKP&XCKT
Discount Schedule	Т
GTIN	3389110933390
Nbr. of units in pkg.	1
Package weight(Lbs)	5.26 oz (149.0 g)
Returnability	No
Country of origin	FR

## **Packing Units**

Unit Type of Package 1	PCE	
Package 1 Height	2.36 in (6 cm)	
Package 1 width	2.83 in (7.2 cm)	
Package 1 Length	4.72 in (12 cm)	
Unit Type of Package 2	S02	
Number of Units in Package 2	22	
Package 2 Weight	7.90 lb(US) (3.582 kg)	
Package 2 Height	5.91 in (15 cm)	
Package 2 width	11.81 in (30 cm)	
Package 2 Length	15.75 in (40 cm)	

## Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EEU RoHS  Declaration	
Mercury free	Yes	
RoHS exemption information	€Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	