

6

5

4

3

5. TERMINAL FOR USE WITH (1.57)/.062 DIA. SERIES HOUSINGS AND WILL ACCEPT

6. PARTS CONFORM TO CLASS B REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002.

9

8

10

CURRENT REV DESC: UPDATE GRAPHICS molex 8:1 mm GENERAL TOLERANCES (UNLESS SPECIFIED) EC NO: 632666 ANGULAR TOL ± 0.62 DIA CRIMP MALE TERM \$ = 0 4 PLACES DRWN: MKIPPER 2019/03/06 材料 MATERIAL CHK'D: DSTEIER 2020/02/26 = 0 3 PLACES APPR: FSMITH 2020/06/05 BRASS 0.2 t PRODUCT CUSTOMER DRAWING 2 PLACES INITIAL REVISION: 仕上げ FINISH 1 PLACE DRWN: NAKAMURAA 2008/12/16 **=** SD-1560-001 PSD | 001 0 PLACES APPR: NUKITA 2009/01/15 適用電線範囲 WIRE RANGE AWG# |8-#24 MATERIAL NUMBER CUSTOMER DRAFT WHERE APPLICABLE THIRD ANGLE PROJECTION DRAWING SERIES SHEET NUMBER 被覆外径 INS. RANGE MUST REMAIN \bigoplus C-SIZE 1560 **GENERAL MARKET** 1 OF 1 SEE CHART \emptyset 1.5 \sim 3.1 WITHIN DIMENSIONS

2

1

12

11

10

4. PACKAGING INFORMATION: 15600000-PK 18 THRU 24 AWG WIRE WITH 1.5/3.1 INSULATION DIA.

DOCUMENT STATUS P1 RELEASE DATE | 2020/06/05 20:49:08