

## Austin SuperLynx™ 12V SIP Non-isolated Power Modules: 10Vdc – 14Vdc Input; 0.75Vdc to 5.5Vdc Output; 16A Output Current

### RoHS Compliant



### Applications

- Distributed power architectures
- Intermediate bus voltage applications
- Telecommunications equipment
- Servers and storage applications
- Networking equipment
- Enterprise Networks
- Latest generation IC's (DSP, FPGA, ASIC) and Microprocessor powered applications

### Features

- Compliant to RoHS EU Directive 2002/95/EC (-Z versions)
- Compliant to ROHS EU Directive 2002/95/EC with lead solder exemption (non-Z versions)
- Delivers up to 16A output current
- High efficiency – 92% at 3.3V full load ( $V_{IN} = 12.0V$ )
- Small size and low profile:  
50.8 mm x 12.7 mm x 8.10 mm  
(2.00 in x 0.50 in x 0.32 in)
- Low output ripple and noise
- High Reliability:  
Calculated MTBF = 4.4M hours at 25°C Full-load
- Constant switching frequency (300 kHz)
- Output voltage programmable from 0.75 Vdc to 5.5Vdc via external resistor
- Line Regulation: 0.3% (typical)
- Load Regulation: 0.4% (typical)
- Temperature Regulation: 0.4 % (typical)
- Remote On/Off
- Remote Sense
- Output overcurrent protection (non-latching)
- Wide operating temperature range (-40°C to 85°C)
- *UL\** 60950-1 Recognized, *CSA†* C22.2 No. 60950-1-03 Certified, and *VDE‡* 0805:2001-12 (EN60950-1) Licensed
- ISO\*\* 9001 and ISO 14001 certified manufacturing facilities

### Description

Austin SuperLynx™ 12V SIP power modules are non-isolated dc-dc converters that can deliver up to 16A of output current with full load efficiency of 92% at 3.3V output. These modules provide a precisely regulated output voltage ranging from 0.75Vdc to 5.5Vdc, programmable via an external resistor over a wide range of input voltage ( $V_{IN} = 10 - 14Vdc$ ). Their open-frame construction and small footprint enable designers to develop cost- and space-efficient solutions. Standard features include remote On/Off, remote sense, output voltage adjustment, overcurrent and overtemperature protection.

\* *UL* is a registered trademark of Underwriters Laboratories, Inc.

† *CSA* is a registered trademark of Canadian Standards Association.

‡ *VDE* is a trademark of Verband Deutscher Elektrotechniker e.V.

\*\* ISO is a registered trademark of the International Organization of Standards

## Absolute Maximum Ratings

Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. These are absolute stress ratings only, functional operation of the device is not implied at these or any other conditions in excess of those given in the operations sections of the data sheet. Exposure to absolute maximum ratings for extended periods can adversely affect the device reliability.

Parameter	Device	Symbol	Min	Max	Unit
Input Voltage Continuous	All	V <sub>IN</sub>	-0.3	15	Vdc
Operating Ambient Temperature (see Thermal Considerations section)	All	T <sub>A</sub>	-40	85	°C
Storage Temperature	All	T <sub>stg</sub>	-55	125	°C

## Electrical Specifications

Unless otherwise indicated, specifications apply over all operating input voltage, resistive load, and temperature conditions.

Parameter	Device	Symbol	Min	Typ	Max	Unit
Operating Input Voltage	$V_{O,\text{set}} \leq V_{IN} - 0.5V$	V <sub>IN</sub>	10.0	12.0	14.0	Vdc
Maximum Input Current ( $V_{IN}=10.0\text{V}$ to $14.0\text{V}$ , $I_O=I_{O,\text{max}}$ )	All	I <sub>IN,max</sub>			9.5	Adc
Input No Load Current ( $V_{IN} = 12.0\text{Vdc}$ , $I_O = 0$ , module enabled)	$V_{O,\text{set}} = 0.75\text{ Vdc}$ $V_{O,\text{set}} = 5.0\text{Vdc}$	I <sub>IN,No load</sub> I <sub>IN,No load</sub>		40 100		mA mA
Input Stand-by Current ( $V_{IN} = 12.0\text{Vdc}$ , module disabled)	All	I <sub>IN,stand-by</sub>		2		mA
Inrush Transient	All	I <sup>2</sup> t			0.4	A <sup>2</sup> s
Input Reflected Ripple Current, peak-to-peak (5Hz to 20MHz, $1\mu\text{H}$ source impedance; $V_{IN,\text{min}}$ to $V_{IN,\text{max}}$ , $I_O=I_{O,\text{max}}$ ; See Test configuration section)	All			30		mAp-p
Input Ripple Rejection (120Hz)	All			30		dB

### CAUTION: This power module is not internally fused. An input line fuse must always be used.

This power module can be used in a wide variety of applications, ranging from simple standalone operation to being part of a complex power architecture. To preserve maximum flexibility, internal fusing is not included, however, to achieve maximum safety and system protection, always use an input line fuse. The safety agencies require a fast-acting fuse with a maximum rating of 15 A (see Safety Considerations section). Based on the information provided in this data sheet on inrush energy and maximum dc input current, the same type of fuse with a lower rating can be used. Refer to the fuse manufacturer's data sheet for further information.

### Electrical Specifications (continued)

Parameter	Device	Symbol	Min	Typ	Max	Unit
Output Voltage Set-point  ( $V_{IN} = V_{IN, min}$ , $I_O = I_{O, max}$ , $T_A = 25^\circ C$ )	All	$V_{O, set}$	-2.0	$V_{O, set}$	+2.0	% $V_{O, set}$
Output Voltage  (Over all operating input voltage, resistive load, and temperature conditions until end of life)	All	$V_{O, set}$	-2.5%	—	+3.5%	% $V_{O, set}$
Adjustment Range Selected by an external resistor	All	$V_O$	0.7525		5.5	Vdc
Output Regulation  Line ( $V_{IN} = V_{IN, min}$ to $V_{IN, max}$ )  Load ( $I_O = I_{O, min}$ to $I_{O, max}$ )  Temperature ( $T_{ref} = T_A, min$ to $T_A, max$ )	All		—	0.3	—	% $V_{O, set}$
Output Ripple and Noise on nominal output  ( $V_{IN} = V_{IN, nom}$ and $I_O = I_{O, min}$ to $I_{O, max}$  $C_{out} = 1\mu F$ ceramic// $10\mu F$ tantalum capacitors)	All		—	12	30	mV <sub>rms</sub>
RMS (5Hz to 20MHz bandwidth)  Peak-to-Peak (5Hz to 20MHz bandwidth)	All		—	30	75	mV <sub>pk-pk</sub>
External Capacitance  ESR $\geq 1\text{ m}\Omega$ ESR $\geq 10\text{ m}\Omega$	All	$C_{O, max}$	—	—	1000	$\mu F$
	All	$C_{O, max}$	—	—	5000	$\mu F$
Output Current	All	$I_O$	0		16	Adc
Output Current Limit Inception (Hiccup Mode )  ( $V_O = 90\%$ of $V_{O, set}$ )	All	$I_{O, lim}$	—	180	—	% $I_O$
Output Short-Circuit Current  ( $V_O \leq 250\text{mV}$ ) ( Hiccup Mode )	All	$I_{O, s/c}$	—	3	—	Adc
Efficiency  $V_{IN} = V_{IN, nom}$ , $T_A = 25^\circ C$ $I_O = I_{O, max}$ , $V_O = V_{O, set}$	$V_{O, set} = 0.75\text{Vdc}$ $V_{O, set} = 1.2\text{Vdc}$ $V_{O, set} = 1.5\text{Vdc}$ $V_{O, set} = 1.8\text{Vdc}$ $V_{O, set} = 2.5\text{Vdc}$ $V_{O, set} = 3.3\text{Vdc}$ $V_{O, set} = 5.0\text{Vdc}$	η		79.0		%
		η		85.0		%
		η		87.0		%
		η		88.0		%
		η		90.5		%
		η		92.0		%
		η		94.0		%
Switching Frequency	All	$f_{sw}$	—	300	—	kHz
Dynamic Load Response  ( $dI_O/dt = 2.5\text{A}/\mu\text{s}$ ; $V_{IN} = V_{IN, nom}$ ; $T_A = 25^\circ C$ )  Load Change from $I_O = 50\%$ to $100\%$ of $I_{O, max}$ ; $1\mu F$ ceramic// $10\mu F$ tantalum	All	$V_{pk}$	—	200	—	mV
Peak Deviation  Settling Time ( $V_O < 10\%$ peak deviation)  ( $dI_O/dt = 2.5\text{A}/\mu\text{s}$ ; $V_{IN} = V_{IN, nom}$ ; $T_A = 25^\circ C$ )  Load Change from $I_O = 100\%$ to $50\%$ of $I_{O, max}$ : $1\mu F$ ceramic// $10\mu F$ tantalum	All	$t_s$	—	25	—	$\mu\text{s}$
	All	$V_{pk}$	—	200	—	mV
Peak Deviation  Settling Time ( $V_O < 10\%$ peak deviation)	All	$t_s$	—	25	—	$\mu\text{s}$

### Electrical Specifications (continued)

Parameter	Device	Symbol	Min	Typ	Max	Unit
Dynamic Load Response  (dIo/dt=2.5A/μs; V <sub>IN</sub> = V <sub>IN, nom</sub> ; T <sub>A</sub> =25°C)  Load Change from I <sub>O</sub> = 50% to 100% of I <sub>O,max</sub> ; Co = 2x150 μF polymer capacitors	All	V <sub>pk</sub>	—	100	—	mV
Peak Deviation						
Settling Time (Vo<10% peak deviation)  (dIo/dt=2.5A/μs; V <sub>IN</sub> = V <sub>IN, nom</sub> ; T <sub>A</sub> =25°C)	All	t <sub>s</sub>	—	50	—	μs
Load Change from I <sub>O</sub> = 100% to 50% of I <sub>O,max</sub> ; Co = 2x150 μF polymer capacitors	All	V <sub>pk</sub>	—	100	—	mV
Peak Deviation						
Settling Time (Vo<10% peak deviation)	All	t <sub>s</sub>	—	50	—	μs

### General Specifications

Parameter	Min	Typ	Max	Unit
Calculated MTBF (I <sub>O</sub> =I <sub>O,max</sub> , T <sub>A</sub> =25°C)	4,400,000			Hours
Weight	—	5.6 (0.2)	—	g (oz.)


## Feature Specifications

Unless otherwise indicated, specifications apply over all operating input voltage, resistive load, and temperature conditions. See Feature Descriptions for additional information.


Parameter	Device	Symbol	Min	Typ	Max	Unit
Remote On/Off Signal interface  ( $V_{IN} = V_{IN, min}$ to $V_{IN, max}$ ; Open collector pnp or equivalent Compatible, Von/off signal referenced to GND See feature description section)  Logic High (On/Off Voltage pin open - Module ON)  Von/Off Ion/Off	All	$V_{IH}$	—	—	$V_{IN}$	V $\mu A$
Logic Low (Von/Off $\leq 0.3V$ – Module OFF)  Von/Off Ion/off	All	$V_{IL}$	—	—	0.3	V
Turn-On Delay and Rise Times  ( $I_o = I_{O, max}$ , $V_{IN} = V_{IN, nom}$ , $T_A = 25^\circ C$ , )  Case 1: On/Off input is set to Logic Low (Module ON) and then input power is applied (delay from instant at which $V_{IN} = V_{IN, min}$ until $V_o = 10\%$ of $V_{o, set}$ )  Case 2: Input power is applied for at least one second and then the On/Off input is set to logic Low (delay from instant at which Von/Off=0.3V until $V_o = 10\%$ of $V_{o, set}$ )  Output voltage Rise time (time for $V_o$ to rise from 10% of $V_{o, set}$ to 90% of $V_{o, set}$ )	All	$T_{delay}$	—	3	—	msec
Output voltage overshoot – Startup  $I_o = I_{O, max}$ ; $V_{IN} = 10$ to $14Vdc$ , $T_A = 25^\circ C$	All	$T_{delay}$	—	3	—	msec
Remote Sense Range			—	—	0.5	
Overtemperature Protection  (See Thermal Consideration section)	All	$T_{ref}$	—	125	—	°C
Input Undervoltage Lockout  Turn-on Threshold Turn-off Threshold	All			8.2		V
	All			8.0		V

## Characteristic Curves


The following figures provide typical characteristics for the Austin SuperLynx™ 12V SIP modules at 25°C.




**Figure 1. Converter Efficiency versus Output Current (Vout = 1.2Vdc)**




**Figure 4. Converter Efficiency versus Output Current (Vout = 2.5Vdc)**




**Figure 2. Converter Efficiency versus Output Current (Vout = 1.5Vdc)**



**Figure 5. Converter Efficiency versus Output Current (Vout = 3.3Vdc)**




**Figure 3. Converter Efficiency versus Output Current (Vout = 1.8Vdc)**




**Figure 6. Converter Efficiency versus Output Current (Vout = 5.0Vdc)**

### Characteristic Curves (continued)


The following figures provide typical characteristics for the Austin SuperLynx™ 12V SIP modules at 25°C.




**Figure 7. Input voltage vs. Input Current  
 $(V_{out} = 5.0Vdc)$ .**




**Figure 10. Transient Response to Dynamic Load  
 Change from 50% to 100% of full load ( $V_o = 5.0Vdc$ ).**




**Figure 8. Typical Output Ripple and Noise  
 $(V_{in} = 12V \text{ dc}, V_o = 2.5 \text{ Vdc}, I_o=16A)$ .**



**Figure 11. Transient Response to Dynamic Load  
 Change from 100% to 50% of full load ( $V_o = 5.0 \text{ Vdc}$ ).**




**Figure 9. Typical Output Ripple and Noise  
 $(V_{in} = 12V \text{ dc}, V_o = 5.0 \text{ Vdc}, I_o=16A)$ .**




**Figure 12. Transient Response to Dynamic Load  
 Change from 50% to 100% of full load ( $V_o = 5.0 \text{ Vdc}$ ,  $C_{ext} = 2 \times 150 \mu\text{F}$  Polymer Capacitors).**

### Characteristic Curves (continued)


The following figures provide typical characteristics for the Austin SuperLynx™ 12V SIP modules at 25°C.




**Figure 13. Transient Response to Dynamic Load Change from 100% of 50% full load ( $V_o = 5.0$  Vdc,  $C_{ext} = 2 \times 150 \mu F$  Polymer Capacitors).**




**Figure 14. Typical Start-Up Using Remote On/Off ( $V_{in} = 12$ Vdc,  $V_o = 5.0$ Vdc,  $I_o = 16$ A).**




**Figure 15. Typical Start-Up Using Remote On/Off with Low-ESR external capacitors (7x150 $\mu$ F Polymer) ( $V_{in} = 12$ Vdc,  $V_o = 5.0$ Vdc,  $I_o = 16$ A,  $C_o = 1050\mu F$ ).**



**Figure 16. Typical Start-Up with application of  $V_{in}$  with low-ESR polymer capacitors at the output (7x150  $\mu$ F) ( $V_{in} = 12$ Vdc,  $V_o = 5.0$ Vdc,  $I_o = 16$ A,  $C_o = 1050 \mu F$ ).**




**Figure 17 Typical Start-Up with Prebias ( $V_{in} = 12$ Vdc,  $V_o = 5.0$ Vdc,  $I_o = 1$ A,  $V_{bias} = 3.3$  Vdc).**




**Figure 18. Output short circuit Current ( $V_{in} = 12$ Vdc,  $V_o = 0.75$ Vdc).**

### Characteristic Curves (continued)


The following figures provide thermal derating curves for the Austin SuperLynx™ 12V SIP modules.




**Figure 19.** Derating Output Current versus Local Ambient Temperature and Airflow (Vin = 12Vdc, Vo=0.75Vdc).



**Figure 22.** Derating Output Current versus Local Ambient Temperature and Airflow (Vin = 12Vdc, Vo=5.0 Vdc).



**Figure 20.** Derating Output Current versus Local Ambient Temperature and Airflow (Vin = 12Vdc, Vo=1.8 Vdc).



**Figure 21.** Derating Output Current versus Local Ambient Temperature and Airflow (Vin = 12Vdc, Vo=3.3 Vdc).

## Test Configurations




Figure 23. Input Reflected Ripple Current Test Setup.




Figure 24. Output Ripple and Noise Test Setup.




Figure 25. Output Voltage and Efficiency Test Setup.

$$\text{Efficiency } \eta = \frac{V_O \cdot I_O}{V_{IN} \cdot I_{IN}} \times 100 \%$$

## Design Considerations

### Input Filtering

The Austin SuperLynx™ 12V SIP module should be connected to a low-impedance source. A highly inductive source can affect the stability of the module. An input capacitance must be placed directly adjacent to the input pin of the module, to minimize input ripple voltage and ensure module stability.

In a typical application, 6x47 μF low-ESR tantalum capacitors (AVX part #: TPSE476M025R0100, 47μF 25V 100 mΩ ESR tantalum capacitor) will be sufficient to provide adequate ripple voltage at the input of the module. To further minimize ripple voltage at the input, very low ESR ceramic capacitors are recommended at the input of the module. Figure 26 shows input ripple voltage (mVp-p) for various outputs with 6x47 μF tantalum capacitors and with 6x22 μF ceramic capacitor (TDK part #: C4532X5R1C226M) at full load.




Figure 26. Input ripple voltage for various output with 6x47 μF tantalum capacitors and with 6x22 μF ceramic capacitors at the input (full load).

## Design Considerations (continued)

### Output Filtering

The Austin SuperLynx™ 12V SIP module is designed for low output ripple voltage and will meet the maximum output ripple specification with 1  $\mu$ F ceramic and 10  $\mu$ F tantalum capacitors at the output of the module.

However, additional output filtering may be required by the system designer for a number of reasons. First, there may be a need to further reduce the output ripple and noise of the module. Second, the dynamic response characteristics may need to be customized to a particular load step change.

To reduce the output ripple and improve the dynamic response to a step load change, additional capacitance at the output can be used. Low ESR polymer and ceramic capacitors are recommended to improve the dynamic response of the module. For stable operation of the module, limit the capacitance to less than the maximum output capacitance as specified in the electrical specification table.

## Safety Considerations

For safety agency approval the power module must be installed in compliance with the spacing and separation requirements of the end-use safety agency standards, i.e., UL 60950-1, CSA C22.2 No. 60950-1-03, and VDE 0850:2001-12 (EN60950-1) Licensed.

For the converter output to be considered meeting the requirements of safety extra-low voltage (SELV), the input must meet SELV requirements. The power module has extra-low voltage (ELV) outputs when all inputs are ELV.

The input to these units is to be provided with a fast-acting fuse with a maximum rating of 6A in the positive input lead.

## Feature Description

### Remote On/Off

The Austin SuperLynx™ 12V SIP power modules feature an On/Off pin for remote On/Off operation of the module. If not using the remote On/Off pin, leave the pin open (module will be On). The On/Off pin signal ( $V_{ON/OFF}$ ) is referenced to ground. To switch the module on and off using remote On/Off, connect an open collector npn transistor or N-channel FET between the On/Off pin and the ground pin (See Figure 27).

During a logic-high (On/Off pin is pulled high internal to the module) when the transistor is in the Off state, the power module is ON. The maximum allowable leakage current of the transistor when  $V_{ON/OFF} = V_{IN,max}$  is  $10\mu A$ . During a logic-low when the transistor is turned-on, the power module is OFF. During this state  $V_{ON/OFF}$  is less than  $0.3V$  and the maximum  $I_{ON/OFF} = 1mA$ .




Figure 27. Remote On/Off Implementation.

### Overcurrent Protection

To provide protection in a fault (output overload) condition, the unit is equipped with internal current-limiting circuitry and can endure current limiting continuously. At the point of current-limit inception, the unit enters hiccup mode. The unit operates normally once the output current is brought back into its specified range. The typical average output current during hiccup is 3A.

### Input Undervoltage Lockout

At input voltages below the input undervoltage lockout limit, module operation is disabled. The module will begin to operate at an input voltage above the undervoltage lockout turn-on threshold.

### Overtentperature Protection

To provide protection in a fault condition, the unit is equipped with a thermal shutdown circuit. The unit will shutdown if the thermal reference point  $T_{ref}$  exceeds  $125^{\circ}C$  (typical), but the thermal shutdown is not

intended as a guarantee that the unit will survive temperatures beyond its rating. The module will automatically restart after it cools down.

### Output Voltage Programming

The output voltage of the Austin SuperLynx™ 12V can be programmed to any voltage from 0.75Vdc to 5.5Vdc by connecting a resistor (shown as  $Rtrim$  in Figure 28) between the Trim and GND pins of the module. Without an external resistor between the Trim and GND pins, the output of the module will be 0.7525Vdc. To calculate the value of the trim resistor,  $Rtrim$  for a desired output voltage, use the following equation:

$$Rtrim = \left[ \frac{10500}{V_o - 0.7525} - 1000 \right] \Omega$$

$Rtrim$  is the external resistor in  $\Omega$

$V_o$  is the desired output voltage

For example, to program the output voltage of the Austin SuperLynx™ 12V module to 1.8V,  $Rtrim$  is calculated as follows:

$$Rtrim = \left[ \frac{10500}{1.8 - 0.75} - 1000 \right]$$

$$Rtrim = 9.024k\Omega$$




Figure 28. Circuit configuration to program output voltage using an external resistor.

Austin SuperLynx™ 12Vdc can also be programmed by applying a voltage between the TRIM and GND pins (Figure 29). The following equation can be used to determine the value of  $Vtrim$  needed to obtain a desired output voltage  $V_o$ :

$$Vtrim = (0.7 - 0.0667 \times \{V_o - 0.7525\})$$

For example, to program the output voltage of a SuperLynx™ module to 3.3 Vdc,  $Vtrim$  is calculated as follows:

$$Vtrim = (0.7 - 0.0667 \times \{3.3 - 0.7525\})$$

$$Vtrim = 0.530V$$

## Feature Descriptions (continued)

### Output Voltage Programming (continued)




Figure 29. Circuit Configuration for programming Output voltage using external voltage source.

Table 1 provides  $R_{trim}$  values for some common output voltages, while Table 2 provides values of the external voltage source,  $V_{trim}$  for same common output voltages.

Table 1

$V_{o, set}$ (V)	$R_{trim}$ (KΩ)
0.7525	Open
1.2	22.46
1.5	13.05
1.8	9.024
2.5	5.009
3.3	3.122
5.0	1.472

Table 2

$V_{o, set}$ (V)	$V_{trim}$ (V)
0.7525	Open
1.2	0.670
1.5	0.650
1.8	0.630
2.5	0.583
3.3	0.530
5.0	0.4166

By using a 1% tolerance trim resistor, set point tolerance of  $\pm 2\%$  is achieved as specified in the electrical specification. The POL Programming Tool, available at [www.lineagepower.com](http://www.lineagepower.com) under the Design Tools section, helps determine the required external trim resistor needed for a specific output voltage.

The amount of power delivered by the module is defined as the voltage at the output terminals multiplied by the output current. When using the trim feature, the output voltage of the module can be increased, which at the same output current would increase the power output of the module. Care should be taken to ensure that the maximum output power of the module remains at or below the maximum rated power ( $P_{max} = V_{o, set} \times I_{o, max}$ ).

### Voltage Margining

Output voltage margining can be implemented in the Austin SuperLynx™ 12V SIP modules by connecting a resistor,  $R_{margin-up}$ , from the Trim pin to the ground pin for margining-up the output voltage and by connecting a resistor,  $R_{margin-down}$ , from the Trim pin to the Output pin for margining-down. Figure 30 shows the circuit configuration for output voltage margining. The Lynx Programming Tool, available at [www.lineagepower.com](http://www.lineagepower.com) under the Design Tools section, also calculates the values of  $R_{margin-up}$  and  $R_{margin-down}$  for a specific output voltage and % margin. Please consult your local Lineage Power technical representative for additional details.




Figure 30. Circuit Configuration for margining Output voltage.

## Feature Descriptions (continued)

### Remote Sense

The Austin SuperLynx™ 12V SIP power modules have a Remote Sense feature to minimize the effects of distribution losses by regulating the voltage at the Remote Sense pin (See Figure 31). The voltage between the Sense pin and Vo pin must not exceed 0.5V.

The amount of power delivered by the module is defined as the output voltage multiplied by the output current ( $V_o \times I_o$ ). When using Remote Sense, the output voltage of the module can increase, which if the same output is maintained, increases the power output by the module. Make sure that the maximum output power of the module remains at or below the maximum rated power. When the Remote Sense feature is not being used, connect the Remote Sense pin to output pin.




Figure 31. Remote sense circuit configuration.

## Thermal Considerations

Power modules operate in a variety of thermal environments; however, sufficient cooling should always be provided to help ensure reliable operation.

Considerations include ambient temperature, airflow, module power dissipation, and the need for increased reliability. A reduction in the operating temperature of the module will result in an increase in reliability. The thermal data presented here is based on physical measurements taken in a wind tunnel. The test set-up is shown in Figure 33. Note that the airflow is parallel to the long axis of the module as shown in figure 32. The derating data applies to airflow in either direction of the module's long axis.




Figure 32.  $T_{ref}$  Temperature measurement location.

The thermal reference point,  $T_{ref}$  used in the specifications is shown in Figure 32. For reliable operation this temperature should not exceed 115°C.

The output power of the module should not exceed the rated power of the module ( $V_o, \text{set } x I_o, \text{max}$ ).

Please refer to the Application Note "Thermal Characterization Process For Open-Frame Board-Mounted Power Modules" for a detailed discussion of thermal aspects including maximum device temperatures.




Figure 33. Thermal Test Set-up.

## Heat Transfer via Convection

Increased airflow over the module enhances the heat transfer via convection. Thermal derating curves showing the maximum output current that can be delivered at different local ambient temperature ( $T_A$ ) for airflow conditions ranging from natural convection and up to 2m/s (400 ft./min) are shown in the Characteristics Curves section.

## **Post solder Cleaning and Drying Considerations**

Post solder cleaning is usually the final circuit-board assembly process prior to electrical board testing. The result of inadequate cleaning and drying can affect both the reliability of a power module and the testability of the finished circuit-board assembly. For guidance on appropriate soldering, cleaning and drying procedures, refer to *Board Mounted Power Modules: Soldering and Cleaning Application Note*.

## **Through-Hole Lead-Free Soldering Information**


The RoHS-compliant through-hole products use the SAC (Sn/Ag/Cu) Pb-free solder and RoHS-compliant components. They are designed to be processed through single or dual wave soldering machines. The pins have an RoHS-compliant finish that is compatible with both Pb and Pb-free wave soldering processes. A maximum preheat rate of 3°C/s is suggested. The wave preheat process should be such that the temperature of the power module board is kept below 210°C. For Pb solder, the recommended pot temperature is 260°C, while the Pb-free solder pot is 270°C max. Not all RoHS-compliant through-hole products can be processed with paste-through-hole Pb or Pb-free reflow process. If additional information is needed, please consult with your Lineage Power technical representative for more details.

## Mechanical Outline

Dimensions are in millimeters and (inches).

Tolerances: x.x mm ± 0.5 mm (x.xx in. ± 0.02 in.) [unless otherwise indicated]

x.xx mm ± 0.25 mm (x.xxx in. ± 0.010 in.)




Pin	Function
1	V <sub>o</sub>
2	V <sub>o</sub>
3	V <sub>o,sense</sub>
4	V <sub>o</sub>
5	GND
6	GND
7	V <sub>IN</sub>
8	V <sub>IN</sub>
9	TRIM
10	ON/OFF

## Recommended Pad Layout

Dimensions are in millimeters and (inches).

Tolerances: x.x mm ± 0.5 mm (x.xx in. ± 0.02 in.) [unless otherwise indicated]

x.xx mm ± 0.25 mm (x.xxx in. ± 0.010 in.)



RECOMMENDED HOLE PATTERN  
COMPONENT-SIDE FOOTPRINT

Pin	Function
1	V <sub>o</sub>
2	V <sub>o</sub>
3	V <sub>o,sense</sub>
4	V <sub>o</sub>
5	GND
6	GND
7	V <sub>IN</sub>
8	V <sub>IN</sub>
9	TRIM
10	ON/OFF

## Ordering Information

Please contact your Lineage Power Sales Representative for pricing, availability and optional features.

**Table 3. Device Codes**

Device Code	Input Voltage Range	Output Voltage	Output Current	Efficiency 3.3V @ 16A	Connector Type	Comcodes
AXA016A0X3	10 – 14Vdc	0.75 – 5.5dc	16 A	92.0%	TH	108982653
AXA016A0X3Z	10 – 14Vdc	0.75 – 5.5dc	16 A	92.0%	TH	CC109104832

-Z refers to RoHS-compliant versions.

**Table 4. Device Option**

Option*	Suffix**
Long Pins 5.08 mm ± 0.25mm (0.200 in. ± 0.010 in.)	5

\* Contact Lineage Power Sales Representative for availability of these options, samples, minimum order quantity and lead times

\*\* When adding multiple options to the product code, add suffix numbers in the descending order



**World Wide Headquarters**  
**Lineage Power Corporation**  
601 Shiloh Road, Plano, TX 75074, USA  
**+1-800-526-7819**  
(Outside U.S.A.: **+1-972-244-9428**)  
[www.lineagepower.com](http://www.lineagepower.com)  
e-mail: [techsupport1@lineagepower.com](mailto:techsupport1@lineagepower.com)

**Asia-Pacific Headquarters**  
Tel: +65 6593 7211

**Europe, Middle-East and Africa Headquarters**  
Tel: +49 898 780 672 80

**India Headquarters**  
Tel: +91 80 28411633

Lineage Power reserves the right to make changes to the product(s) or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Lineage Power DC-DC products are protected under various patents. Information on these patents is available at [www.lineagepower.com/patents](http://www.lineagepower.com/patents).

© 2009 Lineage Power Corporation, (Plano, Texas) All International Rights Reserved.