

BLA9H0912L-1200P; BLA9H0912LS-1200P(G)

LDMOS avionics power transistor

Rev. 2 — 10 January 2023

AMPLEON

Product data sheet

1. Product profile

1.1 General description

1200 W LDMOS power transistor for avionics applications in the frequency range of 960 MHz to 1215 MHz.

Table 1. Typical performance

Typical RF performance at $T_{case} = 25\text{ °C}$; $t_p = 50\text{ }\mu\text{s}$; $\delta = 2\%$; $I_{DQ} = 75\text{ mA}$; in a class-AB demo circuit.

Test signal	f (MHz)	V _{DS} (V)	P _L (W)	G _p (dB)	η_D (%)
pulsed RF	1030	50	1200	19	60
pulsed RF at 1 dB compression	960 to 1215	50	>1050	19	57

1.2 Features and benefits







- High efficiency
- Excellent ruggedness
- Designed for avionics band operation
- Excellent thermal stability
- Easy power control
- Integrated dual sided ESD protection enables excellent off-state isolation
- High flexibility with respect to pulse formats
- Internally matched for ease of use
- For RoHS compliance see the product details on the Ampleon website

1.3 Applications

- Avionics applications in the frequency range of 960 MHz to 1215 MHz

2. Pinning information

Table 2. Pinning

Pin	Description	Simplified outline	Graphic symbol
BLA9H0912L-1200P (SOT539A)			
1	drain1		 sym117
2	drain2		
3	gate1		
4	gate2		
5	source [1]		
BLA9H0912LS-1200P (SOT539B)			
1	drain1		 sym117
2	drain2		
3	gate1		
4	gate2		
5	source [1]		
BLA9H0912LS-1200PG (SOT1248C)			
1	drain1		 sym117
2	drain2		
3	gate1		
4	gate2		
5	source [1]		

[1] Connected to flange.

3. Ordering information

Table 3. Ordering information

Type number	Package		Version
	Name	Description	
BLA9H0912L-1200P	-	flanged balanced ceramic package; 2 mounting holes; 4 leads	SOT539A
BLA9H0912LS-1200P	-	earless flanged balanced ceramic package; 4 leads	SOT539B
BLA9H0912LS-1200PG	-	earless flanged LDMOST ceramic package; 4 leads	SOT1248C

4. Limiting values

Table 4. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Min	Max	Unit
V_{DS}	drain-source voltage	-	106	V
V_{GS}	gate-source voltage	-6	+11	V
T_{stg}	storage temperature	-65	+150	°C
T_j	junction temperature [1]	-	225	°C

[1] Continuous use at maximum temperature will affect the reliability, for details refer to the online MTF calculator.

5. Thermal characteristics

Table 5. Thermal characteristics

Symbol	Parameter	Conditions	Typ	Unit
$Z_{th(j-mb)}$	transient thermal impedance from junction to mounting base	$T_{case} = 85\text{ °C}; P_L = 1200\text{ W}$		
		$t_p = 32\text{ }\mu\text{s}; \delta = 2\%$	0.027	K/W
		$t_p = 10\text{ }\mu\text{s}; \delta = 10\%$	0.036	K/W
		$t_p = 64\text{ }\mu\text{s}; \delta = 1\%$	0.032	K/W
		$t_p = 2.4\text{ ms}; \delta = 6.4\%$	0.126	K/W

6. Characteristics

Table 6. DC characteristics

$T_j = 25\text{ °C}$, per section unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$V_{(BR)DSS}$	drain-source breakdown voltage	$V_{GS} = 0\text{ V}; I_D = 4\text{ mA}$	106	-	-	V
$V_{GS(th)}$	gate-source threshold voltage	$V_{DS} = 10\text{ V}; I_D = 400\text{ mA}$	1.5	2.0	2.5	V
I_{DSS}	drain leakage current	$V_{GS} = 0\text{ V}; V_{DS} = 50\text{ V}$	-	-	2.8	μA
I_{DSX}	drain cut-off current	$V_{GS} = V_{GS(th)} + 3.75\text{ V}; V_{DS} = 10\text{ V}$	-	60	-	A
I_{GSS}	gate leakage current	$V_{GS} = 11\text{ V}; V_{DS} = 0\text{ V}$	-	-	280	nA
g_{fs}	forward transconductance	$V_{DS} = 10\text{ V}; I_D = 400\text{ mA}$	-	3.7	-	S
$R_{DS(on)}$	drain-source on-state resistance	$V_{GS} = V_{GS(th)} + 3.75\text{ V}; I_D = 14\text{ A}$	-	0.060	-	Ω

Table 7. RF characteristics

Test signal: pulsed RF; $f = 1030\text{ MHz}; t_p = 50\text{ }\mu\text{s}; \delta = 2\%$; RF performance at $V_{DS} = 50\text{ V}; I_{Dq} = 75\text{ mA}; T_{case} = 25\text{ °C}$; unless otherwise specified, in a class-AB production circuit.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
G_p	power gain	$P_L = 1200\text{ W}$	17.8	19	-	dB
η_D	drain efficiency	$P_L = 1200\text{ W}$	57	60	-	%
RL_{in}	input return loss	$P_L = 1200\text{ W}$	-	-15	-	dB
$P_{droop(pulse)}$	pulse droop power	$P_L = 1200\text{ W}$	-	0.2	0.5	dB

Table 7. RF characteristics ...continued

Test signal: pulsed RF; $f = 1030$ MHz; $t_p = 50$ μ s; $\delta = 2$ %; RF performance at $V_{DS} = 50$ V; $I_{Dq} = 75$ mA; $T_{case} = 25$ °C; unless otherwise specified, in a class-AB production circuit.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
t_r	rise time	$P_L = 1200$ W	-	6	50	ns
t_f	fall time	$P_L = 1200$ W	-	6	50	ns
$P_{L(2dB)}$	output power at 2 dB gain compression		-	1400	-	W

7. Test information

7.1 Ruggedness in class-AB operation


The BLA9H0912L-1200P, BLA9H0912LS-1200P and BLA9H0912LS-1200PG are capable of withstanding a load mismatch corresponding to VSWR = 20 : 1 through all phases under the following conditions: $V_{DS} = 50$ V; $I_{Dq} = 75$ mA; $P_L = 1200$ W; $t_p = 50$ μ s; $\delta = 2$ %.

7.2 Impedance information

Table 8. Typical impedance (per section)

f (MHz)	Z_S [1] (Ω)	Z_L [1] (Ω)
BLA9H0912L-1200P; BLA9H0912LS-1200P		
950	0.717 – j1.793	0.965 – j1.305
1000	0.953 – j1.886	1.049 – j1.561
1050	1.091 – j1.910	1.032 – j1.780
1100	1.353 – j0.443	1.291 – j1.952
1150	1.962 – j1.061	1.474 – j2.081
1200	0.837 – j0.936	1.514 – j2.413
BLA9H0912LS-1200PG		
950	0.864 – j4.192	1.114 – j3.604
1000	1.168 – j4.414	1.249 – j4.020
1050	1.354 – j4.560	1.267 – j4.411
1100	1.481 – j2.963	1.625 – j4.718
1150	2.274 – j3.655	1.901 – j4.980
1200	1.097 – j3.801	2.087 – j5.532

[1] Z_S and Z_L defined in [Figure 1](#).



7.3 Test circuit





Table 9. List of components
See [Figure 2](#) for component layout.


Component	Description	Value	Remarks
C1, C2, C3, C4	multilayer ceramic chip capacitor	39 pF	ATC 100B
C5, C8, C13, C17	multilayer ceramic chip capacitor	10 μF	Murata: GRM55DR61H106KA88L
C6, C9, C12, C16	multilayer ceramic chip capacitor	1 nF	ATC 100B
C7, C10, C11, C15	multilayer ceramic chip capacitor	51 pF	ATC 100B
C14, C18	electrolytic capacitor	100 μF , 63 V	
C19, C20	multilayer ceramic chip capacitor	0.5 pF	ATC 100A
C21	multilayer ceramic chip capacitor	5.6 pF	ATC 100A
C22	multilayer ceramic chip capacitor	3.0 pF	ATC 100B

Table 9. List of components ...continued
See [Figure 2](#) for component layout.

Component	Description	Value	Remarks
C23a, C23b, C24a, C24b	multilayer ceramic chip capacitor	5.1 pF	ATC 800B
C25, C26, C27, C28	multilayer ceramic chip capacitor	2.4 pF	ATC 100B
C29	multilayer ceramic chip capacitor	0.8 pF	ATC 100B
C30	multilayer ceramic chip capacitor	1.6 pF	ATC 100B
C31, C32, C33, C34, C35, C36	multilayer ceramic chip capacitor	43 pF	ATC 100B
C37, C39	multilayer ceramic chip capacitor	20 nF	ATC 200B
C38, C40	multilayer ceramic chip capacitor	1 nF	ATC 200B
H1, H2	balun transformer		Anaren: 3A412S
L1, L2	inductor	27 nH	Coilcraft: 1111SQ-27NJEB
L3, L4	inductor	1/2 turns, D = 1.5 mm, 8.9 nH	8 mm copper wire
R1, R2	resistor	5 Ω	SMD 0603
R3	resistor	5 mΩ	FC4L110R005FER


7.4 Graphical data






$V_{DS} = 50$ V; $I_{Dq} = 75$ mA; $t_p = 50$ μ s; $\delta = 2$ %.

Fig 5. Power gain as a function of output power; typical values




$V_{DS} = 50$ V; $I_{Dq} = 75$ mA; $t_p = 50$ μ s; $\delta = 2$ %.

Fig 6. Output power as a function of input power; typical values




$V_{DS} = 50$ V; $I_{Dq} = 200$ mA; $t_p = 2.4$ ms; $\delta = 6.4$ %.

Fig 7. Drain efficiency as a function of output power; typical values




$V_{DS} = 50$ V; $I_{Dq} = 200$ mA; $t_p = 2.4$ ms; $\delta = 6.4$ %.

Fig 8. Power gain as a function of output power; typical values



$V_{DS} = 50 \text{ V}$; $I_{Dq} = 200 \text{ mA}$; $t_p = 2.4 \text{ ms}$; $\delta = 6.4 \%$.

Fig 9. Output power as a function of input power; typical values



$V_{DS} = 51.6 \text{ V}$; $I_{Dq} = 100 \text{ mA}$; $P_L = P_{L(1dB)} (>1050 \text{ W})$;
 $t_p = 50 \mu\text{s}$; $\delta = 5 \%$.
 Performance measured in a dedicated broadband fixture.

Fig 10. Power gain and drain efficiency as function of frequency; typical values

8. Package outline

Flanged balanced ceramic package; 2 mounting holes; 4 leads

SOT539A




Fig 11. Package outline SOT539A

Earless flanged balanced ceramic package; 4 leads

SOT539B




Fig 12. Package outline SOT539B

Earless flanged LDMOST ceramic package; 4 leads

SOT1248C




Fig 13. Package outline SOT1248C

9. Handling information

CAUTION



This device is sensitive to ElectroStatic Discharge (ESD). Observe precautions for handling electrostatic sensitive devices.

Such precautions are described in the *ANSI/ESD S20.20*, *IEC/ST 61340-5*, *JESD625-A* or equivalent standards.

Table 10. ESD sensitivity

ESD model	Class
Charged Device Model (CDM); According to ANSI/ESDA/JEDEC standard JS-002	C2A [1]
Human Body Model (HBM); According to ANSI/ESDA/JEDEC standard JS-001	2 [2]

[1] CDM classification C2A is granted to any part that passes after exposure to an ESD pulse of 500 V.

[2] HBM classification 2 is granted to any part that passes after exposure to an ESD pulse of 2000 V.

10. Abbreviations

Table 11. Abbreviations

Acronym	Description
ESD	ElectroStatic Discharge
LDMOS	Laterally Diffused Metal-Oxide Semiconductor
LDMOST	Laterally Diffused Metal-Oxide Semiconductor Transistor
MTF	Median Time to Failure
RoHS	Restriction of Hazardous Substances
SMD	Surface Mounted Device
VSWR	Voltage Standing Wave Ratio

11. Revision history

Table 12. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
BLA9H0912L-1200P_LS-1200P_LS-1200PG v.2	20230110	Product data sheet	-	BLA9H0912L-1200P_LS-1200P v.1
Modifications:	<ul style="list-style-type: none"> • Table 2 on page 2: added BLA9H0912LS-1200PG • Table 3 on page 2: added BLA9H0912LS-1200PG • Table 5 on page 3: changed P_L value from 600 W to 1200 W • Section 7.1 on page 4: added BLA9H0912LS-1200PG • Table 8 on page 4: updated table • Figure 13 on page 11: added figure of package outline SOT1248C • Section 12.2 on page 13: updated section • Section 12.3 on page 13: updated section 			
BLA9H0912L-1200P_LS-1200P v.1	20181101	Product data sheet	-	-

12. Legal information

12.1 Data sheet status

Document status ^{[1][2]}	Product status ^[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.ampleon.com>.

12.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Ampleon does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Ampleon sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Ampleon and its customer, unless Ampleon and customer have explicitly agreed otherwise in writing. An agreement according to which the functions and qualities of Ampleon products exceed those described in the Product data sheet is invalid.

Right to make changes — Ampleon reserves the right to change information including but without limitation specifications and product descriptions published in this document at any time and without notice. This document supersedes and replaces all information regarding these products supplied prior to the publication hereof.

Suitability for use — Ampleon products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an Ampleon product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Insofar as a customer or another party nevertheless uses Ampleon products unlawfully for such purposes, Ampleon and its suppliers are not liable for any damages.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Ampleon makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Ampleon products, and Ampleon is not liable for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Ampleon product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers shall provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Ampleon is not liable related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for and shall do all necessary testing for the customer's applications and products using Ampleon products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Ampleon is not liable in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not guaranteed. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — Ampleon products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.ampleon.com/terms>, unless otherwise agreed in a valid written individual agreement. In the event of signing an individual agreement the terms and conditions of the respective agreement shall apply. Ampleon hereby expressly objects to and rejects the validity of customer's terms and conditions regarding the purchase of Ampleon products by customer.

12.3 Disclaimers

Maturity — After the relevant product(s) have passed the Release Gate in Ampleon's release process, Ampleon will confirm the final version in writing.

Limited warranty and liability — Ampleon uses its best efforts to keep the information in this document accurate and reliable. However, Ampleon gives no representations or warranties, expressed or implied, as to the accuracy or completeness of such information and assumes no liability for the consequences of the use of such information. Ampleon is not liable for content provided by an external information source.

In no event and irrespective of the legal basis (contract, tort (including negligence) statutory liability, misrepresentation, indemnity or any other area of law) shall Ampleon be liable for any indirect, incidental, punitive, special or consequential damages (including but without limitation loss of profit or revenue, loss of use or loss of production, loss of data, cost of capital, cost of substitute goods, property damage external to the Ampleon products and any damage, expenditure or loss arising out of such damage, business interruption, costs related to the removal or replacement of any products or rework charges) or any of the foregoing suffered by any third party.

Notwithstanding any damages that customer might incur for any reason whatsoever, Ampleon's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Ampleon.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Non-automotive qualified products — Unless this data sheet expressly states that this specific Ampleon product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Ampleon is not liable for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer breaches this and uses the products for design and use in automotive applications in accordance with automotive specifications and standards, (a) Ampleon gives no warranty, representation

or other guarantees of any kind with respect to such automotive applications, use and specifications, and (b) such use is solely and exclusively at customer's own risk, and (c) customer fully indemnifies Ampleon against any and all liability, damages or failed product claims, including against third parties, arising out of customer's design and use of the product for automotive applications.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

12.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

13. Contact information

For more information, please visit: <http://www.ampleon.com>

For sales office addresses, please visit: <http://www.ampleon.com/sales>

14. Contents

1 **Product profile** 1

1.1 General description 1

1.2 Features and benefits 1

1.3 Applications 1

2 **Pinning information** 2

3 **Ordering information** 2

4 **Limiting values** 3

5 **Thermal characteristics** 3

6 **Characteristics** 3

7 **Test information** 4

7.1 Ruggedness in class-AB operation 4

7.2 Impedance information 4

7.3 Test circuit 5

7.4 Graphical data 6

8 **Package outline** 9

9 **Handling information** 12

10 **Abbreviations** 12

11 **Revision history** 12

12 **Legal information** 13

12.1 Data sheet status 13

12.2 Definitions 13

12.3 Disclaimers 13

12.4 Trademarks 14

13 **Contact information** 14

14 **Contents** 15

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© Ampleon Netherlands B.V. 2023. All rights reserved.

For more information, please visit: <http://www.ampleon.com>
 For sales office addresses, please visit: <http://www.ampleon.com/sales>

Date of release: 10 January 2023

Document identifier: BLA9H0912L-1200P_LS-1200P_LS-1200PG