



Driver Characteristics

Parameter	Rating	Units
V _{OFFSET}	600	V
I _{O +/-} (Source/Sink)	1.4 / 1.8	A
V _{BIAS}	10-20	V

Features


- Floating Channel for Bootstrap Operation to +600V with an Absolute Maximum Rating of +700V
- Programmable Dead-Time
- Outputs Can Source 1.4A and Sink 1.8A
- Gate Drive Supply Range From 10V to 20V
- Tolerant to Negative Voltage Transients: dV/dt Immune
- 3.3V and 5V Logic Compatible
- Undervoltage Lockout for Both High-side and Low-Side Outputs
- Matched Propagation Delays

Applications

- Switch Mode Power Supply
- Motor Driver Inverter
- DC/DC Converter
- Uninterruptible Power Supplies (UPS)




IX21844 Functional Block Diagram



1. Specifications	3
1.1 Package Pinout	3
1.2 Pin Description (DIP & SOIC)	3
1.3 Absolute Maximum Ratings	4
1.4 Recommended Operating Conditions	4
1.5 Static Electrical Characteristics	5
1.6 Dynamic Electrical Characteristics	5
1.7 Test Waveforms	6
2. Performance Characteristics	7
3. Manufacturing Information	12
3.1 Moisture Sensitivity	12
3.2 ESD Sensitivity	12
3.3 Reflow Profile	12
3.4 Board Wash	12
3.5 Mechanical Dimensions	13

1 Specifications

1.1 Package Pinout



1.2 Pin Description (DIP & SOIC)

Pin#	Name	Description
1	IN	Logic input for both high-side gate drive output (HO) and low-side gate drive output (LO). In phase with HO.
2	\overline{SD}	Shut-down logic input. Active low.
3	V_{ss}	Logic ground
4	DT	Programmable Dead-Time input
5	COM	Low-side return
6	LO	Low-side gate drive output
7	V_{cc}	Low-side and logic supply
8	N/C	No connection
9	N/C	No connection
10	N/C	No connection
11	V_s	High-side floating supply return
12	HO	High-side gate drive output
13	V_B	High-side floating supply
14	N/C	No connection

1.3 Absolute Maximum Ratings

Absolute maximum ratings indicate sustained limits beyond which damage to the device may occur. All voltage parameters are absolute voltages referenced to COM.

Parameter	Symbol	Min	Max	Units
High-Side Floating Absolute Voltage	V_B	-0.3	700	V
High-Side Floating Supply Offset Voltage	V_S	V_B-20	$V_B+0.3$	
High-Side Floating Output Voltage	V_{HO}	$V_S-0.3$	$V_B+0.3$	
Low-Side and Logic Fixed Supply Voltage	V_{CC}	-0.3	20	
Low-Side Output Voltage	V_{LO}	-0.3	$V_{CC}+0.3$	
Programmable Dead-Time Pin Voltage	DT	$V_{SS}-0.3$	$V_{CC}+0.3$	
Logic Input Voltage	V_{IN}, V_{SD}	$V_{SS}-0.3$	$V_{CC}+0.3$	
Logic ground	V_{SS}	$V_{CC}-20$	$V_{CC}+0.3$	
Allowable Offset Supply Voltage Transient	dV_S/dt	-	50	V/ns
Package Power Dissipation @ $T_A = 25^\circ\text{C}$	PD	-	1.6	W
14-Pin SOIC		-	1	
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	-	75	$^\circ\text{C}/\text{W}$
14-Pin SOIC		-	120	
Junction Temperature	T_J	-	150	$^\circ\text{C}$
Storage Temperature	T_S	-50	150	
Lead Temperature (Soldering, 10 Seconds)	T_L	-	300	

1.4 Recommended Operating Conditions

For proper operation, the device should be used within the recommended conditions. The V_S and V_{SS} offset ratings are tested with all supplies biased at a 15V differential.

Parameter	Symbol	Min	Max	Units
High-Side Floating Supply Absolute Voltage	V_B	V_S+10	V_S+20	V
High-Side Floating Supply Offset Voltage	V_S	-5	600	
High-Side Floating Output Voltage	V_{HO}	V_S	V_B	
Low-Side and Logic Fixed Supply Voltage	V_{CC}	10	20	
Low-Side Output Voltage	V_{LO}	0	V_{CC}	
Logic Input Voltage	V_{IN}, V_{SD}	V_{SS}	$V_{SS} + 5$	
Programmable Dead-Time Pin Voltage	DT	V_{SS}	V_{CC}	
Logic Ground	V_{SS}	-5	5	
Ambient Temperature	T_A	-40	+125	$^\circ\text{C}$

1.5 Static Electrical Characteristics

V_{BIAS} (V_{CC} , V_{BS})=15V, V_{SS} =COM, $DT=V_{SS}$, and $T_A=25^\circ C$ unless otherwise specified. The V_{IH} , V_{IH} , and I_{IN} parameters are referenced to V_{SS} /COM and are applicable to the respective input leads: IN and \overline{SD} . V_O and I_O are referenced to COM and are applicable to the respective output leads: HO and LO.

Parameter	Conditions	Symbol	Min	Typ	Max	Units
Logic "1" Input Voltage	$V_{CC}=10V$ to $20V$	V_{IH}	2	-	-	V
Logic "0" Input Voltage		V_{IL}	-	-	0.8	
SD Input Positive Going Threshold		$V_{SD,TH+}$	2	-	-	
SD Input Negative Going Threshold		$V_{SD,TH-}$	-	-	0.8	
High Level Output Voltage, $V_{BIAS} - V_O$	$I_O=0A$	V_{OH}	-	-	2.5	
Low Level Output Voltage, V_O	$I_O=20mA$	V_{OL}	-	-	0.2	
Offset Supply Leakage Current	$V_B=V_S=600V$	I_{LK}	-	33	60	μA
Quiescent V_{BS} Supply Current	$V_{IN}=0V$ or $5V$	I_{QBS}	20	87	150	
Quiescent V_{CC} Supply Current		I_{QCC}	0.4	1.8	2.2	mA
Logic "1" Input Bias Current	$IN=5V$	I_{IN+}	-	35	60	μA
Logic "0" Input Bias Current	$IN=0V$	I_{IN-}	-	-	1	
SD Logic "1" Input Bias Current	$V_{SD}=5V$	I_{SD+}	-	-	30	μA
SD Logic "0" Input Bias Current	$V_{SD}=0V$	I_{SD-}	-	15	60	μA
V_{CC} and V_{BS} Supply Under-voltage Positive Going Threshold	-	V_{CCUV+} V_{BSUV+}	8	8.6	9.8	V
V_{CC} and V_{BS} Supply Under-voltage Negative Going Threshold		V_{CCUV-} V_{BSUV-}	7.4	7.9	9	
Hysteresis		V_{CCUVH} V_{BSUVH}	0.3	0.7	-	
Output High Short Circuit Pulsed Current	$V_O=0V$, $PW \leq 10\mu s$	I_O+	1.4	2.2	-	A
Output Low Short Circuit Pulsed Current	$V_O=15V$, $PW \leq 10\mu s$	I_O-	1.8	2.5	-	


1.6 Dynamic Electrical Characteristics

V_{BIAS} (V_{CC} , V_{BS})=15V, $C_L=1000pF$, $T_A=25^\circ C$, $DT=V_{SS}$, and V_{SS} =COM unless otherwise specified.


Parameter	Conditions	Symbol	Min	Typ	Max	Units
Turn-On Propagation Delay	$V_S=0V$	t_{on}	-	560	900	ns
Turn-Off Propagation Delay	$V_S=0V$ or $600V$	t_{off}	-	200	400	
Shutdown propagation Delay	-	t_{SD}	-	225	400	
Delay Matching, HS & LS Turn-on		$MTon$	-	0	90	
Delay Matching, HS & LS Turn-off		$MToff$	-	0	40	
Turn-On Rise Time	$V_S=0V$	t_r	-	23	60	
Turn-Off Fall Time		t_f	-	14	35	
Dead-Time: LO Turn-off to HO Turn-on (DT_{LO-HO})	$R_{DT}=0\Omega$	DT	280	355	520	μs
& HO Turn-off to LO Turn-on (DT_{HO-LO})	$R_{DT}=200k\Omega$		4	5	6	
Dead-Time Matching: (DT_{LO-HO}) - (DT_{HO-LO})	$R_{DT}=0\Omega$	MDT	-	0	50	ns
	$R_{DT}=200k\Omega$		-	0	600	

1.7 Test Waveforms


1.7.1 Switching Time Test Circuit




1.7.2 Input/Output Timing Diagram




1.7.5 Delay Matching Waveform Definitions




1.7.3 Shutdown Waveform Definition



1.7.6 Switching Time Waveform Definitions















1.7.4 Dead-Time Waveform Definition



























1.7.7 Truth Table

IN	SD	HO	LO
1	1	H	L
0	1	L	H
X	0	L	L

2 Performance Characteristics














Figure 1. Typical Connection Diagram



3 Manufacturing Information

3.1 Moisture Sensitivity

 All plastic encapsulated semiconductor packages are susceptible to moisture ingress. IXYS Integrated Circuits Division classified all of its plastic encapsulated devices for moisture sensitivity according to the latest version of the joint industry standard, **IPC/JEDEC J-STD-020**, in force at the time of product evaluation. We test all of our products to the maximum conditions set forth in the standard, and guarantee proper operation of our devices when handled according to the limitations and information in that standard as well as to any limitations set forth in the information or standards referenced below.

Failure to adhere to the warnings or limitations as established by the listed specifications could result in reduced product performance, reduction of operable life, and/or reduction of overall reliability.

This product carries a **Moisture Sensitivity Level (MSL) rating** as shown below, and should be handled according to the requirements of the latest version of the joint industry standard **IPC/JEDEC J-STD-033**.

Device	Moisture Sensitivity Level (MSL) Rating
IX21844G / IX21844N	MSL 1

3.2 ESD Sensitivity

 This product is **ESD Sensitive**, and should be handled according to the industry standard **JESD-625**.

3.3 Reflow Profile

This product has a maximum body temperature and time rating as shown below. All other guidelines of **J-STD-020** must be observed.

Device	Maximum Temperature x Time
IX21844G (DIP)	245°C for 30 seconds
IX21844N (SOIC)	260°C for 30 seconds


3.4 Board Wash

IXYS Integrated Circuits Division recommends the use of no-clean flux formulations. However, board washing to remove flux residue is acceptable, and the use of a short drying bake may be necessary. Chlorine-based or Fluorine-based solvents or fluxes should not be used. Cleaning methods that employ ultrasonic energy should not be used.




3.5 Mechanical Dimensions


3.5.1 IX21844G 14-Pin DIP Package



3.5.2 IX21844N 14-Pin SOIC (Narrow Body) Package



3.5.3 IX21844NTR Tape & Reel Packaging


NOTES:

1. All dimensions in millimeters
2. 10 sprocket hole pitch cumulative tolerance ± 0.20 .
3. Carrier camber is within 1mm in 250mm.
4. Tape material : Black Conductive Polystyrene Alloy.
5. All dimensions meet EIA-481-C requirements.
6. Thickness : 0.30 ± 0.05 mm.

For additional information please visit our website at: www.ixysic.com

IXYS Integrated Circuits Division makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Neither circuit patent licenses nor indemnity are expressed or implied. Except as set forth in IXYS Integrated Circuits Division's Standard Terms and Conditions of Sale, IXYS Integrated Circuits Division assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including, but not limited to, the implied warranty of merchantability, fitness for a particular purpose, or infringement of any intellectual property right.

The products described in this document are not designed, intended, authorized or warranted for use as components in systems intended for surgical implant into the body, or in other applications intended to support or sustain life, or where malfunction of IXYS Integrated Circuits Division's product may result in direct physical harm, injury, or death to a person or severe property or environmental damage. IXYS Integrated Circuits Division reserves the right to discontinue or make changes to its products at any time without notice.

Specification: DS-IX21844-R01
©Copyright 2013, IXYS Integrated Circuits Division
All rights reserved. Printed in USA.
12/19/2013