

CAB400M12XM3

**1200 V, 400 A All-Silicon Carbide
Switching-Loss Optimized, Half-Bridge Module**

V_{DS}	1200 V
I_{DS}	400 A


Technical Features

- High Power Density Footprint
- High Junction Temperature (175 °C) Operation
- Low Inductance (6.7 nH) Design
- Implements Third Generation SiC MOSFET Technology Optimized for Low Switching Loss
- Silicon Nitride Insulator and Copper Baseplate

Applications

- Motor & Traction Drives
- Vehicle Fast Chargers
- Uninterruptable Power Supplies
- Smart-Grid / Grid-Tied Distributed Generation

Package 80 x 53 x 19 mm



System Benefits

- Terminal layout allows for direct bus bar connection without bends or bushings enabling a simple, low inductance design.
- Isolated integrated temperature sensing enables high-level temperature protection.
- Dedicated drain Kelvin pin enables direct drain voltage sensing for gate driver overcurrent protection.

Key Parameters ($T_c = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions	Note
$V_{DS\max}$	Drain-Source Voltage			1200	V		
$V_{GS\max}$	Gate-Source Voltage, Maximum Value	-4		+19		AC frequency $\geq 1 \text{ Hz}$	Note 1
$V_{GS\text{op}}$	Gate-Source Voltage, Recommended Operating Value	-4		+15		Static	
I_{DS}	DC Continuous Drain Current		395		A	$V_{GS} = 15 \text{ V}, T_c = 25^\circ\text{C}, T_{vj} \leq 175^\circ\text{C}$	Fig. 20
			298			$V_{GS} = 15 \text{ V}, T_c = 90^\circ\text{C}, T_{vj} \leq 175^\circ\text{C}$	Note 2
I_{SD}	DC Source-Drain Current		395			$V_{GS} = 15 \text{ V}, T_c = 25^\circ\text{C}, T_{vj} \leq 175^\circ\text{C}$	
$I_{SD\text{BD}}$	DC Source-Drain Current (Body Diode)		220			$V_{GS} = -4 \text{ V}, T_c = 25^\circ\text{C}, T_{vj} \leq 175^\circ\text{C}$	
$I_{DS\text{pulsed}}$	Maximum Pulsed Drain-Source Current			800		$t_{P\max}$ limited by $T_{j\max}$	
$I_{SD\text{pulsed}}$	Maximum Pulsed Source-Drain Current			800		$V_{GS} = 15 \text{ V}, T_c = 25^\circ\text{C}$	
$T_{vj\text{op}}$	Maximum Virtual Junction Temperature under Switching Conditions	-40		175	°C		

Note 1 If MOSFET body diode is not used, $V_{GS\max} = -8/+19 \text{ V}$

Note 2 Assumes $R_{TH\text{JC}} = 0.15 \text{ }^\circ\text{C/W}$ and $R_{DS\text{on}} = 6.4 \text{ m}\Omega$. Calculate $P_D = (T_{vj} - T_c) / R_{TH\text{JC}}$. Calculate $I_{D\max} = \sqrt{(P_D / R_{DS\text{on}})}$

MOSFET Characteristics (Per Position) ($T_c = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions	Note
V_{BRDSS}	Drain-Source Breakdown Voltage	1200			V	$V_{GS} = 0 \text{ V}, I_D = 400 \mu\text{A}$	
V_{Gsth}	Gate Threshold Voltage	1.8	2.5	3.6		$V_{DS} = V_{GS}, I_D = 92 \text{ mA}$	
			2.0			$V_{DS} = V_{GS}, I_D = 92 \text{ mA}, T_J = 175^\circ\text{C}$	
I_{DSS}	Zero Gate Voltage Drain Current		4	130	μA	$V_{GS} = 0 \text{ V}, V_{DS} = 1200 \text{ V}$	
I_{GSS}	Gate-Source Leakage Current		0.04	1.0		$V_{GS} = 15 \text{ V}, V_{DS} = 0 \text{ V}$	
R_{DSon}	Drain-Source On-State Resistance (Devices Only)		4.0	5.3	$\text{m}\Omega$	$V_{GS} = 15 \text{ V}, I_D = 400 \text{ A}$	Fig. 2 Fig. 3
			6.4			$V_{GS} = 15 \text{ V}, I_D = 400 \text{ A}, T_J = 175^\circ\text{C}$	
g_{fs}	Transconductance		278		S	$V_{DS} = 20 \text{ V}, I_{DS} = 400 \text{ A}$	Fig. 4
			260			$V_{DS} = 20 \text{ V}, I_{DS} = 400 \text{ A}, T_J = 175^\circ\text{C}$	
E_{on}	Turn-On Switching Energy, $T_J = 25^\circ\text{C}$ $T_J = 125^\circ\text{C}$ $T_J = 175^\circ\text{C}$		4.1		mJ	$V_{DS} = 600 \text{ V},$ $I_D = 400 \text{ A},$ $V_{GS} = -4 \text{ V}/15 \text{ V},$ $R_{G(ext)} = 0.0 \Omega,$ $L = 13.6 \mu\text{H}$	Fig. 11 Fig. 13
			5.0				
			5.6				
E_{off}	Turn-Off Switching Energy, $T_J = 25^\circ\text{C}$ $T_J = 125^\circ\text{C}$ $T_J = 175^\circ\text{C}$		3.9				Fig. 11 Fig. 13
			4.2				
			4.1				
R_{Gint}	Internal Gate Resistance		1.4		Ω		
C_{iss}	Input Capacitance		24.5		nF	$V_{GS} = 0 \text{ V}, V_{DS} = 800 \text{ V},$ $V_{AC} = 25 \text{ mV}, f = 100 \text{ kHz}$	Fig. 9
C_{oss}	Output Capacitance		1.0				
C_{rss}	Reverse Transfer Capacitance		50		pF		
Q_{GS}	Gate to Source Charge		256		nC	$V_{DS} = 800 \text{ V}, V_{GS} = -4 \text{ V}/15 \text{ V}$ $I_D = 400 \text{ A}$ Per IEC60747-8-4 pg. 21	
Q_{GD}	Gate to Drain Charge		308				
Q_G	Total Gate Charge		908				
R_{THJC}	FET Thermal Resistance, Junction to Case		0.15	0.16	$^\circ\text{C}/\text{W}$		Fig. 17

Body Diode Characteristics (Per Position) ($T_c = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions	Note
V_{SD}	Body Diode Forward Voltage		6.0		V	$V_{GS} = -4 \text{ V}, I_{SD} = 400 \text{ A}$	Fig. 7
			5.3			$V_{GS} = -4 \text{ V}, I_{SD} = 400 \text{ A}, T_J = 175^\circ\text{C}$	
t_{RR}	Reverse Recovery Time		44		ns	$V_{GS} = -4 \text{ V}, I_{SD} = 400 \text{ A}, V_R = 600 \text{ V}$ $di/dt = 13 \text{ A/ns}, T_J = 175^\circ\text{C}$	
Q_{RR}	Reverse Recovery Charge		6.5		μC		
I_{RR}	Peak Reverse Recovery Current		218		A		
E_{RR}	Reverse Recovery Energy, $T_J = 25^\circ\text{C}$ $T_J = 125^\circ\text{C}$ $T_J = 175^\circ\text{C}$		0.3		mJ	$V_{DS} = 600 \text{ V}, I_D = 400 \text{ A},$ $V_{GS} = -4 \text{ V}/15 \text{ V}, R_{G(ext)} = 0.0 \Omega,$ $L = 13.6 \mu\text{H}$	Fig. 14
			1.0				
			1.9				

Temperature Sensor (NTC) Characteristics

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions
R ₂₅	Rated Resistance		4.7		kΩ	T _{NTC} = 25 °C
ΔR/R	Tolerance of R ₂₅			±1	%	
P ₂₅	Maximum Power Dissipation			50	mW	

Steinhart-Hart Modified Coefficients for R/T Computation: $\frac{1}{T} = A + B \times \ln\left(\frac{R}{R_{25}}\right) + C \times \ln^2\left(\frac{R}{R_{25}}\right) + D \times \ln^3\left(\frac{R}{R_{25}}\right)$

	A	B	C	D
T _{NTC} < 25 °C	3.3540E-03	3.0013E-04	5.0852E-06	2.1877E-07
T _{NTC} ≥ 25 °C	3.3540E-03	3.0013E-04	5.0852E-06	2.1877E-07







Module Physical Characteristics

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions
R ₃₋₁	Package Resistance, M1		0.72		mΩ	T _c = 125 °C, Note 3 & 4
R ₁₋₂	Package Resistance, M2		0.63			T _c = 125 °C, Note 3 & 4
L _{stray}	Stray Inductance		6.7		nH	Between Terminals 2 and 3
T _c	Case Temperature	-40		125	°C	
W	Weight		175		g	
M _s	Mounting Torque	2.0	3.0	4.0	N·m	Baseplate, M4 bolts
		2.0	4.0	5.0		Power Terminals, M5 bolts
V _{isol}	Case Isolation Voltage	4.0			kV	AC, 50 Hz, 1 min
CTI	Comparative Tracking Index	600				
	Clearance Distance	12.5			mm	From 2 to 3, Note 4
		11.5				From 1 to Baseplate, Note 4
		5.7				From 2 to 5, Note 4
		13.7				From 5 to Baseplate, Note 4
	Creepage Distance	14.7				From 2 to 3, Note 4
		14.0				From 1 to Baseplate, Note 4
		14.7				From 2 to 5, Note 4
		14.3				From 5 to Baseplate, Note 4

Note 3 Total Effective Resistance (Per Switch Position) = MOSFET R_{DSon} + Switch Position Package Resistance.







Note 4 Numbers reference the connections from the Schematic and Package Dimensions sections of this document.

Typical Performance



Rev. -, 2019-10-31 CAB400M12XM3 4600 Silicon Dr., Durham, NC 27703
Copyright ©2019 Cree, Inc. All rights reserved. The information in this document is subject to change without notice. Cree®, the Cree logo, Wolfspeed®, and the Wolfspeed logo are registered trademarks of Cree, Inc.

Typical Performance



Typical Performance




Figure 13. MOSFET Switching Energy vs. Junction Temperature




Figure 14. Reverse Recovery Energy vs. Junction Temperature




Figure 15. MOSFET Switching Energy vs. External Gate Resistance




Figure 16. Reserve Recovery Energy vs. External Gate Resistance




Figure 17. MOSFET Junction to Case Transient Thermal Impedance,
 $Z_{th,JC}$ ($^{\circ}\text{C}/\text{W}$)




Figure 18. Forward-Bias Safe Operating Area (FBSOA)

Typical Performance




Figure 19. Reverse-Bias Safe Operating Area (RBSOA)




Figure 20. Continuous Drain Current Derating vs. Case Temperature




Figure 21. Maximum Power Dissipation Derating vs. Case Temperature






Figure 22. Typical Output Current Capability vs. Switching Frequency (Inverter Application)


Schematic and Pin Out



Package Dimension (mm)



Package Dimension (mm)



Supporting Links & Tools

- [CGD12HBXMP: XM3 Evaluation Gate Driver](#)
- [CGD12HB00D: Differential Transceiver Board for CGD12HBXMP](#)
- [CRD200DA12E-XM3: 200 kW Inverter Kit for Conduction-Optimized XM3 \(CPWR-AN30\)](#)
- [KIT-CRD-CIL12N-XM3: Dynamic Performance Evaluation Board for the XM3 Module \(CPWR-AN31\)](#)
- [CPWR-AN28: Module Mounting Application Note](#)
- [CPWR-AN29: Thermal Interface Material Application Note](#)

Notes

- This product has not been designed or tested for use in, and is not intended for use in, applications implanted into the human body nor in applications in which failure of the product could lead to death, personal injury or property damage, including but not limited to equipment used in the operation of nuclear facilities, life-support machines, cardiac defibrillators or similar emergency medical equipment, aircraft navigation or communication or control systems, or air traffic control systems.
- The SiC MOSFET module switches at speeds beyond what is customarily associated with IGBT-based modules. Therefore, special precautions are required to realize optimal performance. The interconnection between the gate driver and module housing needs to be as short as possible. This will afford optimal switching time and avoid the potential for device oscillation. Also, great care is required to insure minimum inductance between the module and DC link capacitors to avoid excessive VDS overshoot.