

## Features

- Glass passivated standard rectifiers
- Very low profile - typical height of 1.0 mm
- Low forward voltage drop
- Low leakage current
- Moisture sensitivity: level 1, per J-STD-020
- AEC-Q101 qualified
- High temperature soldering guaranteed: 260°C/10 seconds
- Halogen-free according to IEC 61249-2-21 definition



Package: eSAGA  
 (SOD-123FL)



RoHS  
 COMPLIANT

## Typical Applications

For use of general purpose rectification in lighting, cellular phones, portable devices, power supplies and other consumer applications.

## Maximum Ratings (T<sub>A</sub>=25°C unless otherwise specified)

Parameter	Symbol	F1A	F2A	F3A	F4A	F5A	F6A	F7A	Unit
Maximum Repetitive Peak Reverse Voltage	V <sub>RRM</sub>	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V <sub>RMS</sub>	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V <sub>DC</sub>	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current at TL (See Fig.1)	I <sub>F(AV)</sub>				1.0				A
Peak Forward Surge Current (8.3 ms single half sine-wave superimposed on rated load)	I <sub>FSM</sub>				40				A
Operating Junction and Storage Temperature Range	T <sub>J</sub> , T <sub>TSG</sub>			- 55 to + 150					°C

## Electrical Characteristics (T<sub>A</sub>=25°C unless otherwise specified)

Parameter	Test Conditions	Symbol	F1A	F2A	F3A	F4A	F5A	F6A	F7A	Unit
Maximum Instantaneous Forward Voltage	1 A	V <sub>F</sub>			1.0					V
Maximum DC Reverse Current at rated DC Blocking Voltage	T <sub>A</sub> =25°C T <sub>A</sub> =125°C	I <sub>R</sub>			5					µA
Typical Reverse Recovery Time	I <sub>F</sub> =0.5A, I <sub>R</sub> =1.0A, I <sub>rr</sub> =0.25A	t <sub>rr</sub>			1.8					µS
Typical Junction Capacitance	4.0 V, 1 MHz	C <sub>J</sub>			6					pF
Typical Thermal Resistance <sup>1)</sup>	Junction to Ambient	R <sub>θJA</sub>			63					
	Junction to Case	R <sub>θJC</sub>			22					°C/W
	Junction to Mount	R <sub>θJM</sub>			2					

Note:1)The thermal resistance from junction to ambient,case or mount,mounted on P.C.B with 5×5mm copper pads,2 OZ,FR4 PC

## Ratings and Characteristic Curves




Figure 1. Forward Current Derating Curve




Figure 3. Typical Reverse Characteristics




Figure 5. Typical Instantaneous Forward Characteristics




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current





Figure 4. Typical Junction Capacitance


## Package Outline Dimensions



eSAGA (SOD-123FL)

DIM	Unit: mm		Unit: inch	
	MIN	MAX	MIN	MAX
A	0.9	1.08	0.035	0.043
A1	0	0.1	0.000	0.004
B	0.85	1.05	0.033	0.041
C	0.1	0.25	0.004	0.010
D	1.7	2	0.067	0.079
E	2.9	3.1	0.114	0.122
L	0.43	0.83	0.017	0.033
HE	3.5	3.9	0.138	0.154

Soldering  
footprint



## Packing Information

### Packing quantities:

3000 pcs/Reel, 40 Reels/Box; 8mm Tape, 7" Reel

### Tape & Reel Specification

