

TSHL600-27K-12V-R16-KIT
 TSHL600-30K-12V-R16-KIT
 TSHL600-52K-12V-R16-KIT

4.4W White LED Tape Light Kit, High Output

SPECIFICATION:

Input Voltage	12 VDC
Wattage	4.4 W/ft
Output	<div style="display: flex; align-items: center;"> <div style="width: 15px; height: 15px; background-color: #FFD700; margin-right: 5px;"></div> 2700K - 320 lm/ft <div style="width: 15px; height: 15px; background-color: #FFFF00; margin-right: 5px; margin-top: 5px;"></div> 3000K - 329 lm/ft <div style="width: 15px; height: 15px; background-color: #ADD8E6; margin-right: 5px; margin-top: 5px;"></div> 5200K - 395 lm/ft </div>
CRI	90+
Dimmable	0-10V, ELV, MLV
Max. Run Length	16 ft
Field Cuttable	2" cut points
Beam Angle	120°
LED Tape Operating Temp.	-13 °F to 140 °F
LED Tape Warranty	5 year limited*
LED Tape Lifetime	50,000 hours
LED Tape Adhesive	3M™ VHB mounting adhesive on back
LED Tape Dimensions	0.39" W x 0.08" H (10mm x 2mm)
IP Rating	IP20 - dry locations onlu
Incl. Power Supply	120VAC to 12VDC, 72W Capacity



HIGH QUALITY
LED LIGHTING KITS



Applications:

- Indoor signage
- Indirect lighting
- Accent lighting
- Undercabinet
- Furniture accents

INCLUDED IN KIT



TSHL600-XX-12V-R16
16FT TAPELIGHT REEL

1 OF EACH



P72W12V
12V POWER SUPPLY

1 OF EACH



GRIPPER-TT-SC
GRIPPER-TW-SC

2 OF EACH

TSHL600-27K-12V-R16-KIT
TSHL600-30K-12V-R16-KIT
TSHL600-52K-12V-R16-KIT

4.4W White LED Tape Light Kit, High Output

WIRING DIAGRAM:

