



Main Product Characteristics

BV _{DSS}	100V
R _{DS(ON)}	3.6mΩ
I _D	140A



Schematic Diagram

Features and Benefits

- Advanced MOSFET process technology
- Ideal for high efficiency switched mode power supplies
- Low on-resistance with low gate charge
- Fast switching and reverse body recovery



Description

The GSFP10140 utilizes the latest techniques to achieve high cell density and low on-resistance. These features make this device extremely efficient and reliable for use in high efficiency switch mode power supply and a wide variety of other applications.

Absolute Maximum Ratings ($T_c=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Max.	Unit
Drain-Source Voltage	V _{DS}	100	V
Gate-Source Voltage	V _{GS}	±20	V
Drain Current-Continuous ($T_c=25^\circ\text{C}$)	I _D	140	A
Drain Current-Continuous ($T_c=100^\circ\text{C}$)		88	
Drain Current-Pulsed ¹	I _{DM}	560	A
Single Pulse Avalanche Energy ²	E _{AS}	405	mJ
Single Pulse Avalanche Current ²	I _{AS}	90	A
Power Dissipation ($T_c=25^\circ\text{C}$)	P _D	192	W
Power Dissipation-Derate above 25°C		1.54	W/°C
Thermal Resistance, Junction-to-Ambient	R _{θJA}	62	°C/W
Thermal Resistance, Junction-to-Case	R _{θJC}	0.65	°C/W
Operating Junction Temperature Range	T _J	-55 To +150	°C
Storage Temperature Range	T _{STG}	-55 To +150	°C



GSFP10140

100V N-Channel MOSFET

Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
On/Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_D=250\mu\text{A}$	100	-	-	V
Drain-Source Leakage Current	I_{DSS}	$\text{V}_{\text{DS}}=80\text{V}, \text{V}_{\text{GS}}=0\text{V}, \text{T}_J=25^\circ\text{C}$	-	-	1	μA
		$\text{V}_{\text{DS}}=80\text{V}, \text{V}_{\text{GS}}=0\text{V}, \text{T}_J=85^\circ\text{C}$	-	-	10	
Gate-Source Leakage Current	I_{GSS}	$\text{V}_{\text{GS}}=\pm20\text{V}, \text{V}_{\text{DS}}=0\text{V}$	-	-	±100	nA
Static Drain-Source On-Resistance ³	$\text{R}_{\text{DS(ON)}}$	$\text{V}_{\text{GS}}=10\text{V}, \text{I}_D=20\text{A}$	-	3.1	3.6	$\text{m}\Omega$
		$\text{V}_{\text{GS}}=4.5\text{V}, \text{I}_D=15\text{A}$	-	3.9	5.1	
Gate Threshold Voltage	$\text{V}_{\text{GS(th)}}$	$\text{V}_{\text{GS}}=\text{V}_{\text{DS}}, \text{I}_D=250\mu\text{A}$	1.2	1.6	2.5	V
Forward Transconductance	g_{fs}	$\text{V}_{\text{DS}}=10\text{V}, \text{I}_D=3\text{A}$	-	22	-	S
Dynamic and Switching Characteristics						
Total Gate Charge ^{3,4}	Q_g	$\text{V}_{\text{DS}}=50\text{V}, \text{I}_D=70\text{A}, \text{V}_{\text{GS}}=10\text{V}$	-	65.0	100	nC
Gate-Source Charge ^{3,4}	Q_{gs}		-	9.5	15	
Gate-Drain Charge ^{3,4}	Q_{gd}		-	14	21	
Turn-On Delay Time ^{3,4}	$\text{t}_{\text{d(on)}}$	$\text{V}_{\text{DD}}=50\text{V}, \text{R}_G=6\Omega, \text{V}_{\text{GS}}=10\text{V}, \text{I}_D=70\text{A}$	-	24	36	nS
Rise Time ^{3,4}	t_r		-	20	30	
Turn-Off Delay Time ^{3,4}	$\text{t}_{\text{d(off)}}$		-	45	70	
Fall Time ^{3,4}	t_f		-	25	40	
Input Capacitance	C_{iss}		-	4000	6000	pF
Output Capacitance	C_{oss}	$\text{V}_{\text{DS}}=50\text{V}, \text{V}_{\text{GS}}=0\text{V}, \text{F}=1\text{MHz}$	-	750	1150	
Reverse Transfer Capacitance	C_{rss}		-	10	15	
Gate Resistance	R_g	$\text{V}_{\text{GS}}=0\text{V}, \text{V}_{\text{DS}}=0\text{V}, \text{F}=1\text{MHz}$	-	1.8	-	Ω
Drain-Source Diode Characteristics and Maximum Ratings						
Continuous Source Current	I_s	$\text{V}_G=\text{V}_D=0\text{V}, \text{Force Current}$	-	-	140	A
Pulsed Source Current	I_{SM}		-	-	280	A
Diode Forward Voltage	V_{SD}	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_s=1\text{A}, \text{T}_J=25^\circ\text{C}$	-	-	1	V
Reverse Recovery Time	t_{rr}	$\text{V}_R=100\text{V}, \text{I}_s=10\text{A}, \text{di/dt}=100\text{A}/\mu\text{s}, \text{T}_J=25^\circ\text{C}$	-	210	-	nS
Reverse Recovery Charge	Q_{rr}		-	490	-	nC

Note:

1. Repetitive rating: Pulsed width limited by maximum junction temperature.
2. $\text{V}_{\text{DD}}=50\text{V}, \text{V}_{\text{GS}}=10\text{V}, \text{L}=0.1\text{mH}, \text{I}_{\text{AS}}=90\text{A}, \text{R}_G=25\Omega$, starting $\text{T}_J=25^\circ\text{C}$.
3. Pulse test: pulse width $\leqslant 300\text{us}$, duty cycle $\leqslant 2\%$.
4. Essentially independent of operating temperature.

Typical Electrical and Thermal Characteristic Curves




Figure 1. Typical Output Characteristics




Figure 2. Continuous Drain Current vs. T_C




Figure 3. Normalized $R_{DS(on)}$ vs. T_J




Figure 4. Normalized V_{th} vs. T_J




Figure 5. Turn-On Resistance vs. V_{GS}




Figure 6. Turn-On Resistance vs. I_D

Typical Electrical and Thermal Characteristic Curves




Figure 7. Capacitance Characteristics




Figure 8. Gate Charge Waveform




Figure 9. Normalized Transient Impedance




Figure 10. Maximum Safe Operation Area




Figure 11. Switching Time Waveform





Figure 12. EAS Waveform

Package Outline Dimensions (PPAK5x6)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MAX	MIN	MAX	MIN
A	1.200	0.850	0.047	0.031
b	0.510	0.300	0.020	0.012
C	0.300	0.200	0.012	0.008
D1	5.400	4.800	0.212	0.189
D2	4.310	3.610	0.170	0.142
E	6.300	5.850	0.248	0.230
E1	5.960	5.450	0.235	0.215
E2	3.920	3.300	0.154	0.130
e	1.27BSC		0.05BSC	
H	0.650	0.380	0.026	0.015
K	-	1.100	-	0.043
L	0.710	0.380	0.028	0.015
L1	0.250	0.050	0.009	0.002
θ	12°	0°	12°	0°