




P3M171K2K3 SiC MOS N-Channel Enhancement Mode

V_{RRM}	= 1700	V
I_D	= 6	A
$I_D (100^\circ C)$	= 4	A
$R_{DS(on)}$	= 1	Ω

SiC MOS P3M171K2K3 N-Channel Enhancement Mode

Features

- High Blocking Voltage with Low On-Resistance
- High-Frequency Operation
- Ultra-Small Q_{gd}
- 100% UIS tested



Benefits

- Improve System Efficiency
- Increase Power Density
- Reduce Heat Sink Requirements
- Reduction of System Cost

Applications

- Solar Inverters
- EV Battery Chargers
- High Voltage DC/DC Converters
- Switch Mode Power Supplies

TO-247-3

Gate	1
Drain	2
Source	3



Order Information

Part Number	Package	Marking
P3M171K2K3	TO-247-3	P3M171K2K3



Contents

Features.....	1
Benefits.....	1
Applications	1
Order Information	1
Contents.....	2
1. Maximum Ratings.....	3
2. Electrical Characteristics	4
3. Reverse Diode Characteristics	5
4. Thermal Characteristics.....	6
5. Typical Performance	6
6. Definitions	10
7. Package Outlines.....	11



1. Maximum Ratings

At $T_J = 25^\circ\text{C}$, unless specified otherwise

Parameter	Symbol	Value	Unit	Test Conditions
Drain - Source Voltage	$V_{DS\max}$	1700	V	$V_{GS} = 0\text{V}$ $I_D = 200\mu\text{A}$
Gate - Source Voltage (Dynamic)	$V_{GS\max}$	-8 / +19	V	AC ($f > 1\text{Hz}$)
Gate - Source Voltage (Static)	V_{GSop}	-3 / +15	V	Static
Continuous Drain Current	I_D	6	A	$V_{GS} = 15\text{V}$ $T_C = 25^\circ\text{C}$
		4		$V_{GS} = 15\text{V}$ $T_C = 100^\circ\text{C}$
Power Dissipation	P_D	68	W	
Operating Junction Temperature	T_J	-55 To +175	°C	
Storage Temperature	T_{stg}	-55 To +175	°C	
Solder Temperature	T_L	260	°C	
Mounting Torque	M_d	1 8.8	Nm lbf-in	M3 or 6-32 screw



2. Electrical Characteristics

At $T_J = 25^\circ\text{C}$, unless specified otherwise

Parameter	Symbol	Value			Unit	Test Conditions
		Min.	Typ.	Max.		
Drain-Source Breakdown Voltage	$V_{(\text{BR})\text{DSS}}$	1700	/	/	V	$V_{GS} = 0\text{V}$ $I_D = 200\mu\text{A}$
Gate Threshold Voltage	$V_{GS(\text{th})}$	1.8	2.2	/	V	(tested after 30ms pulse at $V_{GS} = 15\text{V}$) $V_{DS} = V_{GS}$ $I_D = 2\text{mA}$ $T_J = 25^\circ\text{C}$
		/	1.45	/	V	$V_{DS} = V_{GS}$ $I_D = 2\text{mA}$ $T_J = 175^\circ\text{C}$
Zero Gate Voltage Drain Current	I_{DSS}	/	2.6	200	μA	$V_{GS} = 0\text{V}$ $V_{DS} = 1700\text{V}$
Gate-Source Leakage Current	I_{GSS}	/	2	125	nA	$V_{GS} = 15\text{V}$ $V_{DS} = 0\text{V}$
Drain-Source On-State Resistance	$R_{DS(\text{on})}$	/	1.2	1.4	Ω	$V_{GS} = 15\text{V}$ $I_D = 2\text{A}$ $T_J = 25^\circ\text{C}$
Transconductance	g_{fs}	/	1.07	/	S	$V_{DS} = 20\text{V}$ $I_{DS} = 2\text{A}$ $T_J = 25^\circ\text{C}$
		/	1.32	/		$V_{DS} = 20\text{V}$ $I_{DS} = 2\text{A}$ $T_J = 175^\circ\text{C}$



P3M171K2K3 SiC MOS
N-Channel Enhancement Mode

Parameter	Symbol	Value			Unit	Test Conditions	
		Min.	Typ.	Max.			
Input Capacitance	C_{iss}	/	196	/	pF	$V_{GS} = 0V$ $V_{DS} = 1000V$ $f = 1MHz$ $V_{AC} = 25mV$	
Output Capacitance	C_{oss}	/	7.5	/			
Reverse Transfer Capacitance	C_{rss}	/	2.4	/			
Coss Stored Energy	E_{oss}	/	7.8	/	μJ	$V_{DS} = 1200V$ $I_{DS} = 2A$ $V_{GS} = -3 \text{ to } 15V$ $I_G = 2mA$	
Gate to Source Charge	Q_{gs}	/	1.8	/	nC		
Gate to Drain Charge	Q_{gd}	/	2.1	/			
Total Gate Charge	Q_g	/	6.2	/			

3. Reverse Diode Characteristics

At $T_J=25^\circ C$, unless specified otherwise

Parameter	Symbol	Value		Unit	Test Conditions
		Typ.	Max.		
Diode Forward Voltage	V_{SD}	5.1	/	V	$V_{GS} = -3V$ $I_{SD} = 1A$ $T_J = 25^\circ C$
		5.1	/	V	$V_{GS} = -3V$ $I_{SD} = 1A$ $T_J = 175^\circ C$
Continuous Diode Forward Current	I_S	5	/	A	$V_{GS} = -3V$



4. Thermal Characteristics

Parameter	Symbol	Value	Unit
Thermal Resistance from Junction to Case	$R_{\theta JC}$	2.2	°C/W

5. Typical Performance

At $T_J = 25^\circ\text{C}$, unless specified otherwise




Figure 1. Output Characteristics $T_J = -55^\circ\text{C}$




Figure 2. Output Characteristics $T_J = 25^\circ\text{C}$




Figure 3. Output Characteristics $T_J = 125^\circ\text{C}$




Figure 4. Output Characteristics $T_J = 175^\circ\text{C}$



P3M171K2K3 SiC MOS N-Channel Enhancement Mode




Figure 5. Normalized On-Resistance vs. Temperature




Figure 6. On-Resistance vs. Drain Current Various Temperatures




Figure 7. On-Resistance vs. Gate-Source Voltage




Figure 8. Transfer Characteristic for Various Junction Temperatures




Figure 9. Body Diode Characteristic at -55°C




Figure 10. Body Diode Characteristic at 25°C



P3M171K2K3 SiC MOS N-Channel Enhancement Mode




Figure 11. Body Diode Characteristic at 125°C




Figure 12. Body Diode Characteristic at 175°C




Figure 13. Threshold Voltage vs. Temperatures




Figure 14. Gate Charge Characteristics




Figure 15. 3rd Quadrant Characteristic at -55°C




Figure 16. 3rd Quadrant Characteristic at 25°C



P3M171K2K3 SiC MOS N-Channel Enhancement Mode




Figure 17. 3rd Quadrant Characteristic at 125 °C




Figure 18. 3rd Quadrant Characteristic at 175 °C




Figure 19. Maximum Power Dissipation Derating vs. Case Temperature




Figure 20. Output Capacitor Stored Energy




Figure 21. Capacitances vs. Drain-Source Voltage (0-200V)




Figure 22. Capacitances vs. Drain-Source Voltage (0-1000V)



P3M171K2K3 SiC MOS N-Channel Enhancement Mode

6. Definitions




Figure 23. Turn-off Transient Definitions




Figure 24. Turn-on Transient Definitions




Figure 25. Reverse Recovery Definitions






Figure 26. Vgs Transient Definitions




P3M171K2K3 SiC MOS N-Channel Enhancement Mode

7. Package Outlines



SYMBOL	DIMENSIONS			NOTES
	MIN.	NOM.	MAX.	
A	4,83	5,02	5,21	
A1	2,29	2,41	2,55	
A2	1,50	2,00	2,49	
b	1,12	1,20	1,33	
b1	1,12	1,20	1,28	
b2	1,91	2,00	2,39	6
b3	1,91	2,00	2,34	
b4	2,87	3,00	3,22	6, 8
b5	2,87	3,00	3,18	
c	0,55	0,60	0,69	6
c1	0,55	0,60	0,65	
D	20,80	20,95	21,10	4
D1	16,25	16,55	17,65	5
D2	0,51	1,19	1,35	
E	15,75	15,94	16,13	4
E1	13,46	14,02	14,16	5
E2	4,32	4,91	5,49	3
e	5,44BSC			
L	19,81	20,07	20,32	
L1	4,10	4,19	4,40	6
ØP	3,56	3,61	3,65	7
ØP1	7,19REF.			
Q	5,39	5,79	6,20	
S	6,04	6,17	6,30	

Drawing and Dimensions



Important Notice

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, PN Junction hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

PN Junction reserves the right to make changes at any time to any products or information herein, without notice. "Typical" parameters which may be provided in PN Junction data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typical" must be validated for each customer application by customer's technical experts.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of PN Junction in customer's applications. The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology, delivery terms and conditions and prices please contact your nearest PN Junction office (www.pnjsemi.com).

Warnings

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest PN Junction office.

Except as otherwise explicitly approved by PN Junction in a written document signed by authorized representatives of PN Junction, PN Junction's products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.