

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.
THIS COPT IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAT DETRIBLENTAL TO THE INTERESTS OF PANDOT CORP.

Material	High Conductivity Seamless Copper Tube		
Plating	Electro-Tin		
Wire Size	1 AWG		
Wire Type	Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric		
Wire Strip Length	11/16 in.		
Stud Size	5/16 in.		
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.		
UL Temperature Rating	90° C		
C.S.A Certified Wire Connector	Yes		
Panduit Color Code on Barrel	GREEN		
Panduit Die Index No. on Barrel	P37		
Alternate Industry Die Index No. () on Barrel	(11)		









						CORP. TINLEY PARK, ILLINOIS
						LCAS1-56F-E
01	4-03	PWS	PWS	REMOVED PANDUIT FROM BARREL MARKINGS	10790	Copper Lug - One-Hole, Short Barrel, 90° Angle Tongue
REV	DATE	BY	снк	DESCRIPTION	ECN	SCALE N/A DRAWING NO / CAD FILE LCAS1-56F-CUST