



**Mallory Sonalert Products, Inc.**

Part #: **SCE048LD2VC4B**

# Sales Outline Drawing

Revision: **A**

## Specifications:

|                        |  |                           |                             |
|------------------------|--|---------------------------|-----------------------------|
| Sound Level Category:  | Loud   | Medium                    | Soft                        |
| Mode of Operation:     | Slow Pulse   | Slow Pulse                | Slow Pulse                  |
| Pulse Rate (PPS):      | 1  | 1                         | 1                           |
| Loudness @ 2 FT:       | 85 to 95 dB(A) Typ.  | 75 to 85 dB(A) Typ.       | 65 to 75 dB(A) Typ.         |
| Frequency:             | 2000 ± 500 Hz  | 2000 ± 500 Hz             | 2000 ± 500 Hz               |
| Connection:            | T-BLOCK ONLY   | T-BLOCK; BLUE WIRE TO (-) | T-BLOCK; YELLOW WIRE TO (-) |
| Voltage Rating:        | 28 to 48 VDC   |                           |                             |
| Current Draw:          | 40mA MAX   |                           |                             |
| Housing Material:      | 6/6 Nylon, Color: Black  |                           |                             |
| Storage Temperature:   | -40° to +85° C   |                           |                             |
| Operating Temperature: | -40° to +85° C   |                           |                             |
| Panel Mounting:        | Recommended hole size is 1.25"(31.75mm). Thread front will fit standard 30mm(1.181") hole. |                           |                             |
| Knurled Nut:           | Used to attach part to panel. The max recommended torque is 10 in-lbs.                     |                           |                             |
| Weight (Typical):      | 2.1 oz (60g)   |                           |                             |
| NEMA 3R,4X, & 12:      | Approved with use of ACC03.  |                           |                             |
| cUL Recognition:       | cUL Recognized   |                           |                             |
| Options:               | Please contact factory.  |                           |                             |

## Dimensions: Inches (mm)

**ROHS Compliant**

