Search Entire Site Contact IDT | Investors | Press

Support

About IDT Products Applications

Document Search | Package Search | Parametric Search | Cross Reference Search | Green & RoHS | Calculators | Thermal Data | Reliability & Quality | Military

Home > Products > > 952911 > 952911BFLFT

Add to myIDT [?]

You may also like...

myIDT

Time is money

952911BFLFT

OIDT

Category:

952911 Generic Part: Market Group: PC CLOCK Description: PC MAIN CLOCK

ICS952911 is a 48 pin clock chip for VIA PT890 style chipsets. When used with a fanout DDR buffer, such as the 93788, it provides all the necessary clock signals for such a system. Output Features: • 2 - 0.7V current-mode differential CPU pairs • 10 - PCI, 3 free running, 33MHz • 3 - REF, 14.318MHz • 3 - 3V66, 66.66MHz • 1 -

48MHz • 1 - 24/48MHz • 2 - 25MHz @ 2.5V

Parameters

SSOP 48 (PVG48)
NA
С
3.3 V
Active
No
1000
1000

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Туре	Title	Size	Revision Date	
Misc	PC Clocks Contact Info	61 KB	05/29/2007	

Package

Description	SSOP 300 MIL, 48LD
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Green
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temprature	260°C
Rebake Conditions	N/A
Length	15.9
Mark	PVG
Width	7.5
Pitch	0.64
Thickness	2.3
Status	Active