Material	High Conductivity Seamless Copper Tube			
Plating	Electro-Tin			
Wire Size	1 AWG	63 R Ref		
Wire Type	Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric	Color coded barrel markings		
Wire Strip Length	15/16 in.	- 75±.04 PANDIII SUN		
Stud Size	1/2 in.			
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	.63±.04 - 1.75±.0253±.02 DIA (2) PLS		
UL Temperature Rating	90° C			
C.S.A Certified Wire Connector	Yes			
Panduit Color Code on Barrel	GREEN			
Panduit Die Index No. on Barrel	P37	₩ire inspection window——.88±.04 → Beveled wire entry		
Alternate Industry Die Index No. () on Barrel	(11)	36±.01 .47±.01		
CERTIFIE	(1)	9±.01		

						CORP. TINLEY PARK, ILLINOIS
00	12/02	SAB	DRL	RELEASED	10343	LCD1-12-E Copper Lug - Two-Hole, Standard Barrel
REV	DATE	BY	снк	DESCRIPTION	ECN	SCALE N/A DRAWING NO / CAD FILE LCD1-12-CUST