



190403494 C8051T622/3, C8051T326/7 Missing Clock Detector Max Increase to 800us

PCN Issue Date: 4/3/2019

Effective Date: 7/9/2019

PCN Type: Datasheet

Description of Change

Silicon Labs is pleased to announce the release of version 1.2 of the C8051T622/3 and C8051T326/7 datasheet. The changes for this revision are as follows:

- Increased maximum value of "Missing Clock Detector Timeout" parameter in Table 6.4, "Reset Electrical Characteristics," on page 30 from 750us to 800us.
- Added VBUS specification to Table 6.1, "Absolute Maximum Ratings," on page 28.
- Updated Supply Voltage footnote in Table 6.2, "Global Electrical Characteristics," on page 29.
- Removed Supply Voltage, Regulator1 in Bypass Mode specification in Table 6.2, "Global Electrical Characteristics," on page 29.
- Removed Supply Voltage, Regulator1 in Normal Mode test condition in Table 6.2, "Global Electrical Characteristics," on page 29.
- Renamed Supply Voltage parameter to VDD in Table 6.2, "Global Electrical Characteristics," on page 29.
- Increased maximum value of "Missing Clock Detector Timeout" parameter in Table 6.4, "Reset Electrical Characteristics," on page 30.
- Corrected units for Dropout Voltage in Table 6.5, "Internal Voltage Regulator Electrical Characteristics," on page 31.
- Added required settings for operation above 25 MHz in "Prefetch Engine" on page 49.
- Corrected typographical errors in Table 17.1, "Port I/O Assignment for Analog Functions," on page 99 and Table 17.2, "Port I/O Assignment for Digital Functions," on page 99.

Reason for Change

Further device characterization.

Impact on Form, Fit, Function, Quality, Reliability

There is no impact on form, fit, quality or reliability. Increasing the missing clock detector max time will increase the time it takes for the system to detect that the system clock has been held high or low and thus the missing clock detect reset will be 50us later than before.

Product Identification

C8051T326-GM
C8051T326-GMR
C8051T327-GM
C8051T327-GMR
C8051T622-GM
C8051T622-GMR
C8051T623-GM
C8051T623-GMR
CT326-PX0568GM
CT326-PX0568GMR
CT326-PX0615GM
CT326-PX0615GMR
CT326-PX0616GM

CT326-PX0616GMR
CT326-PX0672GM
CT326-PX0672GMR
CT326-PX0858GM
CT326-PX0858GMR
CT623-PM0873GM
CT623-PM0873GMR

Last Date of Unchanged Product: 7/9/2019

Qualification Samples

Available upon request.

Customer Response

Lack of acknowledgment of the PCN within 30 days constitutes acceptance of the change, Ref. JEDEC-J-STD-046.

To request further data or inquire about this notification, please contact your Silicon Labs sales representative. A list of Silicon Labs sales representatives is available at <http://www.silabs.com>.


Customers may approve early PCN acceptance by emailing approval, along with PCN # to PCNEarlyAcceptance@silabs.com

User Registration

Register today to create your account on Silabs.com. Your personalized profile allows you to receive technical document updates, new product announcements, "how-to" and design documents, product change notices (PCN) and other valuable content available only to registered users. <http://www.silabs.com/profile>

Qualification Data

Available upon request.



Disclaimer

Silicon Labs intends to provide customers with the latest, accurate, and in-depth documentation of all peripherals and modules available for system and software implementers using or intending to use the Silicon Labs products. Characterization data, available modules and peripherals, memory sizes and memory addresses refer to each specific device, and "Typical" parameters provided can and do vary in different applications. Application examples described herein are for illustrative purposes only. Silicon Labs reserves the right to make changes without further notice and limitation to product information, specifications, and descriptions herein, and does not give warranties as to the accuracy or completeness of the included information. Silicon Labs shall have no liability for the consequences of use of the information supplied herein. This document does not imply or express copyright licenses granted hereunder to design or fabricate any integrated circuits. The products are not designed or authorized to be used within any Life Support System without the specific written consent of Silicon Labs. A "Life Support System" is any product or system intended to support or sustain life and/or health, which, if it fails, can be reasonably expected to result in significant personal injury or death. Silicon Labs products are not designed or authorized for military applications. Silicon Labs products shall under no circumstances be used in weapons of mass destruction including (but not limited to) nuclear, biological or chemical weapons, or missiles capable of delivering such weapons.

Trademark Information

Silicon Laboratories Inc.®, Silicon Laboratories®, Silicon Labs®, SiLabs® and the Silicon Labs logo®, Bluegiga®, Bluegiga Logo®, Clockbuilder®, CMEMS®, DSPLL®, EFM®, EFM32®, EFR, Ember®, Energy Micro, Energy Micro logo and combinations thereof, "the world's most energy friendly microcontrollers", Ember®, EZLink®, EZRadio®, EZRadioPRO®, Gecko®, ISOModem®, Micrium, Precision32®, ProSLIC®, Simplicity Studio®, SiPHY®, Telegesis, the Telegesis Logo®, USBXpress®, Zentri and others are trademarks or registered trademarks of Silicon Labs. ARM, CORTEX, Cortex-M3 and THUMB are trademarks or registered trademarks of ARM Holdings. Keil is a registered trademark of ARM Limited. All other products or brand names mentioned herein are trademarks of their respective holders.



Silicon Laboratories Inc.
400 West Cesar Chavez
Austin, TX 78701

<http://www.silabs.com>