


## Features

- Low gate charge
- 100% avalanche tested
- Improved dv/dt capability
- RoHS compliant
- JEDEC Qualification

N-channel MOSFET		
$BV_{DSS}$	$I_D$	$R_{DS(on)}$
600V	16A	< 0.47Ω



Device	Package	Marking	Remark
GP1M016A060N	TO-3PN	GP1M016A060N	RoHS

## Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Drain-Source Voltage	$V_{DS}$	600	V
Gate-Source Voltage	$V_{GS}$	$\pm 30$	V
Continuous Drain Current  $T_C = 25\text{ }^\circ\text{C}$	$I_D$	16	A
$T_C = 100\text{ }^\circ\text{C}$		10.3	A
Pulsed Drain Current (Note 1)	$I_{DM}$	64	A
Single Pulse Avalanche Energy (Note 2)	$E_{AS}$	865	mJ
Repetitive Avalanche Current (Note 1)	$I_{AR}$	16	A
Repetitive Avalanche Energy (Note 1)	$E_{AR}$	31.2	mJ
Power Dissipation  $T_C = 25\text{ }^\circ\text{C}$	$P_D$	312	W
Derate above $25\text{ }^\circ\text{C}$		2.5	W/ $^\circ\text{C}$
Peak Diode Recovery dv/dt (Note 3)	dv/dt	4.5	V/ns
Operating Junction and Storage Temperature Range	$T_J, T_{STG}$	-55~150	°C
Maximum lead temperature for soldering purposes, 1/8" from case for 5 seconds	$T_L$	300	°C

\* Limited only by maximum junction temperature

## Thermal Characteristics







Parameter	Symbol	Value	Unit
Maximum Thermal resistance, Junction-to-Case	$R_{\theta JC}$	0.4	°C/W
Maximum Thermal resistance, Junction-to-Ambient	$R_{\theta JA}$	62.5	°C/W







**Electrical Characteristics :  $T_c=25^\circ\text{C}$ , unless otherwise noted**

Parameter	Symbol	Test condition	Min	Typ	Max	Units
<b>OFF</b>						
Drain-Source Breakdown Voltage	$\text{BV}_{\text{DSS}}$	$V_{\text{GS}} = 0 \text{ V}, I_{\text{D}} = 250 \mu\text{A}$	600	--	--	V
Zero Gate Voltage Drain Current	$I_{\text{DSS}}$	$V_{\text{DS}} = 600 \text{ V}, V_{\text{GS}} = 0 \text{ V}$	--	--	1	$\mu\text{A}$
		$V_{\text{DS}} = 480 \text{ V}, T_c = 125^\circ\text{C}$	--	--	10	$\mu\text{A}$
Forward Gate-Source Leakage Current	$I_{\text{GSSF}}$	$V_{\text{GS}} = 30 \text{ V}, V_{\text{DS}} = 0 \text{ V}$	--	--	100	nA
Reverse Gate-Source Leakage Current	$I_{\text{GSSR}}$	$V_{\text{GS}} = -30 \text{ V}, V_{\text{DS}} = 0 \text{ V}$	--	--	-100	nA
<b>ON</b>						
Gate Threshold Voltage	$V_{\text{GS(th)}}$	$V_{\text{DS}} = V_{\text{GS}}, I_{\text{D}} = 250 \mu\text{A}$	2	--	4	V
Drain-Source On-Resistance	$R_{\text{DS(on)}}$	$V_{\text{GS}} = 10 \text{ V}, I_{\text{D}} = 8 \text{ A}$	--	0.38	0.47	$\Omega$
Forward Transconductance <sup>(Note 4)</sup>	$g_{\text{FS}}$	$V_{\text{DS}} = 30 \text{ V}, I_{\text{D}} = 8 \text{ A}$	--	10	--	S
<b>DYNAMIC</b>						
Input Capacitance	$C_{\text{iss}}$	$V_{\text{DS}} = 25 \text{ V}, V_{\text{GS}} = 0 \text{ V}, f = 1.0 \text{ MHz}$	--	3039	--	pF
Output Capacitance	$C_{\text{oss}}$		--	256	--	pF
Reverse Transfer Capacitance	$C_{\text{rss}}$		--	42	--	pF
<b>SWITCHING</b>						
Turn-On Delay Time <sup>(Note 4,5)</sup>	$t_{\text{d(on)}}$	$V_{\text{DD}} = 300 \text{ V}, I_{\text{D}} = 16 \text{ A}, R_{\text{G}} = 25 \Omega$	--	74	--	ns
Turn-On Rise Time <sup>(Note 4,5)</sup>	$t_{\text{r}}$		--	61	--	ns
Turn-Off Delay Time <sup>(Note 4,5)</sup>	$t_{\text{d(off)}}$		--	190	--	ns
Turn-Off Fall Time <sup>(Note 4,5)</sup>	$t_{\text{f}}$		--	71	--	ns
Total Gate Charge <sup>(Note 4,5)</sup>	$Q_{\text{g}}$	$V_{\text{DS}} = 480 \text{ V}, I_{\text{D}} = 16 \text{ A}, V_{\text{GS}} = 10 \text{ V}$	--	53	--	nC
Gate-Source Charge <sup>(Note 4,5)</sup>	$Q_{\text{gs}}$		--	15	--	nC
Gate-Drain Charge <sup>(Note 4,5)</sup>	$Q_{\text{gd}}$		--	12	--	nC
<b>SOURCE DRAIN DIODE</b>						
Maximum Continuous Drain-Source Diode Forward Current	$I_{\text{s}}$	---	--	--	16	A
Maximum Pulsed Drain-Source Diode Forward Current	$I_{\text{SM}}$	---	--	--	64	A
Drain-Source Diode Forward Voltage	$V_{\text{SD}}$	$V_{\text{GS}} = 0 \text{ V}, I_{\text{s}} = 16 \text{ A}$	--	--	1.5	V
Reverse Recovery Time <sup>(Note 4)</sup>	$t_{\text{rr}}$	$V_{\text{GS}} = 0 \text{ V}, I_{\text{s}} = 16 \text{ A}$ $dI_{\text{F}} / dt = 100 \text{ A}/\mu\text{s}$	--	435	--	ns
Reverse Recovery Charge <sup>(Note 4)</sup>	$Q_{\text{rr}}$		--	5.8	--	$\mu\text{C}$


Note :

1. Repeated rating : Pulse width limited by safe operating area
2.  $L = 6.2 \text{ mH}$ ,  $I_{\text{AS}} = 16 \text{ A}$ ,  $V_{\text{DD}} = 50 \text{ V}$ ,  $R_{\text{G}} = 25 \Omega$ , Starting  $T_j = 25^\circ\text{C}$ , not subject to production test – verified by design/characterization
3.  $I_{\text{SD}} \leq 16 \text{ A}$ ,  $di/dt \leq 200 \text{ A}/\mu\text{s}$ ,  $V_{\text{DD}} \leq \text{BV}_{\text{DS}}$ , Starting  $T_j = 25^\circ\text{C}$
4. Pulse Test : Pulse width  $\leq 300 \mu\text{s}$ , Duty Cycle  $\leq 2\%$
5. Essentially Independent of Operating Temperature Typical Characteristics





## TO-3PN MECHANICAL DATA



SYMBOL	MIN	NOM	MAX
A	4.60	4.80	5.00
b	0.80	1.00	1.20
b1	1.80	2.00	2.20
b2	2.80	3.00	3.20
c	0.55	0.60	0.75
c1	1.45	1.50	1.65
D	15.40	15.60	15.80
E	19.70	19.90	20.10
e	5.15	5.45	5.75
L1	3.30	3.50	3.70
L2	19.80	20.00	20.20
øP1	3.30	3.40	3.50
øP2		(3.20)	
Q	2.20	2.40	2.60
q1	4.80	5.00	5.20

**Disclaimer :**

Global Power Technologies Group reserves the right to make changes without notice to products herein to improve reliability, performance, or design. The information given in this document is believed to be accurate and reliable. However, it shall in no event be regarded as a guarantee of conditions and characteristics. With respect to any information regarding the application of the device, Global Power Technologies Group hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of patent rights of any third party.