9001KP5R31 PILOT LIGHT 480VAC 30MM TYPE K +OPTIONS

K





Main Range of Product Harmony 9001K Product or Component Pilot light Туре

Complementary

Bezel material	Chromium plated metal	
Mounting diameter	1.18 in (30 mm)	
Lens type	Fresnel plastic	
Cap/operator or lens colour	Red	
Light block supply	Via transformer 380 V AC 50/60 Hz Via transformer 480 V AC 50/60 Hz	
Shape of screw head	Round	
Operating Mode	Normal	

Device short name

Environment

Product Certifications	CE	
	CSA LR25490 class 3211 03	
	UL listed file E42259 CCN NKCR	
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13	

Ordering and shipping details

21426 - 9001 K (NOT KA,KM,KX)	
CS1	
785901033127	
1	
8.00 oz (226.796 g)	
No	
MX	
	CS1 785901033127 1 8.00 oz (226.796 g) No

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	5.08 in (12.903 cm)	
Package 1 width	2.00 in (5.08 cm)	
Package 1 Length	12.90 in (32.774 cm)	

Offer Sustainability

Warranty

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

18 months