



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089

NTE6246 & NTE6247 Ultrafast Switchmode Power Rectifier, 30 Amp

Features:

- Low Forward Drop
- Current Derating Specified at both Case and Ambient Temperatures

Applications:

- Switching Power Supplies
- Inverters
- For use as Free Wheeling Diodes

Absolute Maximum Ratings:

Peak Repetitive Reverse Voltage, V_{RRM}

NTE6246	200V
NTE6247	600V

Working Peak Reverse Voltage, V_{RWM}

NTE6246	200V
NTE6247	600V

DC Blocking Voltage, V_R

NTE6246	200V
NTE6247	600V

Average Rectified Forward Current, (Rated V_R), $I_F(AV)$

Per Leg ($T_C = +150^\circ\text{C}$ (NTE6246), $T_C = +145^\circ\text{C}$ (NTE6247))	15A
Per Device ($T_C = +150^\circ\text{C}$ (NTE6246), $T_C = +145^\circ\text{C}$ (NTE6247))	30A

Peak Repetitive Forward Current, Per Leg, I_{FRM}

(Rated V_R , Square Wave, 20kHz), $T_C = +150^\circ\text{C}$ (NTE6246), $T_C = +145^\circ\text{C}$ (NTE6247) . 30A

Nonrepetitive Peak Surge Current, I_{FSM}

(Surge applied at rated load conditions halfwave, single phase, 60Hz) Per Leg

NTE6246	200A
NTE6247	150A

Operating Junction Temperature Range, T_J

-65° to $+175^\circ\text{C}$

Storage Temperature Range, T_{stg}

-65° to $+175^\circ\text{C}$

Maximum Thermal Resistance (Per Diode Leg)

Junction-to-Case, R_{thJC}	1.5°C/W
Junction-to-Ambient, R_{thJA}	40°C/W

Electrical Characteristics (Per Diode Leg):

Maximum Instantaneous Forward Voltage, v_F

($i_F = 15A$, $T_C = +150^\circ C$, Note 1)

NTE6246 0.85V

NTE6247 1.2V

($i_F = 15A$, $T_C = +25^\circ C$, Note 1)

NTE6246 1.05V

NTE6247 1.5V

Maximum Instantaneous Reverse Current, i_R

(Rated DC Voltage, $T_C = +150^\circ C$, Note 1)

NTE6246 500 μA

NTE6247 1000 μA

(Rated DC Voltage, $T_C = +25^\circ C$, Note 1) 10 μA

Maximum Reverse Recovery Time, t_{rr}

($I_F = 1A$, $di/dt = 50A/\mu s$)

NTE6246 35ns

NTE6247 60ns

Note 1. Pulse Test: Pulse Width = 300 μs , Duty Cycle $\leq 2\%$.

