



## **NTE3029B Infrared-Emitting Diode**

### **Description:**

The NTE3029B is a 940nm LED encapsulated in a clear, wide angle, sidelooker package.

### **Features:**

- Good Optical to Mechanical Alignment
- High Irradiance Level

### **Absolute Maximum Ratings:** ( $T_A = +25^\circ\text{C}$ unless otherwise specified)

Forward Current, $I_F$			
Continuous .....	.....	60mA	
Peak (PW, 1μs; ≤ 33Hz) .....	.....	3A	
Reverse Voltage, $V_R$ .....	.....	6V	
Power Dissipation, $P_D$ .....	.....	100mW	
Derate Linearly Above $25^\circ\text{C}$ .....	.....	1.33mW/°C	
Operating Temperature Range, $T_{opr}$ .....	.....	-55° to +100°C	
Storage Temperature Range, $T_{stg}$ .....	.....	-55° to +100°C	
Lead Temperature (During Soldering, 1/16" from case, 5sec), $T_L$ .....	.....	+240°C	

### **Electrical Characteristics:** ( $T_A = +25^\circ\text{C}$ , Note 1 unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Forward Voltage	$V_F$	$I_F = 60\text{mA}$	-	-	1.7	V
Reverse Breakdown Voltage	$V_R$	$I_R = 10\mu\text{A}$	6	-	-	V
Reverse Leakage Current	$I_R$	$V_R = 5\text{V}$	-	-	10	$\mu\text{A}$
Peak Emission Wavelength	$\lambda_P$	$I_F = 100\text{mA}$	-	940	-	nm
Emission Angle at 1/2 Power	$\theta$		-	±35	-	deg.
Radiant Intensity	$I_e$	$I_F = 20\text{mA}$ , Note 2	0.28	-	-	mW/sr

Note 1. All measurements are made under pulse conditions.

Note 2. Radiant Intensity is measured with a 0.45cm aperture placed 1.6cm from the tip of the lens centerline perpendicular to the plane of the leads.

