

SkelStart 24V

### MORE STARTING POWER

ULTRACAPACITORS HAVE MULTIPLE BENEFITS OVER BATTERIES




# ULTRACAPACITOR-BASED SPACE TECHNOLOGY THAT STARTS YOUR ENGINE

#### ULTRACAPACITORS USE ELECTRIC FIELD (FAST)



- \* ALMOST INSTANT CHARGING AND DISCHARGING
- **+ HIGH POWER**
- + LOW ENERGY
- NOT TEMPERATURE SENSITIVE
- LONG LIFETIME

### BATTERIES USE A CHEMICAL REACTION (SLOW)



- SLOW CHARGING AND DISCHARGING
- + LOW POWER
- + HIGH ENERGY
- **+ TEMPERATURE SENSITIVE**
- + SHORT LIFETIME

### THE SKELSTART ENGINE START MODULE

ALWAYS PROVIDES THE STARTING POWER, WHILE BATTERIES HANDLE ALL THE OTHER LOADS.

### ADVANTAGES & DISADVANTAGES







HIGH POWER (FOR STARTING)







HIGH ENERGY (FOR HOTEL LOADS)







ZERO TO FULL IN MINUTES

**LONG LIFETIME** 











WORKS IN EXTREME TEMPERATURES

(1000000 CYCLES)





### WHAT DOES IT MEAN FOR THE USER?

### **RELIABLE STARTING**

- Much higher peak power than batteries can provide
- Temperature won't affect starting power
- + Starting power even with "dead" batteries If SkelStart energy is used, it needs only 18V to be recharged again. SkelStart will be fully charged in few minutes.

### BATTERY LIFETIME INCREASE

- Starting power doesn't come directly from batteries
- More energy stored by the end of the work day
- Battery lifetime will be increased 1.5 2x

### FUEL CONSUMPTION DECREASE

- + No need for idling to charge the batteries
- Measured example: Idling fuel consumption from 6% to 2% = 400L/year

### NO HASSLE -ONE TIME INVESTMENT

- Lifetime 1M cycles, no maintenance needed
- Warranty 6 years

### **REAL LIFE USE CASE:**


"I used to idle my truck almost every day while I was cooking or watching TV - just to avoid surprises the next morning. Having SkelStart is like having an ace in my back pocket - whatever the weather, or the status of my batteries, I can still start the truck. I can also feel the engine cranking much faster now. I got SkelStart installed on a 2011 Scania R620 that I plan to replace in few years - thankfully SkelStart has a long lifetime and 6 years of warranty, so I can just install it to my next truck."

- Rainer, Lundens Frakt. Göteborg, Sweden.





SkelStart is based on Skeleton Technologies' industry-leading SkelCap ultracapacitors, which have the highest power and energy density on the market. This advantage carries over to SkelStart, making it the most powerful engine start module on the market.



#### **SKELSTART**

### **EASY INSTALLATION**

Skelstart is installed between the batteries and the starter, which means the batteries are disconnected from the starter.

Skelstart will always provide the starting power for the engine, and the batteries will only need to provide energy for lights, air conditioning, heating, etc.

## SkelStart





### **SPECIFICATIONS**

| SkelStart 24V   | Unit               |                          |
|---|--------------------|--------------------------|
| Cold Cranking Amps (CCA)*                                 | А                  | 1206                     |
| Maximum Peak Current<br>(0.4 sec current)                 | А                  | 4353                     |
| Peak Power**  | kW                 | 104                      |
| Charged full voltage                                      | V                  | 28.2                     |
| Energy  | Wh                 | 35                       |
| Rated Capacitance   | F                  | 320                      |
| Individual Cell Capacitance                               | F                  | 3200                     |
| Charging current  | А                  | 16 (max)                 |
| Continuous input<br>voltage range                         | V                  | 18-32                    |
| Continuous input voltage range with specified charge time | V                  | 23-32                    |
| Recharge time (from 0 V)                                  | min                | 10                       |
| Operating temperature                                     | Deg <sup>o</sup> C | -40 to +65               |
| Standby current draw                                      | mA                 | <10                      |
| Dimensions  | mm                 | 328 L x 171 W x<br>241 H |
| Weight  | kg                 | 8.5                      |

<sup>\*</sup> Based on 1s ESR

<sup>\*\*</sup> Based on 10ms ESR