
Customer Information Sheet





EXAMPLE: CONNECTOR WITH 20 CONTACTS, GOLD

CONTACT AREA AND 100% TIN ON TAIL, M80-5022042P

DIM 'A' = 18.00mm, DIM 'B' = 25.00mm.

DIM 'C' = 30.0mm

www.harwin.com technical@harwin.com

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING. TENDERING OR FOR ANY

OTHER PURPOSE WITHOUT

THEIR WRITTEN PERMISSION

FINISH -

05 - GOLD

TOLERANCES

22 - SELECTIVE GOLD + TIN/LEAD

42 - SELECTIVE GOLD + 100% TIN

 $X = \pm 1$ mm $X.X = \pm 0.50 mm$ $X.XX = \pm 0.20$ mm $X.XXX = \pm 0.01$ mm

ANGLES = ±5° UNLESS STATED MATERIAL:

2.00 TYP →

FINISH: SEE ABOVE S/AREA:

SEE ABOVE

RECOMMENDED PCB LAYOUT

TOLERANCE = ± 0.05

mm²

TITLE: JACKSCREW DATAMATE DIL VERTICAL SMT MALE

- I.OO TYP

P/PLACE

CUSTOMER REF.:

ASSEMBLY DRG:

DRAWING NUMBER: M80-502XXXXP

SHT