

Description: GNSS/2x LTE/0, 1x, 2x or 3x WiFi

Direct Mount

Series: RAZORBACK

PART NUMBER: RAZ32011DM, RAZ32012DM, RAZ42111DM, RAZ42112DM, RAZ52211DM, RAZ52212DM, RAZ62311DM, RAZ62312DM



RAZ52211DM (Black)



RAZ52212DM (White)

Features:

- 2x LTE 644-2700MHz (MiMo)
- 0, 1x, 2x or 3x WiFi 2.4/5GHz
- DSRC
- · GNSS Active:
 - · Beidou, GPS, Glonass
 - RHCP polarization
 - · Amplifier Gain 30dBi
- Size: 88.5 x 195.1 x 92.6mm 3.48 x 7.68 x 3.65 in
- Power withstanding 45W
- Available Models
- RAZ32011DM = 3 Cable, Black RAZ32012DM = 3 Cable, White RAZ42111DM = 4 Cable, Black RAZ42112DM = 4 Cable, White RAZ52211DM = 5 Cable, Black RAZ52212DM = 5 Cable, White RAZ62311DM = 6 Cable, Black RAZ62312DM = 6 Cable, White

Applications:

- · Vehicular use Telematics
- Fleet management
- Trucking
- Navigation, GIS and survey
- Public safety
- Search and Rescue
- Metering, Utility boxes

Issue: 1827

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden. For more information:

Pulse Worldwide Headquarters 15255 Innovation Drive #100 San Diego, CA 92128 USA Tel:1-858-674-8100 Pulse/Larsen Antennas 18110 SE 34th St Bldg 2 Suite 250 Vancouver, WA 98683 USA Tel: 1-360-944-7551 Europe Headquarters Pulse GmbH & Do, KG Zeppelinstrasse 15 Herrenberg, Germany Tel: 49 7032 7806 0 Pulse (Suzhou) Wireless Products Co, Inc. 99 Huo Ju Road(#29 Bldg,4th Phase Suzhou New District Jiangsu Province, Suzhou 215009 PR China Tel: 86 512 6807 9998



Description: GNSS/2x LTE/0, 1x, 2x or 3x WiFi

Direct Mount

Series: RAZORBACK

PART NUMBER: RAZ32011DM, RAZ32012DM, RAZ42111DM, RAZ42112DM, RAZ52211DM, RAZ52212DM, RAZ62311DM, RAZ62312DM

ELECTRICAL SPECIFICATIONS

(40) ground plane
1	1 (40**

Frequency (2x LTE) 644-960/1710-2700 MHz
Frequency (1x, 2x or 3x WiFi) 2400-2500/4900-5925 MHz

Nominal Impedance 50 Ω VSWR 2:1 Radiation Pattern Omni HPBW / Vertical Plane (LTE, 644-960) 42° HPBW / Vertical Plane (LTE, 1710-2700) 31°

HPBW / Vertical Plane (WIFI, 2400-2500) 25° HPBW / Vertical Plane (WIFI, 4900-5925) 20°

Polarization Vertical

Average Peak Gain (LTE, 644-960) (LTE, 1710-2700) 4.6/4.9 dBi

Average Peak Gain (WIFI, 2400-2500) (WIFI, 4900-5925) 6/6.6 dBi

Isolation (LTE1 to LTE2) <-13
Isolation (WiFi1/2, WiF2/3 & WiFi1/3) <-13
Average Efficiency (LTE) 67 %

Average Efficiency (WiFi) 57 %
Power Withstanding 45 W

GNSS Beidou-GPS-Glonass

Frequency 1561.098±2.046,1575.42±1.023,1602.5625±4 MHz

VSWR 2:1 Nominal Impedance 50 Ω

Gain (Radiating element)

1 dBic +/- 1dB

30 dB +/- 2 dB

Polarization RHCP





Description: GNSS/2x LTE/0, 1x, 2x or 3x WiFi

Direct Mount

Series: RAZORBACK

PART NUMBER: RAZ32011DM, RAZ32012DM, RAZ42111DM, RAZ42112DM, RAZ52211DM, RAZ52212DM, RAZ62311DM, RAZ62312DM

ELECTRICAL SPECIFICATIONS

Out of Band Rejection 960MHz >65 dB, 1710MHz >60 dB,

2170MHz >65 dB, 2400MHz >65 dB

Noise Figure < 2.4dB

Operating Voltage $3.3 - 5 \text{ Vdc} \pm 0.5 \text{ V}$

Current Consumption < 11 mA

MECHANICAL SPECIFICATIONS

Length/Height/Width 195.1mm (7.68")/92.6 (3.65")/88.5mm (3.48")

Weight 856 g (1.9 lbs)

Antenna Color / Material Black or White / PC/ABS, UV protected

Cable / Connector 2x LTE, 5.2m (17') LMR-195/SMA-Male

1x, 2x or 3x WiFi, 5.2m (17') LMR-195/RP-SMA-Male

GNSS, 5.2m (17') RG-174/SMA-Male

Mounting Configuration Ø22.3mm (7/8") Hole required

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature -40/+85° C

Ingress Protection IP67

RoHS Compliant Yes

OTHER SPECIFICATIONS

Total cable assembly loss for 5.2m (17') LMR-195 @ 850MHz	2.1 dB
Total cable assembly loss for 5.2m (17') RG-174 @ 1575MHz	6.0 dB
Total cable assembly loss for 5.2m (17') LMR-195 @ 1930MHz	3.2 dB
Total cable assembly loss for 5.2m (17') LMR-195 @ 2500MHz	3.7 dB
Total cable assembly loss for 5.2m (17') LMR-195 @ 2450MHz	3.6 dB
Total cable assembly loss for 5.2m (17') LMR-195 @ 5350MHz	5.5 dB






Description: GNSS/2x LTE/0, 1x, 2x or 3x WiFi

Direct Mount

Series: RAZORBACK

PART NUMBER: RAZ32011DM, RAZ32012DM, RAZ42111DM, RAZ42112DM, RAZ52211DM, RAZ52212DM, RAZ62311DM, RAZ62312DM

MECHANICAL DRAWING



All dimensions are in mm / inches

Issue: 1827

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION





Description: GNSS/2x LTE/0, 1x, 2x or 3x WiFi

Direct Mount

Series: RAZORBACK

PART NUMBER: RAZ32011DM, RAZ32012DM, RAZ42111DM, RAZ42112DM, RAZ52211DM, RAZ52212DM, RAZ62311DM, RAZ62312DM

MECHANICAL DRAWING

Vehicular Multiband Antenna with Direct Mount

(Part Number)













(1)











1	Product ID: RAZORBACK				
2	Total Number of Cable leads				
3	Total Number of LTE Cable Leads				
4	Total Number of WiFi Cable Leads				
(5)	Total Number of GPS Cable Leads				
	The Color of the Plastic Housing				
6	1=Black; 2= White				
7	Mounting: Direct Mount; 7/8" Hole Required				

RAZXXXXXDM		CABLE	CABLE LENGTH	CONNECTOR
1	LTE-1 Cable Assy			OMA Mala
2	LTE-2 Cable Assy	LMR195	5181 mm /	SMA Male
3	WiFi-1 Cable Assy			
4	WiFi-2 Cable Assy		204" /	RP-SMA Male
5	WiFi-3 Cable Assy		17 FT	
6	GPS Cable Assy	RG-174		SMA Male

All dimensions are in mm / inches



Description: GNSS/2x LTE/0, 1x, 2x or 3x WiFi

Direct Mount


Series: RAZORBACK

PART NUMBER: RAZ32011DM, RAZ32012DM, RAZ42111DM, RAZ42112DM, RAZ52211DM, RAZ52212DM, RAZ62311DM, RAZ62312DM

CHARTS

VSWR vs Frequency RAZ62311DM Measured with 17' cables on Ø40" GP

LTE 1 & 2 Measured with 5.2m (17') cable



Return loss vs Frequency RAZ62311DM Measured with 17' cables on Ø40" GP

Measured at Pulse, USA - July 07, 2017 0 -5 -10 Return loss -15 -20 -25 -30 -35 -40 Freq (MHz) LTE 1 —LTE 2 ---- Isolation

LTE 1 & 2 Measured with 5.2m (17') cable



Description: GNSS/2x LTE/0, 1x, 2x or 3x WiFi

Direct Mount

Series: RAZORBACK


Measured with 5.2m

(17') cable


PART NUMBER: RAZ32011DM, RAZ32012DM, RAZ42111DM, RAZ42112DM, RAZ52211DM, RAZ52212DM, RAZ62311DM, RAZ62312DM

CHARTS

VSWR vs Frequency RAZ62311DM Measured with 17' cables on Ø40" GP (WiFi 1, 2 &3)



Return loss vs Frequency RAZ62311DM Measured with 17' cables on Ø40" GP (WiFi 1, 2 &3)



Issue: 1827

WiFi 1, 2 & 3

Measured with 5.2m

(17') cable



Description: GNSS/2x LTE/0, 1x, 2x or 3x WiFi

Direct Mount


Series: RAZORBACK

PART NUMBER: RAZ32011DM, RAZ32012DM, RAZ42111DM, RAZ42112DM, RAZ52211DM, RAZ52212DM, RAZ62311DM, RAZ62312DM

CHARTS

Peak Gain vs Frequency RAZ62311DM Measured with 4" cables on Ø40" GP (LTE 1)

Measured at Pulse, USA - Aug 04, 2017




LTF 1 Measured with 102mm (4") cable

Efficiency vs Frequency

640-960

RAZ62311DM Measured with 4" cables on Ø40" GP (LTE 1) Measured at Pulse, USA - aUG 04, 2017



LTE 1 Measured with 102mm (4") cable




Description: GNSS/2x LTE/0, 1x, 2x or 3x WiFi

Direct Mount

Series: RAZORBACK

PART NUMBER: RAZ32011DM, RAZ32012DM, RAZ42111DM, RAZ42112DM, RAZ52211DM, RAZ52212DM, RAZ62311DM, RAZ62312DM



Issue: 1827

2500

1930

800

240

210

180

150

Theta Angle (°)



Description: GNSS/2x LTE/0, 1x, 2x or 3x WiFi

Direct Mount


Series: RAZORBACK

PART NUMBER: RAZ32011DM, RAZ32012DM, RAZ42111DM, RAZ42112DM, RAZ52211DM, RAZ52212DM, RAZ62311DM, RAZ62312DM

CHARTS

Peak Gain vs Frequency RAZ62311DM Measured with 4" cables on Ø40" GP (LTE 2)


Measured at Pulse, USA - Aug 04, 2017



LTF 2 Measured with 102mm (4") cable

Efficiency vs Frequency RAZ62311DM Measured with 4" cables on Ø40" GP (LTE 2)

Measured at Pulse, USA - aUG 04, 2017



LTE 2 Measured with 102mm (4") cable




Description: GNSS/2x LTE/0, 1x, 2x or 3x WiFi

Direct Mount

Series: RAZORBACK

PART NUMBER: RAZ32011DM, RAZ32012DM, RAZ42111DM, RAZ42112DM, RAZ52211DM, RAZ52212DM, RAZ62311DM, RAZ62312DM

CHARTS XY plane @ Lower Band 0 800 330 30 Avg (dBi) = -3.21Peak (dBi) = -1.25Avg - 3 (deg) = 145-10 1930 300 60 Avg (dBi) = 0.00Peak (dBi) = 2.17 -20 Avg - 3 (deg) = 1492500 LTE 2 -30. Avg (dBi) = -2.64Peak (dBi) = -0.06 270 -85 Avg - 3 (deg) = 162Measured with 102mm (4") cable 240 120 210 150 800 **-**1930 -2500 Phi Angle (°) 180









Description: GNSS/2x LTE/0, 1x, 2x or 3x WiFi

Direct Mount


Series: RAZORBACK

PART NUMBER: RAZ32011DM, RAZ32012DM, RAZ42111DM, RAZ42112DM, RAZ52211DM, RAZ52212DM, RAZ62311DM, RAZ62312DM

CHARTS


Peak Gain vs Frequency RAZ62311DM Measured with 4" cables on Ø40" GP (WiFi 1)

Measured at Pulse, USA - Aug 04, 2017



WiFi 1 Measured with 102mm (4") cable

> Efficiency vs Frequency RAZ62311DM Measured with 4" cables on Ø40" GP (WiFi 1)



WiFi 1 Measured with 102mm (4") cable




Description: GNSS/2x LTE/0, 1x, 2x or 3x WiFi

Direct Mount

Series: RAZORBACK

PART NUMBER: RAZ32011DM, RAZ32012DM, RAZ42111DM, RAZ42112DM, RAZ52211DM, RAZ52212DM, RAZ62311DM, RAZ62312DM



Issue: 1827

WiFi 1

WiFi 1

180



Description: GNSS/2x LTE/0, 1x, 2x or 3x WiFi

Direct Mount


Series: RAZORBACK

PART NUMBER: RAZ32011DM, RAZ32012DM, RAZ42111DM, RAZ42112DM, RAZ52211DM, RAZ52212DM, RAZ62311DM, RAZ62312DM

CHARTS


Peak Gain vs Frequency RAZ62311DM Measured with 4" cables on Ø40" GP (WiFi 2)

Measured at Pulse, USA - Aug 04, 2017



WiFi 2
Measured with
102mm (4") cable

Efficiency vs Frequency RAZ62311DM Measured with 4" cables on Ø40" GP (WiFi 2)



WiFi 2
Measured with
102mm (4") cable

Issue: 1827

ROHS

14




Description: GNSS/2x LTE/0, 1x, 2x or 3x WiFi

Direct Mount

Series: RAZORBACK

PART NUMBER: RAZ32011DM, RAZ32012DM, RAZ42111DM, RAZ42112DM, RAZ52211DM, RAZ52212DM, RAZ62311DM, RAZ62312DM



Issue: 1827

WiFi 2

Measured with

WiFi 2

Measured with



Description: GNSS/2x LTE/0, 1x, 2x or 3x WiFi

Direct Mount


Series: RAZORBACK

PART NUMBER: RAZ32011DM, RAZ32012DM, RAZ42111DM, RAZ42112DM, RAZ52211DM, RAZ52212DM, RAZ62311DM, RAZ62312DM

CHARTS

Peak Gain vs Frequency RAZ62311DM Measured with 4" cables on Ø40" GP (WiFi 3)

Measured at Pulse, USA - Aug 04, 2017




WiFi 3 Measured with 102mm (4") cable

Efficiency vs Frequency RAZ62311DM Measured with 4" cables on Ø40" GP (WiFi 3)

2400-2500 — 4900-5925

Measured at Pulse, USA - Aug 04, 2017



WiFi 3 Measured with 102mm (4") cable




Description: GNSS/2x LTE/0, 1x, 2x or 3x WiFi

Direct Mount

Series: RAZORBACK

PART NUMBER: RAZ32011DM, RAZ32012DM, RAZ42111DM, RAZ42112DM, RAZ52211DM, RAZ52212DM, RAZ62311DM, RAZ62312DM



Issue: 1827

ROHS



Description: GNSS/2x LTE/0, 1x, 2x or 3x WiFi


Direct Mount


Series: RAZORBACK

PART NUMBER: RAZ32011DM, RAZ32012DM, RAZ42111DM, RAZ42112DM, RAZ52211DM, RAZ52212DM, RAZ62311DM, RAZ62312DM

CHARTS

GNSS LNA Gain and out-of-band rejection





GNSS

Passive Measurement Measured with 152mm (6") cable

Issue: 1827

ROHS

HS



Description: GNSS/2x LTE/0, 1x, 2x or 3x WiFi

Direct Mount

Series: RAZORBACK

PART NUMBER: RAZ32011DM, RAZ32012DM, RAZ42111DM, RAZ42112DM, RAZ52211DM, RAZ52212DM, RAZ62311DM, RAZ62312DM

PACKAGING

1pcs antennas per foam bag

6pcs antennas per package box

Total 6pcs antenna per package box

Package box: 558mm*386mm*210mm