## Amphenol <sup>Mfg by</sup> eavise Industrial UL 1977 Effortless & Arcless Din Connectors 160A/320A/430A CE @ c Avis

than normal for connecting and disconnecting

IB-16-2

Locking handle and lock

Locking collar

# **EFFORTLESSNESS**

Amphenol Industrial Operations (AIO) has partnered with Eaxtron who has designed a state of the art female contact. The patented Vortex Clip<sup>™</sup> significantly improves all aspects of the connection interface. Not only does the unique spiraling shape allow for more contact points, providing a higher rate of conductivity, it also facilitates coupling with eighty percent less effort than the industry standard!

## DURABILITY

Amphenol Industrial Operations / Eaxtron contacts are made from pure copper (Cu11 000) and plated with an industry leading 6um of silver. The plating ensures minimal wear and tear on the contact. Even more importantly the patented vortex clip significantly reduces coupling friction, further maximizing the lifetime of the contact.

Polyamide material guarantees robust performance in even the toughest of working conditions. These flexible handles are highly durable, so you can avoid the most common cause and cost of early replacement, broken handles.

By virtue of these innovations, the initial results of ongoing tests show that an AIO connector lasts up to twelve thousand cycles, more than double the industry standard.

### SAFETY

Amphenol Industrial Operations' product has Eaxtron designed and patented locking mechanisms that work in conjunction with the user to provide an arcless experience. Additionally the unique design of the female contacts and durable housing nullifies all 'inevitable' arcs. When the connector is load bearing the patented design manages and safely disperses arcs within the connector carriage. All of this innovation allows the user to operate in a truly arcless environment, with none of the risks traditionally posed to both individuals and equipment.

The color coded system prevents non-compatible connection by clearly classifying by color different voltages and applications.

### **EFFICIENCY**



The Vortex Clip<sup>™</sup> guarantees a safer and easier connection, it also allows for a higher rate of conductivity.

The highly innovative contact loader, allows you to attach wired pilots, auxiliaries, and main contacts faster than ever before, directly to the connector.



Please contact us at eaxtron@amphenol-aio.com for more information.

## COLOR CODED CABLE CLAMPS

Identify battery voltages easily thanks to the color coded cable clamps. In addition to the coding pins, AIO's cable clamps allow you to track different battery voltages and types from a distance to avoid any mismatch in use.

Kit of Cable Clamp:

24 V	36 V	48 V	72 V	80 V
Red	Grey	Blue	Green	Black

The cap and bottom cable clamps are the same for males and females, and available for 160A, 320A and 430A connectors.

#### **RELIABLE: PREVENT CABLE DAMAGE**

AlO's cable clamps are also self-centering; they will maintain your wires in proper position and preserve the integrity of the cable.

Self-centering cable clamp

## **ONE LOADER FOR ALL OUR CONTACTS**

The clip on contact loader to make wiring the connectors easier. After crimping or soldering contacts to wires, one needs to only clip them (including auxiliaries, air tubes & pilot contacts) to the contact loader to be clipped securely as one in the housing. **Reliable. Safe & Easy.** 

Durable

Air tubes or pilot contacts





Everything you need comes ready with instructions for you or your customers to safely install the connectors. No additional adaption is required. Simply install, safely use & reliably trust these patented battery connectors.

#### LOCKING ADAPTOR

The locking adapter makes the handle interoperable and easily affixed on the Male or Female Connector & DSC Solution.









Please contact us at **eaxtron@amphenol-aio.com** for more information.



Auxillary contacts

© 2022 All Rights Reserved. Amphenol Industrial Operations

amphenol-industrial.com/eaxtron



# HOW TO ORDER

Connector (please choose one code per position, below)											
1	2		3		4		5		6		
Connector Kit	Current Capability		Co	ontact Gender	На	Indle Length	Handle			Wire Size	
	160	160 A	F	Female/ Vortex Clip™ Socket	S	Short (Female Only - Optional)	Н	Standard (Female Only - Required)	1/0	1/0 (50mm²)	Available for 160 and 320
К	320	320 A							2/0	2/0 (70mm²)	Available for 320 only
(Eaxtron Series)				Male/Pin		Left blank for Male/Pin Gender		3/0	3/0 (95mm²)		
	430	430 A	Μ	iviale/PIII		Len Diarik for M	ale/Plf	Genuer	4/0 4/0 (120mm²) Availab	Available for 320 and 430	

Example: K160M1/0 (Eaxtron Connector Plug Kit; 160A rated; Male Pin; 1/0 Wire Size); K320FSH4/0 (Eaxtron Connector Socket Kit; 320A rated; Female Socket; w/ Short Handle; 4/0 Wire Size); K320FH2/0 (Eaxtron Connector Socket Kit; 320A rated; Female Socket; Standard Handle; 2/0 Wire Size)

Cable Clamp and Accessories						
1	2			3		
Cable Clamp		(Color / Voltage) or Clamp Screws Current Capa				
	RD	Red= 24v	160	160 A		
	GY	Grey= 36v	320	320A / 430A		
	BE	Blue= 48v				
CC	GN					
(Eaxtron Cable Clamp)	BK	Black= 80v				
	Screws					
	1000 Standard Cable Clamp Screws (package of 50)					
	2000	Max Cable Screws- 320A connectors (package of 50)				
Examples: CCBK320 (Cable Clamp: Black 80V/ 320 Amps) or CC1000 (Standard Cample Clamp Screws)						

Examples: CCBK320 (Cable Clamp; Black 80V; 320 Amps) or CC1000 (Standard Cample Clamp Screws)

Handles								
	1		2					
	Handle Type	Current Capability						
LHDOR	Long Handle	160	160 A					
LPHDOR	Low Profile Short Orange Handle	320	320A / 430A					
LHM Handle								
Example: LPHDOR160 (Low Profile Short Orange Handle; 160 Amps)								

Contacts	
Part Number	Description
	Main Contacts
FMC1607	Female Main Contacts 160A, 50mm <sup>2</sup> AWG 1/0, (Pk of 2)
MMC1606	Male Main Contacts 160A, 50mm <sup>2</sup> AWG 1/0, (Pk of 2)
MMC3200	Male Main Contacts 320A, 50mm <sup>2</sup> AWG 1/0, (Pk of 2)
MMC3202	Male Main Contacts 320A, 70mm <sup>2</sup> AWG 2/0, (Pk of 2)
MMC3204	Male Main Contacts 320A, 95mm <sup>2</sup> AWG 3/0, (Pk of 2)
MMC3206	Male Main Contacts 320A, AWG 4/0, (Pk of 2)
	Auxiliary Pilot & Auxiliary Contacts
AXP1000	160A Male Auxiliary Pilot & Auxiliary Contacts Kit
AXP1001	160A Female Auxiliary Pilot & Auxiliary Contacts Kit
AXP1002	320A Male Auxiliary Pilot & Auxiliary Contacts Kit
AXP1003	320A Female Auxiliary Pilot & Auxiliary Contacts Kit

	Access	ories						
		1	2					
	A	ccesory	Current	t Capability				
	CL	Contact Loader	160	160 A				
	MH	Male Housing	320	320A / 430A				
	FH	Female Housing						
	CV	Locking Collar						
	Example: CL160 (Contact Loader; 160 Amps)							
	Double Stack Connector Kits							
	Part N	umber	Descrip	otion				
	DSC	KITP	DSC Plu	ıg Kit				
	DSC	KITS	DSC Soc	ket Kit				
	NOTE: For prop OSHA Plate	er assembly, DSC Kits m	ust be purchase	d together with an				
		Coding I	Keys					
	Part N	umber	Descrip	otion				
	CK1000 Coding Keys, (Pk of 12)							
Tools								
Pa	rt Number		Descriptio	on				
	OSHA		OSHA Pla	te				

Hand Crimping Tool with Full Set of 6W-Dies



Please contact us at eaxtron@amphenol-aio.com for more information.

CCT1000