# **GRM0335C1E330JD01**# "#" indicates a package specification code.














Date of discontinuation: 31 Mar 2014

< List of part numbers with package codes > GRM0335C1E330JD01D , GRM0335C1E330JD01W , GRM0335C1E330JD01J

### Shape



#### Notes

Please use replacements or Recommended.

#### References

Packaging	Specifications	Minimum quantity
D	$_{\Psi}$ 180mm Paper taping	15000
J	φ 330mm Paper taping	50000
W	φ 180mm Paper taping (W8P1*)  * Width: 8mm, Pocket pitch: 1mm	30000

Mass (typ.)		
1 piece	0.33mg	
φ 180mm Reel	118g	

## Specifications

Capacitance	33pF ±5%
Rated voltage	25Vdc
Temperature characteristics (complied standard)	COG(EIA)
Temperature coefficient	0±30ppm/°C
Temperature range of temperature characteristics	25 to 125℃
Operating temperature range	-55 to 125℃

1 of 1



1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$ 

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

