

Thermomagnetic device circuit breaker - TMC 62C 0,5A - 0902166

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



Thermomagnetic circuit breaker, two-pole, 0.5 A thermal trip. DIN rail mounted and UL 1077-recognized with optional auxiliary contact for either S or H remote signal. Protects wiring and equipment from overcurrent and short circuit faults

Key commercial data

Packing unit	1 pc
Minimum order quantity	6 pc
Weight per Piece (excluding packing)	264.6 GRM
Custom tariff number	85362010
Country of origin	Hungary

Technical data

Product type	Thermomagnetic device circuit breakers
Approval	CSA
	UL Recognized
	cUL Recognized
	cULus Recognized
Mounting type	DIN rail: 35 mm
Nominal current I _N	0.5 A

Classifications

eCl@ss

eCl@ss 4.0	27141116
eCl@ss 4.1	27141116
eCl@ss 5.0	27141116
eCl@ss 5.1	27141116
eCl@ss 6.0	27141116
eCl@ss 7.0	27141116
eCl@ss 8.0	27141116



Thermomagnetic device circuit breaker - TMC 62C 0,5A - 0902166

Classifications

ETIM

ETIM 3.0	EC000899
ETIM 4.0	EC000899
ETIM 5.0	EC000899

UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121411
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121411

Approvals

Approvals

Approvals

 ${\sf CSA\ /\ UL\ Recognized\ /\ cUL\ Recognized\ /\ cULus\ Recognized}$


Ex Approvals

Approvals submitted

Approval details



UL Recognized **\$\)**





Thermomagnetic device circuit breaker - TMC 62C 0,5A - 0902166

Approvals

cULus Recognized Sus

Accessories

Accessories

Bridge

Wiring bridge - MPB 18/1- 3 - 2809212



Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 3-pos.

Thermomagnetic device circuit breaker - TMC 6LOCKOUT - 0902467

Locking element for TMC 6 circuit breakers

© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com