# 9080GR612

Terminal block, Linergy, box lug connector, 12 block assembly, natural color, 60A, 600 V



#### Main

Range of Product	9080G
Product Type	Terminal block
Color	Natural

Complementary

Voltage Rating	600 V AC/DC
Current Rating	60 A UL
	60 A CSA
Assemblies Consist of	1 end barrier
	2 end clamp(s)
	12 terminal blocks
	1 mounting track
Wire Size	AWG 22AWG 8 copper
Mounting Type	9080GH track
Certifications	CE
	CSA file 62144 class 6228 01
	UL recognized E60616 CCN XCFR2
Protection Type	Fingersafe DIN 57470
Ambient Air Temperature for Operation	-40257 °F (-40125 °C)
Electrical Connrection Tightening Torque	Lug copper 1820 lbf.in (2.032.26 N.m) : AWG 22AWG 8 copper)
Height	1.82 in (46.23 mm)
Width	1.72 in (43.69 mm)
Depth	6 in (152.40 mm)

### Ordering and shipping details

Category	21702-9080 G (NOT GCB)	
Discount Schedule	CP5	
GTIN	785901958604	
Nbr. of units in pkg.	1	
Package weight(Lbs)	19.20 oz (544.311 g)	
Returnability	No	
Country of origin	MX	

## **Packing Units**

Unit Type of Package 1	PCE	
Package 1 Height	1.81 in (4.6 cm)	
Package 1 width	1.73 in (4.4 cm)	
Package 1 Length	5.98 in (15.2 cm)	

# Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	exemption information	
China RoHS Regulation	☐ China RoHS Declaration	
PVC free	Yes	

### Contractual warranty

14/	40 months
vvarranty	18 months