


P-Channel 20-V (D-S) MOSFET with Schottky Diode

PRODUCT SUMMARY			
V _{DS} (V)	R _{DS(on)} (Ω)	I _D (A) ^a	Q _g (Typ.)
- 20	0.215 at V _{GS} = - 4.5 V	- 2	2.6 nC
	0.320 at V _{GS} = - 2.5 V	- 2	

SCHOTTKY PRODUCT SUMMARY		
V _{KA} (V)	V _f (V) Diode Forward Voltage	I _F (A) ^a
30	0.44 at 1 A	2




FEATURES

- Halogen-free According to IEC 61249-2-21 Definition
- LITTLE FOOT® Plus Schottky
- 100 % R_g Tested
- Compliant to RoHS Directive 2002/95/EC



APPLICATIONS

- Load Switch for Portable Devices
- DC/DC Buck Converter



P-Channel MOSFET

Ordering Information: Si4829DY-T1-E3 (Lead (Pb)-free)
Si4829DY-T1-GE3 (Lead (Pb)-free and Halogen-free)

ABSOLUTE MAXIMUM RATINGS T_A = 25 °C, unless otherwise noted

Parameter	Symbol	Limit	Unit
Drain-Source Voltage (MOSFET)	V _{DS}	- 20	V
Reverse Voltage (Schottky)	V _{KA}	30	
Gate-Source Voltage (MOSFET)	V _{GS}	± 12	
Continuous Drain Current (T _J = 150 °C) (MOSFET)	T _C = 25 °C	I _D	A
	T _C = 70 °C		
	T _A = 25 °C		
	T _A = 70 °C		
Pulsed Drain Current (MOSFET)	I _{DM}	- 7	
Continuous Source-Drain Diode Current (MOSFET Diode Conduction)	T _C = 25 °C	I _S	
	T _A = 25 °C		
Average Forward Current (Schottky)	I _F	2 ^b	
Maximum Power Dissipation (MOSFET)	T _C = 25 °C	P _D	W
	T _C = 70 °C		
	T _A = 25 °C		
	T _A = 70 °C		
Maximum Power Dissipation (Schottky)	T _C = 25 °C		
	T _C = 70 °C		
	T _A = 25 °C		
	T _A = 70 °C		
Operating Junction and Storage Temperature Range	T _J , T _{stg}	- 55 to 150	°C

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Typical	Maximum	Unit
Maximum Junction-to-Ambient (MOSFET) ^{b, f}	R_{thJA}	55	62.5	$^{\circ}\text{C}/\text{W}$
Maximum Junction-to-Foot (Drain) (MOSFET)	R_{thJF}	30	40	
Maximum Junction-to-Ambient (Schottky) ^{b, g}	R_{thJA}	57	75	
Maximum Junction-to-Foot (Drain) (Schottky)	R_{thJF}	42	55	

Notes:

- a. Package limited.
- b. Surface Mounted on 1" x 1" FR4 board.
- c. t = 10 s.
- f. Maximum under Steady State conditions is 110 $^{\circ}\text{C}/\text{W}$.
- g. Maximum under Steady State conditions is 110 $^{\circ}\text{C}/\text{W}$.

SPECIFICATIONS $T_J = 25^{\circ}\text{C}$, unless otherwise noted

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Static						
Drain-Source Breakdown Voltage	V_{DS}	$V_{GS} = 0 \text{ V}, I_D = - 250 \mu\text{A}$	- 20			V
V_{DS} Temperature Coefficient	$\Delta V_{DS}/T_J$	$I_D = - 250 \mu\text{A}$		- 19		$\text{mV}/^{\circ}\text{C}$
$V_{GS(\text{th})}$ Temperature Coefficient	$\Delta V_{GS(\text{th})}/T_J$			3		
Gate-Source Threshold Voltage	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}, I_D = - 250 \mu\text{A}$	- 0.6		- 1.5	V
Gate-Source Leakage	I_{GSS}	$V_{DS} = 0 \text{ V}, V_{GS} = \pm 12 \text{ V}$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = - 20 \text{ V}, V_{GS} = 0 \text{ V}$			- 1	μA
		$V_{DS} = - 20 \text{ V}, V_{GS} = 0 \text{ V}, T_J = 55^{\circ}\text{C}$			- 10	
On-State Drain Current ^a	$I_{D(\text{on})}$	$V_{DS} \leq - 5 \text{ V}, V_{GS} = - 10 \text{ V}$	- 7			A
Drain-Source On-State Resistance ^a	$R_{DS(\text{on})}$	$V_{GS} = - 4.5 \text{ V}, I_D = - 2.5 \text{ A}$		0.175	0.215	Ω
		$V_{GS} = - 2.5 \text{ V}, I_D = - 1.0 \text{ A}$		0.260	0.320	
Forward Transconductance ^a	g_{fs}	$V_{DS} = - 10 \text{ V}, I_D = - 2.5 \text{ A}$		5		S
Dynamic^b						
Input Capacitance	C_{iss}	$V_{DS} = - 10 \text{ V}, V_{GS} = 0 \text{ V}, f = 1 \text{ MHz}$		210		pF
Output Capacitance	C_{oss}			55		
Reverse Transfer Capacitance	C_{rss}			40		
Total Gate Charge	Q_g	$V_{DS} = - 10 \text{ V}, V_{GS} = - 10 \text{ V}, I_D = - 2.5 \text{ A}$		5.2	8	nC
Gate-Source Charge	Q_{gs}	$V_{DS} = - 10 \text{ V}, V_{GS} = - 4.5 \text{ V}, I_D = - 2.5 \text{ A}$		2.6	4	
Gate-Drain Charge	Q_{gd}			0.53		
Gate Resistance	R_g			0.9		
Turn-On Delay Time	$t_{d(\text{on})}$	$V_{DD} = - 10 \text{ V}, R_L = 5 \Omega$ $I_D \approx - 2 \text{ A}, V_{GEN} = - 4.5 \text{ V}, R_g = 1 \Omega$		7	14	Ω
Rise Time	t_r			20	30	
Turn-Off Delay Time	$t_{d(\text{off})}$			45	70	
Fall Time	t_f			15	25	
Turn-On Delay Time	$t_{d(\text{on})}$			10	15	
Rise Time	t_r			5	10	
Turn-Off Delay Time	$t_{d(\text{off})}$	$V_{DD} = - 10 \text{ V}, R_L = 5 \Omega$ $I_D \approx - 2 \text{ A}, V_{GEN} = - 10 \text{ V}, R_g = 1 \Omega$		12	20	ns
Fall Time	t_f			15	25	
				10	15	

SPECIFICATIONS $T_J = 25^\circ\text{C}$, unless otherwise noted

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Drain-Source Body Diode Characteristics						
Continuous Source-Drain Diode Current	I_S	$T_C = 25^\circ\text{C}$			- 2	A
Pulse Diode Forward Current	I_{SM}				- 7	
Body Diode Voltage	V_{SD}	$I_S = -2 \text{ A}, V_{GS} = 0 \text{ V}$		- 1	- 1.4	V
Body Diode Reverse Recovery Time	t_{rr}	$I_F = -2 \text{ A}, dI/dt = 100 \text{ A}/\mu\text{s}, T_J = 25^\circ\text{C}$		20	30	ns
Body Diode Reverse Recovery Charge	Q_{rr}			14	20	nC
Reverse Recovery Fall Time	t_a			14		ns
Reverse Recovery Rise Time	t_b			6		




Notes:



- a. Pulse test; pulse width $\leq 300 \mu\text{s}$, duty cycle $\leq 2\%$.
- b. Guaranteed by design, not subject to production testing.







SCHOTTKY SPECIFICATIONS $T_J = 25^\circ\text{C}$, unless otherwise noted






Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Forward Voltage Drop	V_F	$I_F = 1 \text{ A}$		0.36	0.44	V
		$I_F = 1 \text{ A}, T_J = 125^\circ\text{C}$		0.29	0.35	
Maximum Reverse Leakage Current	I_{rm}	$V_R = 20 \text{ V}$		0.025	0.200	mA
		$V_R = 20 \text{ V}, T_J = 75^\circ\text{C}$		0.41	4	
		$V_R = 20 \text{ V}, T_J = 125^\circ\text{C}$		5	50	
Junction Capacitance	C_T	$V_R = 15 \text{ V}$		60		pF



Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

SCHOTTKY TYPICAL CHARACTERISTICS $T_A = 25^\circ\text{C}$, unless otherwise noted**Reverse Current vs. Junction Temperature****Forward Voltage Drop****Capacitance**



SCHOTTKY TYPICAL CHARACTERISTICS $T_A = 25^\circ\text{C}$, unless otherwise noted

Normalized Thermal Transient Impedance, Junction-to-Ambient

Normalized Thermal Transient Impedance, Junction-to-Foot

MOSFET TYPICAL CHARACTERISTICS $T_A = 25^\circ\text{C}$, unless otherwise noted**Output Characteristics****Transfer Characteristics****On-Resistance vs. Drain Current and Gate Voltage****Capacitance****Gate Charge****On-Resistance vs. Junction Temperature**

MOSFET TYPICAL CHARACTERISTICS $T_A = 25^\circ\text{C}$, unless otherwise noted


MOSFET TYPICAL CHARACTERISTICS $T_A = 25^\circ\text{C}$, unless otherwise noted

* The power dissipation P_D is based on $T_{J(\text{max})} = 150^\circ\text{C}$, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

MOSFET TYPICAL CHARACTERISTICS $T_A = 25^\circ\text{C}$, unless otherwise noted

Normalized Thermal Transient Impedance, Junction-to-Ambient

Normalized Thermal Transient Impedance, Junction-to-Foot

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?68760.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.