NOTES:

I. MATERIALS AND FINISHES:

- BRASS, NICKEL PLATING

- BRASS, NICKEL PLATING RETAINING RING - BRASS, NICKEL PLATING WASHER - BRASS, NICKEL PLATING

COUPLING NUT - ZINC DIECAST
CONTACT - BRASS, GOLD PLATING
INSULATOR - DELRIN, NATURAL - SILICONE RUBBER, RED GASKET SPRING - BeCu, NICKEL PLATING

RESISTOR

## 2. ELECTRICAL:

COVER

A. IMPEDANCE: 75 OHM B. FREQUENCY RANGE: DC - 2 GHz

C. VSWR (RETURN LOSS): 1.30 (-17.692 dB), MAX.

D. D.W.V: 1500 VRMS, MIN.

## 3. MECHANICAL:


A. DURABILITY: 500 CYCLES MIN. B. TEMPERATURE RANGE: -40°C TO +85°C

## 4. PACKAGING:

A. QUANTITY: SINGLE PACK

B. MARKING: BAG TO BE MARKED


"AMPHENOL RF, 46650-75RFX, AND DATE CODE"



THIRD ANGLE PROJ. 🕀 🖯

REV

D



SCALE 2.200

## **CUSTOMER OUTLINE DRAWING**

REVISIONS

DATE

- -

13-Jul-06

04-May-15 50266

ECO

46154

APPR

- -

GΗ

HHE

DESCRIPTION

RELEASE TO MFG.

BAYONET WAS BRASS

REDRAWN IN PRO-E\RD-DMI504230IM

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE: <0.5mm 0.5 - 6mm 6 - 30mm 30 - 120mm ANGLES ±0.05mm ±0.1mm ±0.2mm ± 0.3mm ±1°	MATERIAL SEE NOTES	DRAWN M.ZHANG	DATE 22-Apr-15	TITLE BNC STR PLUG	Amphenol RF
NOTICE - These drawings, specifications, or other data (I) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they		ENGINEER K.CAPOZZI	DATE 25-Nov-14	TERMINATOR	www.amphenolrf.com
not to be regarded by implication or otherwise in any manner licensing, granting		APPROVED S.HSIEH	DATE 22-Apr-15	SCALE: 8.0:1.0 SHEET 2 OF 2	DRAWING NO.BI004BI-ND3G-75R-0.0I-IW  ITEM NO. 011004ABN00ND7F
product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.	CONFIGURATION LEVEL: In Work FINISH	CAD FILE		DWG SIZĖ REV B E	PART NO. 46650-75RFX