

High Speed, Precision JFET Input Operational Amplifier

FEATURES

- **Guaranteed** Slew Rate: 23V/ μ s Min
- **Guaranteed** Offset Voltage: 250 μ V Max
–55°C to 125°C: 750 μ V Max
- **Guaranteed** Drift: 5 μ V/°C Max
- **Guaranteed** Bias Current:
70°C, 180pA Max
125°C, 4nA Max
- Gain-Bandwidth Product: 8.5MHz Typ
- Settling Time to 0.05% (10V Step): 0.9 μ s Typ

APPLICATIONS

- Fast D/A Output Amplifiers (12, 14, 16 Bits)
- High Speed Instrumentation
- Fast, Precision Sample and Hold
- Voltage-to-Frequency Converters
- Logarithmic Amplifiers

DESCRIPTION

The LT®1022 JFET input operational amplifier combines high speed and precision performance.

A 26V/ μ s slew rate and 8.5MHz gain-bandwidth product are simultaneously achieved with offset voltage of typically 80 μ V, 1.5 μ V/°C drift, bias currents of 50pA at 70°C, 500pA at 125°C. The output delivers 20mA of load current without gain degradation.

The 250 μ V maximum offset voltage specification represents less than 1/2 least significant bit error in a 14-bit, 10V system.

The LT1022A meets or exceeds all OP-16A and OP-16E specifications. It is faster and more accurate without stability problems at cold temperatures.


The LT1022 can be used as the output amplifier for 12-bit current output D/A converters, as shown below.

For a more accurate, lower power dissipation, but slower JFET input op amp, please refer to the LT1055 data sheet.

 LTC and LT are registered trademarks of Linear Technology Corporation.

TYPICAL APPLICATION

12-Bit Voltage Output D/A Converter




$C_F = 15\text{pF TO } 33\text{pF}$

SETTLING TIME TO 2mV (0.8 LSB) = 1.5 μ s TO 2 μ s

LT1022 • TA01

Large-Signal Response



$A_V = 1$

$C_L = 100\text{pF}$

$T_A = 25^\circ\text{C}$

$V_S = \pm 15\text{V}$

ABSOLUTE MAXIMUM RATINGS

(Note 1)

Supply Voltage	$\pm 20V$
Differential Input Voltage	$\pm 40V$
Input Voltage	$\pm 20V$
Output Short Circuit Duration	Indefinite

Operating Temperature Range

LT1022AM/1022M (**OBsolete**) $-55^{\circ}C$ to $125^{\circ}C$ LT1022AC/1022C $0^{\circ}C$ to $70^{\circ}C$ Storage Temperature Range $-65^{\circ}C$ to $150^{\circ}C$ Lead Temperature (Soldering, 10 sec.) $300^{\circ}C$ **PACKAGE/ORDER INFORMATION**

TOP VIEW N/C	ORDER PART NUMBER	TOP VIEW	ORDER PART NUMBER				
BALANCE	LT1022AMH	1	8	N/C			
-IN	LT1022MH	2	7	V+			
+IN	LT1022ACH	3	6	OUT			
V-	LT1022CH	4	5	BAL			
METAL CAN H PACKAGE							
$T_{JMAX} = 150^{\circ}C$, $\theta_{JA} = 150^{\circ}C/W$, $\theta_{JC} = 45^{\circ}C/W$							
OBSoLETE PACKAGE		N8 PACKAGE 8-LEAD PDIP					
Consider the N8 Package as an Alternate Source		$T_{JMAX} = 100^{\circ}C$, $\theta_{JA} = 130^{\circ}C/W$					
LT1022 • P0101							

Consult LTC Marketing for parts specified with wider operating temperature ranges.

ELECTRICAL CHARACTERISTICS $V_S = \pm 15V$, $T_A = 25^{\circ}C$, $V_{CM} = 0V$ unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS	LT1022AM LT1022AC			LT1022M, LT1022CH LT1022CN8			UNITS
			MIN	TYP	MAX	MIN	TYP	MAX	
V_{OS}	Input Offset Voltage (Note 2)	H Package N8 Package	80	250		100	600		μV
						160		1000	μV
I_{OS}	Input Offset Current	Fully Warmed Up	2	10		2	20		pA
I_B	Input Bias Current	Fully Warmed Up $V_{CM} = +10V$	± 10 30	± 50 100		± 10 30	± 50 150		pA
	Input Resistance—Differential —Common Mode	$V_{CM} = -11V$ to $8V$ $V_{CM} = 8V$ to $11V$	10^{12} 10^{12} 10^{11}			10^{12} 10^{12} 10^{11}			Ω
	Input Capacitance		4			4			pF
ϵ_n	Input Noise Voltage	0.1Hz to 10Hz	2.5			2.8			$\mu V/\sqrt{Hz}$
ϵ_n	Input Noise Voltage Density	$f_0 = 10Hz$ (Note 3) $f_0 = 1kHz$ (Note 4)	28 14	50 20		30 15	60 22		nV/\sqrt{Hz}
i_n	Input Noise Current Density	$f_0 = 10Hz, 1kHz$ (Note 5)	1.8	4		1.8	4		fA/ \sqrt{Hz}
A_{VOL}	Large Signal Voltage Gain	$V_0 = \pm 10V$ $R_L = 2k$ $R_L = 1k$	150 130	400 300		120 100	400 300		V/mV
	Input Voltage Range		± 10.5	± 12		± 10.5	± 12		V
CMRR	Common-Mode Rejection Ratio	$V_{CM} = \pm 10.5V$	86	94		82	92		dB
PSRR	Power Supply Rejection Ratio	$V_S = \pm 10V$ to $\pm 18V$	88	104		86	102		dB
V_{OUT}	Output Voltage Swing	$R_L = 2k$	± 12	± 13.2		± 12	± 13.2		V
SR	Slew Rate		23	26		18	24		V/ μs

1022fa

ELECTRICAL CHARACTERISTICS $V_S = \pm 15V$, $T_A = 25^\circ C$, $V_{CM} = 0V$ unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS	LT1022AM LT1022AC			LT1022M, LT1022CH LT1022CN8			UNITS
			MIN	Typ	MAX	MIN	Typ	MAX	
GBW	Gain-Bandwidth Product	$f = 1MHz$		8.5			8.0		MHz
I_S	Supply Current			5.2	7.0		5.2	7.0	mA
	Settling Time	$A = +1$ or $A = -1$ 10V Step to 0.05% 10V Step to 0.02%		0.9			0.9		μs
				1.3			1.3		μs
	Offset Voltage Adjustment Range	$R_{POT} = 100k$		± 7			± 7		mV

The ● denotes the specifications which apply over the full operating temperature range of $V_{CM} = 0V$, $0^\circ C \leq T_A \leq 70^\circ C$. $V_S = \pm 15V$, unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS	LT1022AC			LT1022CH LT1022CN8			UNITS
			MIN	Typ	MAX	MIN	Typ	MAX	
V_{OS}	Input Offset Voltage (Note 2)	H Package N8 Package	● ●	140	480		180 300	1000 1700	μV μV
	Average Temperature Coefficient of Input Offset Voltage	H Package N8 Package (Note 6)	● ●	1.3	5.0		1.8 3.0	9.0 15.0	$\mu V/^\circ C$ $\mu V/^\circ C$
I_{OS}	Input Offset Current	Warmed Up, $T_A = 70^\circ C$	●	15	80		18	100	pA
I_B	Input Bias Current	Warmed Up, $T_A = 70^\circ C$	●	± 50	± 200		± 60	± 250	pA
A_{VOL}	Large-Signal Voltage Gain	$V_0 = \pm 10V$, $R_L = 2k$	●	80	250		60	250	V/mV
CMRR	Common Mode Rejection Ratio	$V_{CM} = \pm 10.4V$	●	85	93		80	91	dB
PSRR	Power Supply Rejection Ratio	$V_S = \pm 10V$ to $\pm 18V$	●	86	103		84	101	dB
V_{OUT}	Output Voltage Swing	$R_L = 2k$	●	± 12	± 13.1		± 12	± 13.1	V

The ● denotes the specifications which apply over the full operating temperature range of $-55^\circ C \leq T_A \leq 125^\circ C$. $V_S = \pm 15V$, $V_{CM} = 0V$, unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS	LT1022AM			LT1022M			UNITS
			MIN	Typ	MAX	MIN	Typ	MAX	
V_{OS}	Input Offset Voltage (Note 2)	(Note 2)	●	230	750		300	1500	μV
	Average Temperature Coefficient of Input Offset Voltage	(Note 6)	●	1.5	5.0		2.0	9.0	$\mu V/^\circ C$
I_{OS}	Input Offset Current	Warmed Up, $T_A = 125^\circ C$	●	0.3	2.0		0.30	3.0	nA
I_B	Input Bias Current	Warmed Up, $T_A = 125^\circ C$	●	± 0.5	± 4.0		± 0.7	± 6.0	nA
A_{VOL}	Large Signal Voltage Gain	$V_0 = \pm 10V$, $R_L = 2k$	●	40	120		35	120	V/mV
CMRR	Common-Mode Rejection Ratio	$V_{CM} = \pm 10.4V$	●	85	92		80	90	dB
PSRR	Power Supply Rejection Ratio	$V_S = \pm 10V$ to $\pm 17V$	●	86	102		84	100	dB
V_{OUT}	Output Voltage Swing	$R_L = 2k$	●	± 12	± 12.9		± 12	± 12.9	V

Note 1: Absolute Maximum Ratings are those values beyond which the life of a device may be impaired.

Note 2: Offset voltage is measured under two different conditions:

- (a) approximately 0.5 seconds after application of power;
- (b) at $T_A = 25^\circ C$, with the chip self-heated to approximately $45^\circ C$ to account for chip temperature rise when the device is fully warmed up.

Note 3: 10Hz noise voltage density is sample tested on every lot of A grades. Devices 100% tested at 10Hz are available on request.







Note 4: This parameter is tested on a sample basis only.

Note 5: Current noise is calculated from the formula: $i_n = (2qI_B)^{1/2}$, where $q = 1.6 \cdot 10^{-19}$ coulomb. The noise of source resistors up to $1G\Omega$ swamps the contribution of current noise.

Note 6: Offset voltage drift with temperature is practically unchanged when the offset voltage is trimmed to zero with a 100k potentiometer between the balance terminals and the wiper tied to V^+ . Devices tested to tighter drift specifications are available on request.

1022fa

TYPICAL PERFORMANCE CHARACTERISTICS



The typical behavior of many LT1022 parameters is identical to the LT1056. Please refer to the LT1055/1056 data sheet for the following typical performance characteristics:

Input Bias and Offset Currents vs Temperature

Input Bias Current Over the Common-Mode Range

Distribution of Input Offset Voltage (H and N8 Package)

Distribution of Offset Voltage Drift with Temperature

Warm-Up Drift

Long Term Drift of Representative Units

0.1Hz to 10Hz Noise

Voltage Noise vs Frequency

Noise vs Chip Temperature

Short Circuit Current vs Time

Output Impedance vs Frequency

Common Mode Range vs Temperature

Common Mode and Power Supply Rejections vs Temperature

Common Mode Rejection Ratio vs Frequency

Power Supply Rejection Ratio vs Frequency

Voltage Gain vs Temperature

Supply Current vs Supply Voltage

Output Swing vs Load Resistance

APPLICATIONS INFORMATION


The LT1056 applications information is directly applicable to the LT1022. Please consult the LT1055/1056 data sheet for details on:

- (1) plug-in compatibility to industry standard devices
- (2) offset nulling
- (3) achieving picoampere/microvolt performance

- (4) phase-reversal protection
- (5) high speed operation (including settling time test circuit)
- (6) noise performance
- (7) simplified circuit schematic

TYPICAL APPLICATIONS


Fast Piezoelectric Accelerometer



LT1022 • TA03


TYPICAL APPLICATIONS

10Hz to 1MHz Voltage-to-Frequency Converter



TYPICAL APPLICATIONS

PIN Photodiode-to-Frequency Converter



SCALE FACTOR =
1nW/Hz AT 900 NANOMETERS FROM 20nW TO 2mW

= HEWLETT PACKARD PHOTODIODE HP5082-4204

= 1N4148


[†]POLYSTYRENE

* SELECT VALUE FOR 2mW IN = 2MHz OUT

LT1022 • TA05


TYPICAL APPLICATIONS

Wide Bandwidth Absolute Value Circuit



LT1022 • TA06

Fast, Differential Input Current Source




*MATCH TO 0.01%
FULL-SCALE POWER BANDWIDTH
= 1MHz FOR $I_{OUT}R = 8V_{P-P}$
= 400kHz FOR $I_{OUT}R = 20V_{P-P}$
MAXIMUM $I_{OUT} = 10mA_{P-P}$
COMMON-MODE VOLTAGE AT LT1022 INPUT = $\frac{I_{OUTP-P} \cdot R_L}{2}$

LT1022 • TA07


TYPICAL APPLICATIONS

High Output Current Op Amp



LT1022 • TA08


Low Distortion Sine Wave Oscillator




LT1022 • TA09

TYPICAL APPLICATIONS

Fast, Precision Sample-And-Hold




PACKAGE DESCRIPTION



OBSOLETE PACKAGE

PACKAGE DESCRIPTION

N8 Package
8-Lead PDIP (Narrow .300 Inch)
(Reference LTC DWG # 05-08-1510)



*THESE DIMENSIONS DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS.
MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED 0.010 INCH (0.254mm)