Fuse Holder Datasheet

**Cartridge Fuse Holders** 0PTF0045M & 0PTF0050M Circuit Board Mountable





### **Product Dimensions (in mm)**



# **0PTF0050M** Panel min. 0,8 mm



## **Product Characteristics**

0PTF0045M / 0PTF0050M		
Compatible Fuses	5x20 mm	
Electrical Specifications	Rated Voltage: 250V	
	Rated Current: 10 A	
	Rated Power: 2.5W	
Materials	Molded Holder and Cap Body: Black PBT (UL94 V-0)	
	PCBTerminals: Tin plated brass	
Protection Class & Category	PC2 (IEC 60127-6)	
Contact Resistance	≤ 5mΩ	
Degree of Protection	IP 20	
IAmbient Temperature	-30 °C to 85 °C	

# **Ordering Information**

Ordering PN	Description	Packaging
0PTF0045M	Vertical Mount	1000 pieces, bulk pack
0PTF0050M	Horizontal Mount	1000 pieces, bulk pack
Note		

Panel minimum 0,8 mm and maximum 4,5 mm

### **Additional Information**







Resources

Accessories

Samples

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littlefuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at http://www.littelfuse.com/disclaimer-electronics

