



### OPTICALLY COUPLED BILATERAL SWITCH NON-ZERO CROSSING TRIAC



#### APPROVALS

- UL recognised, File No. E91231  
Package Code " KK "

#### 'X' SPECIFICATION APPROVALS

- VDE 0884 in 3 available lead form : -
  - STD
  - G form
  - SMD approved to CECC 00802

#### DESCRIPTION



The MOC3009,301\_ series are optically coupled isolators consisting of a Gallium Arsenide infrared emitting diode coupled with a light activated silicon bilateral switch performing the functions of a triac mounted in a standard 6 pin dual-in-line package.

#### FEATURE

- Options :-  
10mm lead spread - add G after part no.  
Surface mount - add SM after part no.  
Tape&reel - add SMT&R after part no.
- High Isolation Voltage (5.3kV<sub>RMS</sub>, 7.5kV<sub>PK</sub>)
- 250V Peak Blocking Voltage
- All electrical parameters 100% tested
- Custom electrical selections available

#### APPLICATIONS

- CRTs
- Power Triac Driver
- Motors
- Consumer appliances
- Printers



#### ABSOLUTE MAXIMUM RATINGS

(25 °C unless otherwise noted)

Storage Temperature	—	-55°C - +150°C
Operating Temperature	—	-40°C - +100°C
Lead Soldering Temperature	—	260°C (1.6mm from case for 10 seconds)

#### INPUT DIODE

Forward Current	—	50mA
Reverse Voltage	—	6V
Power Dissipation	—	70mW (derate linearly 0.93mW/°C above 25°C)

#### OUTPUT PHOTO TRIAC

Off-State Output Terminal Voltage	—	250V
Forward Current (Peak)	—	1A
Power Dissipation	—	300mW (derate linearly 4.0mW/°C above 25°C)

#### POWER DISSIPATION

Total Power Dissipation	—	330mW
	(derate linearly 4.4mW/°C above 25°C)	

#### ISOCOM COMPONENTS 2004 LTD

Unit 25B, Park View Road West,  
Park View Industrial Estate, Brenda Road  
Hartlepool, TS25 1UD England Tel:  
(01429)863609 Fax:(01429)863581 e-mail  
sales@isocom.co.uk http://www.isocom.com

**ELECTRICAL CHARACTERISTICS (  $T_A = 25^\circ\text{C}$  Unless otherwise noted )**


PARAMETER		MIN	TYP	MAX	UNITS	TEST CONDITION
Input	Forward Voltage ( $V_F$ ) Reverse Current ( $I_R$ )		1.2 100	1.5 $\mu\text{A}$	V $\mu\text{A}$	$I_F = 10\text{mA}$ $V_R = 6\text{V}$
Output	Peak Off-state Current ( $I_{DRM}$ ) Peak Blocking Voltage ( $V_{DRM}$ ) On-state Voltage ( $V_{TM}$ ) Critical rate of rise of off-state Voltage ( dv/dt ) ( note 1 ) Critical rate of rise of commutating Voltage ( dv/dt ) ( note 1 )	250	1.5	100 3.0	nA V V	$V_{DRM} = 250\text{V}$ ( note 1 ) $I_{DRM} = 100\text{nA}$ $I_{TM} = 100\text{mA}$ ( peak )
Coupled	Input Current to Trigger ( $I_{FT}$ )(note 2 ) MOC3009 MOC3010 MOC3011 MOC3012  Holding Current , either direction ( $I_H$ )  Input to Output Isolation Voltage $V_{ISO}$			30 15 10 5	mA mA mA mA	$V_D = 3\text{V}$ ( note 2 )
			100		$\mu\text{A}$	
		5300 7500			$V_{RMS}$ $V_{PK}$	See note 3 See note 3

Note 1. Test voltage must be applied within dv/dt rating.


Note 2. Guaranteed to trigger at an  $I_F$  value less than or equal to max.  $I_{FT}$ , recommended  $I_F$  lies between Rated  $I_{FT}$  and absolute max.  $I_{FT}$ .

Note 3. Measured with input leads shorted together and output leads shorted together.


**FIGURE 1**




**RMS On-state Current vs. Ambient Temperature**




**Normalised Repetitive Peak Off-state Voltage vs. Ambient Temperature**




**Forward Current vs. Ambient Temperature**



**Normalised Input Trigger Current vs. Ambient Temperature**



**On-state Voltage vs. Ambient Temperature**



**On-state Current vs. On-state Voltage**

