



POS.	Α	В	С	D	Е	F	G
15	1.213	0.984	0.644	0.756	0.311	0.090	0.496
	30.80	24.99	16.34	19.20	7.90	2.29	12.60
26	1.541	1.312	0.966	1.091	0.311	0.090	0.496
	39.15	33.32	24.53	27.70	7.90	2.29	12.60
44	2.087	1.852	1.512	1.618	0.311	0.090	0.496
	53.00	47.04	38.40	41.10	7.90	2.29	12.60
62	2.728	2.500	2.156	2.256	0.311	0.095	0.496
	69.30	63.50	54.76	57.30	7.90	2.41	12.60
78	2.079	2.406	2.057	2.169	0.429	0.095	0.606
	52.81	61.00	52.26	55.10	10.90	2.41	15.39





01 = .098" 4-40 CLINCH NUT (BOARD SIDE) 02 = .250" 4-40 CLINCH NUT (BOARD SIDE) 03 = .250" 4-40 CLINCH NUT (MATING SIDE) 91 = .225" 4-40 SPACER/BOARD LOCK

91 = .225" 4-40 SPACER/BOAF PLATING OPTIONS ——— 1 = GOLD FLASH

**ELECTRICALS:** 

**CURRENT RATING: 2 AMPS** 

CONTACT RESISTANCE: 15 mOHMS MAX. INSULATOR RESISTANCE: 1000MOHMS MIN.

VOLTAGE: 500V FOR 1 MINUTE TEMPERATURE: -50° TO +100°

**MATERIALS:** 

SHELL: STEEL, TIN PLATED

INSULATOR: PBT - BLACK (UL-94-VO)

## NOTE: WILL ACCEPT UP TO 24 AWG WIRE

