
PAF	PART NO. RF123F-SM							
REV	DESCRIPTION	DWN	DATE	APPROVED				
_	ENGINEERING RELEASE	CZS	09/14/17	JDMc				



SPECIFICATIONS:

IMPEDANCE: 50 Ohms

FREQUENCY RANGE: 0-3 GHz

<-155 dBc IN PCS BAND w/2+43 dB TONES WORKING VOLTAGE: 250 V rms @ sea level TEMPERATURE RANGE: -65°C TO 155°C

INSULATION RESISTANCE: 5k M Ohms min.

		ONLESS OTTENING	DE SI ECII IED.				
6	COUPLING NUT	1	BRASS	WHITE BRONZE	DIMENSIONS ARE IN INCHES		
5	RETAINING RING	1	SST	PASSIVATED	AND [MILLIMETERS]		
4	GASKET	1	RUBBER		DRAWN	09/14/17	
3	PIN	1	BeCu	SILVER	C. ZUNIGA	09/14/1/	
2	INSULATOR	1	PTFE		CHECKED		
1	BODY	1	BRASS	WHITE BRONZE	ORJ DRAWN		
#	DESCRIPTION	QTY	MATERIAL		C. ZUNIGA	09/14/17	

CUSTOMER OUTLINE DRAWING

ALL DIMENSIONS ARE REFERENCE ONLY

UNLESS OTHERWISE SPECIFIED:

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO RF INDUSTRIES, ANY UNAUTHORIZED USE OF THIS DRAWING IS EXPRESSLY PROHIBITED WITHOUT WRITTEN PERMISSION FROM RF INDUSTRIES, ANY VIOLATION IS PUNISHABLE UNDER U.S. COPYRIGHT LAWS.

PROPRIETARY AND CONFIDENTIAL

CONTROCTORSSAN DIEGO, CA 92126 (858) 549-6340 DIVISION OF RF INDUSTRIES, LTD. (858) 549-6345 FAX

RFINDUSTRIES.COM 7610 MIRAMAR RD.

SMA PLUG TO 1.0/2.3 JACK

ADAPTER

	SIZE	CABLE	GROUP	DWG NO				REV	
1	А	Ν	/A	RF123F-SM					_
٠ ا	SCALE	: NTS	ENGINEE	RING ID:	000000	SHEET	1	OF	1