Thermistor Probes and AssembliesThreaded

USP12755 Thermistor Probe




Description

Littelfuse offers Stainless probe assemblies suitable for a wide range of temperature sensing applications. If the dimensions and electrical characteristics on this product won't work for your requirements, please contact us for further assistance.


Features

- 5/16"-24 UNJF-3A Thread
- PVC Insulated Lead Wire
- 105°C Max Operating Temperature

Dimensions



Part Numbering System



Dimensions in inches.

Α	В	С	D
6.00"	0.650"	0.500"	0.188"
±0.750"	±0.030"	±0.035"	±0.005"

E	F	G
0.125" ±0.015"	Strip 0.250" ±0.070"	0.500" ±0.018" Hex

Note: Not all combinations of Part Number codes are available. Contact Littelfuse for details.

Specifications

Part	Resistance Ohms	R-T	Beta (K)	Temperature
Number	@25°C	Curve	25-85°C	Rating (°C)
USP12755	10000	E1	3435	-55 to +105

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littlefuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at: www.littlefuse.com/disclaimer-electronics