# Product data sheet Characteristics

## 9001KS53K5E11

selector switch Ø 30 - black - 3 positions - spring return both sides to center





Main	
Range of Product	Harmony 9001KS
Product or Component Type	Selector switch
Device short name	9001KS
Type of operator	Both sides to centre spring return
Operator profile	Black key switch

#### Complementary

- Compression y		
Bezel material	Chromium plated metal	
Mounting diameter	1.18 in (30 mm)	
Net Weight	0.54 lb(US) (0.245 kg)	
Shape of signaling unit head	Round	
Operator position information	3 positions	
Key number	E11	
Key withdrawal position	Center	
Contacts type and composition	Without contact block	
Mechanical durability	500000 cycles	
Device presentation	Basic element	

#### **Environment**

Protective treatment	TC	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-13158 °F (-2570 °C)	
Overvoltage category	Class II IEC 61140	
IP degree of protection	IP66 IEC 60529	
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3R NEMA 4 NEMA 6	
Standards	EN/IEC 60947-5-1 CSA C22.2 No 14 EN/IEC 60947-5-4 JIS C 852 EN/IEC 60947-1 JIS C 4520 UL 508	
Product Certifications	UL 508 NEMA	
Vibration resistance	7 gn 2500 Hz)IEC 60068-2-6	
Shock resistance	50 gn IEC 60068-2-27	

## Ordering and shipping details

Category	21426 - 9001 K (NOT KA,KM,KX)	
Discount Schedule	CS1	
GTIN	785901188193	
Nbr. of units in pkg.	1	
Package weight(Lbs)	8.00 oz (226.796 g)	
Returnability	No	
Country of origin	MX	

## Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	5.08 in (12.903 cm)	
Package 1 width	2.00 in (5.08 cm)	
Package 1 Length	12.90 in (32.774 cm)	

## Offer Sustainability

Green Premium product	
WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
☑ REACh Declaration	
Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration	
Yes	
€Yes	
China RoHS Declaration	
Product Environmental Profile	
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

#### Contractual warranty

- Contraction was and	
Warranty	18 months