VM1PTOQ

Hyde Park, ultrasonic sensor flat form + M18, Sn508mm, NO/NC, 12...24 VDC, M12





Main

Range of Product	Hyde Park
Sensor Type	Ultrasonic sensor
Series name	Virtu VM1
Device short name	VM1
Sensor design	Flat form + cylindrical M18
Type of sensing window	Adjustable
Material	Plastic
Enclosure Material	Valox
Front material	Glass epoxy
Type of output signal	Discrete
Discrete output function	1 NO or 1 NC programmable
Wiring Technique	4-wire
[Us] rated supply voltage	1224 V DC overload and short-circuit protection
Supply voltage limits	1028 V DC
Discrete output type	PNP
Electrical connection	Male connector M12 4 pins
Product Specific Application	-

Complementary

Complementary	
[Sn] nominal sensing distance	20.00 in (508 mm)
[Sd] sensing range	2.0020.00 in (50.8508 mm)
[Sa] assured operating distance	2.0020.00 in (50.8508 mm) remote teach push-button
Blind zone	0.002.01 in (051 mm)
Transmission frequency	300 kHz
Repeat accuracy	1.27 %
Beam angle	5 °
Minimum size of detected object	Cylinder diameter 2.5 mm - up to 200 mm sensing distance
Current Consumption	40 mA
Maximum switching current	100 mA reverse polarity protection
Resistance to electrostatic discharge	8 kV level 4 IEC 61000-4-2
Height	1.72 in (43.7 mm)
Width	0.71 in (18 mm)
Depth	1.72 in (43.7 mm)
Length	2.35 in (59.69 mm)
Net Weight	0.07 lb(US) (0.033 kg)

Environment

Product Certifications	UL	
Marking	CE	
NEMA degree of protection	NEMA 4X indoor use only)	
IP degree of protection	IP67	
Ambient Air Temperature for Operation	-22158 °F (-3070 °C)	
Ambient Air Temperature for Storage	-40185 °F (-4085 °C)	
Relative humidity	100 % without condensation	

Vibration resistance	+/-1 mm 1055 Hz)IEC 60068-2-6
Shock resistance	30 gn in all 3 axes 11 ms IEC 60068-2-27
Resistance to electromagnetic fields	9.14 V/m (10 V/m) level 3 IEC 61000-4-3
Resistance to fast transients	1 kV level 3 IEC 61000-4-4

Ordering and shipping details

0 11 0	
Category	22490-SENSORS-ULTRASONIC (XX5,6)
Discount Schedule	DS2
GTIN	785901624165
Nbr. of units in pkg.	1
Package weight(Lbs)	2.08 oz (58.967 g)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	3.31 in (8.415 cm)	
Package 1 width	0.50 in (1.27 cm)	
Package 1 Length	3.31 in (8.415 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEN RoHS
Mercury free	Yes
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
vvarianty	TO MONUS
•	