### Product data sheet Characteristics

## ABS7SC1B

plug-in solid state relay - 5 mm - output - 24 V DC - 2 A





#### Complementary

Response time	<= 0.01 ms from state 0 to 1 <= 0.4 ms from state 1 to 0
Product Compatibility	ABE7R16T111 ABE7P16M111 ABE7P16T111

#### Ordering and shipping details

Category	22375 - INTERFACE MODULE(ABA,R,S)	
Discount Schedule	CP2	
GTIN	3389110251487	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.18 oz (5 g)	
Returnability	No	
Country of origin	LV	

#### **Packing Units**

· coming cine	
Unit Type of Package 1	PCE
Package 1 Height	0.28 in (0.7 cm)
Package 1 width	0.94 in (2.4 cm)
Package 1 Length	5.94 in (15.1 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	4
Package 2 Weight	0.81 oz (23 g)
Package 2 Height	0.28 in (0.7 cm)
Package 2 width	0.94 in (2.4 cm)
Package 2 Length	5.94 in (15.1 cm)
Unit Type of Package 3	CAR
Number of Units in Package 3	4
Package 3 Weight	0.88 oz (25 g)
Package 3 Height	0.31 in (0.8 cm)
Package 3 width	5.91 in (15 cm)
Package 3 Length	0.98 in (2.5 cm)

### Offer Sustainability

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	<sup>☑</sup> China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

18 months

## Product data sheet Connections and Schema

# ABS7SC1B

### Internal Wiring Diagram

