

**STANLEY**


SINGLE COLOR LED

5mm Round Shape

**H-1000L / H-2000L / H-3000L**

HIGH BRIGHTNESS COLOR

Outline Dimensions



Unit: mm

## Absolute Maximum Ratings

(Ta=25°C)

Item	Symbol	Red				Units
		H (KR)				
Power Dissipation	Pd			125		mW
Forward Current	I <sub>F</sub>			50		mA
Peak Forward Current	I <sub>FM</sub>			300		mA
Reverse Voltage	V <sub>R</sub>			4		V
Operating Temperature	T <sub>opr</sub>			-30 to +85		°C
Storage Temperature	T <sub>stg</sub>			-30 to +100		°C
Derating (DC)*	I <sub>F</sub>			0.67		mA/°C

\* Ta=25°C, I<sub>fm</sub> applies for the pulse width 1msec. and duty cycle 1/20  
The current derating for operation applies when the temperature is above 25°C


## Electro-Optical Characteristics

\*The viewing angle is an average and will vary by color

(Ta=25°C)

Part No.	Material	Emitted Color	Lens Color	Luminous Intensity I <sub>V</sub>			Wavelength				Forward Voltage V <sub>F</sub>			Reverse Current I <sub>R</sub> MAX.	Viewing Angle (2 1/2)	
				MIN.	TYP.	I <sub>F</sub>	Peak P TYP.	Dominant d TYP.	Spectral Line Half Width		TYP.	MAX.	I <sub>F</sub>	TYP.		
H-3000L	GaAlAs	Red	Water Clear	2,400	3,000	20	660	647	25	20	1.8	2.5	20	100	4	10°
H-2000L				1,400	2,000	20	660	647	25	20	1.8	2.5	20	100	4	
H-1000L				700	1,000	20	660	647	25	20	1.8	2.5	20	100	4	
Units				mcd		mA	nm			mA	V		mA	μA	V	Deg.

## Spatial Distribution (x)



## Operation Current Derating Chart

