

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Y distributor, 8-position, shielded, Plug straight M12 SPEEDCON, A-coded, on Socket straight M12 SPEEDCON, A-coded and Socket straight M12 SPEEDCON, A-coded, Parallel distributor



Key Commercial Data

Packing unit	5 pc
GTIN	4 046356 577199
GTIN	4046356577199

Technical data

Dimensions

Center distance	21 mm
1	

Ambient conditions

Ambient temperature (operation)	-25 °C 90 °C (Plug / socket)
Degree of protection	IP65/IP67

General

Rated current at 40°C	2 A
Rated voltage	30 V AC
	30 V DC
Number of positions	8
Color handle area	black
Insulation resistance	≥ 100 MΩ
Coding	A - standard
Standards/regulations	M12 connector IEC 61076-2-101
Status display	No
Overvoltage category	II
Degree of pollution	3
Insertion/withdrawal cycles	≥ 100

09/07/2019 Page 1 / 7



Technical data

General Torque

Material		
Flammability rating according to UL 94	НВ	
Contact material	CuZn	
Contact surface material	Ni/Au	
Contact carrier material	TPU GF	
Material of grip body	TPU, hardly inflammable, self-extinguishing	

0.4 Nm (M12 connector)

Zinc die-cast, nickel-plated

Standards and Regulations

Standard designation	M12 connector
Standards/regulations	IEC 61076-2-101
Flammability rating according to UL 94	НВ

NBR

Environmental Product Compliance

PEACH SVHC	Load 7420 02 4
REACH SVHC	Lead 7439-92-1


Drawings

Material, knurls

Sealing material




Schematic diagram



Pin assignment M12 plug, 8-pos., A-coded, view plug side




Schematic diagram



Pin assignment M12 socket, 8-pos., A-coded, view female side




Dimensional drawing



M12 Y distributor







Contact assignment of the M12 Y distributor

Approvals

Approvals

Approvals


EAC

Ex Approvals

Approval details



Approvals



Phoenix Contact 2019 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com